

# Assignment 13

- 1) 1) Create a union of two queries that shows the names, cities, and ratings of all customers. Those with rating of 200 or greater will also have the words "High Rating", while the others will have the words "Low Rating".?

Ans→

```
select cname,city,rating ,concat(rating , ' high rating') from customers where rating >=200  
union select cname,city, rating,concat(rating,' low rating') from customers where rating<200 ;
```

```
Command Prompt - mysql -u + -  
+-----+-----+-----+-----+  
| Grass | Berlin | 300 | 300 high rating |  
| Cinsneros | San Jose | 300 | 300 high rating |  
| Hoffman | London | 100 | 100 low rating |  
| Clemens | London | 100 | 100 low rating |  
| Pereira | Rome | 100 | 100 low rating |  
| Alex | san | 50 | 50 low rating |  
| bob | rome | 50 | 50 low rating |  
+-----+-----+-----+-----+  
9 rows in set (0.00 sec)  
  
KD2_mrunali_86706@>select cname,city,rating ,concat(rating , ' high rating') from  
-> customers where rating >=200 union select cname,city, rating,concat(rating,  
-> ' low rating') from customers where rating<200 ;  
+-----+-----+-----+-----+  
| cname | city | rating | concat(rating , ' high rating') |  
+-----+-----+-----+-----+  
| Giovanni | Rome | 200 | 200 high rating |  
| Liu | San Jose | 200 | 200 high rating |  
| Grass | Berlin | 300 | 300 high rating |  
| Cinsneros | San Jose | 300 | 300 high rating |  
| Hoffman | London | 100 | 100 low rating |  
| Clemens | London | 100 | 100 low rating |  
| Pereira | Rome | 100 | 100 low rating |  
| Alex | san | 50 | 50 low rating |  
| bob | rome | 50 | 50 low rating |  
+-----+-----+-----+-----+  
9 rows in set (0.00 sec)  
  
KD2_mrunali_86706@>
```

27°C Cloudy 14:59 04-09-2024

2) Write a command that produces the name and number of each salesperson and each customer with more than one current order. Put the results in alphabetical order.?

Ans→

select snum,sname from salespeople where snum in

(select snum from orders group by snum having count(snum)>1)

union

select cnum,cname from customers where cnum in (select cnum from orders group by cnum having count(cnum)>1)order by snum,sname;

```
Command Prompt - mysql -u x + v
+-----+-----+-----+-----+-----+
| 2005 | Alex | san | 50 | 1008 |
+-----+-----+-----+-----+
6 rows in set (0.00 sec)

KD2_mrunali_86706@>select * from orders;
+-----+-----+-----+-----+-----+
| Onum | Amt | Odate | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3003 | 767.19 | 1990-10-03 | 2007 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3010 | 1309.95 | 1990-10-06 | 2004 | 1002 |
| 3005 | 0.00 | 1990-10-24 | 2005 | 1007 |
+-----+-----+-----+-----+-----+
9 rows in set (0.00 sec)

KD2_mrunali_86706@>select snum,sname from salespeople where snum in
-> (select snum from orders group by snum having count(snum)>1)
-> union
-> select cnum,cname from customers where cnum in (select cnum from orders group by cnum having count(cnum)>1)order by snum,sname;
+-----+-----+
| snum | sname |
+-----+-----+
| 1002 | Serres |
| 2004 | Grass |
| 2007 | Pereira |
| 2008 | Cinsneros |
+-----+-----+
4 rows in set (0.00 sec)

KD2_mrunali_86706@>
```

3) Form a union of three queries. Have the first select the snums of all salespeople in San Jose; the second, the cnums of all customers in San Jose; and the third the onums of all orders on October 3. Retain duplicates between the last two queries but eliminate any redundancies between either of them and the first. (Note: in the sample tables as given, there would be no such redundancy. This is besides the point.)?

Ans→select snum from salespeople where city='san jose'

Union select snum from customers where city='san jose'

Union

Select snum from orders where odate='1990-10-03';

```
Command Prompt - mysql -u x
KD2_mrunali_86706@>select snum from salespeople where city='san jose' union select snum from customers where city='san jose' union select snum from orders where odate='1990-10-3';
+-----+
| snum |
+-----+
| 1002 |
| 1100 |
| 1004 |
| 1007 |
| 1001 |
+-----+
5 rows in set (0.00 sec)

KD2_mrunali_86706@>select snum from salespeople where city='san jose'
-> union
-> select snum from customers where city='san jose'
-> union
-> select snum from orders where odate='1990-10-3';
+-----+
| snum |
+-----+
| 1002 |
| 1100 |
| 1004 |
| 1007 |
| 1001 |
+-----+
```