

## Assignment – 12

Using the operators IN, ANY, and ALL.

1) Write a query that selects all customers whose ratings are equal to or greater than ANY of Serres'.

```
KD3_86720_Raju@>select * from customers where rating >= any(select rating from customers where snum in(select snum from salespeople where sname='serres'));
```

Cnum	Cname	City	Rating	Snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

4 rows in set (0.01 sec)

2) Write a query using ANY or ALL that will find all salespeople who have no customers located in their city.

```
KD3_86720_Raju@>select * from salespeople where (snum,city)<> all(select snum,city from customers);
```

Snum	Sname	City	Comm
1004	Motika	London	0.11
1007	Rifkin	Barcelona	0.15
1003	Axelrod	New York	0.10

3 rows in set (0.00 sec)

Raju Kumar (rajukumar.bih12@gmail.com) is signed in

3) Write a query that selects all orders for amounts greater than any for the customers in London.

```
KD3_86720_Raju@>select * from orders where amt > any(select amt from orders
where cnum in (select cnum from customers where city = 'London'));
```

Onum	Amt	Odate	Cnum	Snum
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

```
7 rows in set (0.01 sec)
```

4) Write the above query using MIN or MAX

```
KD3_86720_Raju@>select * from orders where amt > any(select MIN(amt) from or
ders where cnum in (select cnum from customers where city = 'London'));
```

Onum	Amt	Odate	Cnum	Snum
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

```
7 rows in set (0.00 sec)
```