

ASSIGNMENT-7

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
KD3-99543-Arnav SELECT o.onum, c.cname
-> FROM customers c
-> INNER JOIN orders o
-> ON c.cnum = o.cnum;
```

onum	cname
3001	Cisneros
3003	Hoffman
3002	Pereira
3005	Liu
3006	Cisneros
3009	Giovanni
3007	Grass
3008	Clemens
3010	Grass
3011	Clemens

10 rows in set (0.00 sec)

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
KD3-99543-Arnav SELECT o.onum, c.cname, s.sname
-> FROM orders o
-> INNER JOIN customers c ON o.cnum = c.cnum
-> INNER JOIN salespeople s ON o.snum = s.snum;
```

onum	cname	sname
3003	Hoffman	Peel
3009	Giovanni	Axelrod
3005	Liu	Serres
3010	Grass	Serres
3007	Grass	Serres
3011	Clemens	Peel
3008	Clemens	Peel
3006	Cisneros	Rifkin
3001	Cisneros	Rifkin
3002	Pereira	Motika

10 rows in set (0.00 sec)

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
KD3-99543-Arnay SELECT c.cname,s.sname,s.comm FROM customers c
-> INNER JOIN salespeople s ON c.snum=s.snum
-> WHERE comm>0.12;
```

cname	sname	comm
Liu	Serres	0.13
Grass	Serres	0.13
Cisneros	Rifkin	0.15

3 rows in set (0.00 sec)

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
KD3-99543-Arnay
KD3-99543-Arnay SELECT o.onum,s.comm,s.comm*o.amt
-> FROM orders o
-> INNER JOIN customers c ON o.cnum=c.cnum
-> INNER JOIN salespeople s ON o.snum=s.snum
-> WHERE c.rating>100;
```

onum	comm	s.comm*o.amt
3010	0.13	40.2935
3007	0.13	9.8475
3005	0.13	670.8585
3006	0.15	164.7240
3001	0.15	2.8035
3009	0.10	171.3230

6 rows in set (0.01 sec)

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed.

```
KD3-99543-Arnay SELECT
-> s1.sname AS salesperson_1,
-> s2.sname AS salesperson_2,
-> s1.city
-> FROM salespeople s1
-> INNER JOIN salespeople s2 ON s1.city = s2.city
-> WHERE s1.snum < s2.snum;
```

salesperson_1	salesperson_2	city
Peel	Motika	London

1 row in set (0.01 sec)