Chandrakant Kumbhar -CDAC

SQL ASSIGNEMENT 1

```
mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
    '> ;
    '> ;
    '> ;
    '> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''
,'Red',19,'London');
;
;

INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('' at line 1
mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
Query OK, 6 rows affected (0.820 sec)
Records: 6  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM P
    -> SELECT * FROM P;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'S
ELECT * FROM P' at line 2
mysql> SELECT * FROM P;
+------+--------+-------+--------+--------+
| P#   | Pnamne | color | weight | city   |
+------+--------+-------+--------+--------+
| P1   | Nut    | Red   |     12 | London |
| P2   | Bolt   | Green |     17 | Paris  |
| P3   | Screw  | Blue  |     17 | Rome   |
| P4   | Screw  | Red   |     14 | London |
| P5   | Cam    | Blue  |     12 | Paris  |
| P6   | Cog    | Red   |     19 | London |
+------+--------+-------+--------+--------+
6 rows in set (0.005 sec)

mysql> |
```

```
mysql> INSERT INTO S VALUES(S1,'Smith',20,'London'),(S2,'Jones',10,'Paris'),(S3,'Blake',30,'Paris'),(S4,'Clark',20,'London'),(S5,'Adams',30,'Athens');
ERROR 1054 (42S22): Unknown column 'S1' in 'field list'
mysql> CREATE TABLE S(S# CHAR(5),Snamne CHAR(20),status SMALLINT,city CHAR(15));
    -> CREATE TABLE S(S# CHAR(5),Snamne CHAR(20),status SMALLINT,city CHAR(15));
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'C
REATE TABLE S(S# CHAR(5),Snamne CHAR(20),status SMALLINT,city CHAR(15))' at line 2
mysql> CREATE TABLE S(`S#` CHAR(5),Snamne CHAR(20),status SMALLINT,city CHAR(15));
ERROR 1050 (42S01): Table 's' already exists
mysql> INSERT INTO S VALUES(S1,'Smith',20,'London'),(S2,'Jones',10,'Paris'),(S3,'Blake',30,'Paris'),(S4,'Clark',20,'London'),(S5,'Adams',30,'Athens');
ERROR 1054 (42S22): Unknown column 'S1' in 'field list'
mysql> DROP TABLE S;
Query OK, 0 rows affected (1.050 sec)

mysql> CREATE TABLE S(`S#` CHAR(5),Snamne CHAR(20),status SMALLINT,city CHAR(15));
Query OK, 0 rows affected (1.040 sec)

mysql> INSERT INTO S VALUES(S1,'Smith',20,'London'),(S2,'Jones',10,'Paris'),(S3,'Blake',30,'Paris'),(S4,'Clark',20,'London'),(S5,'Adams',30,'Athens');
ERROR 1054 (42S22): Unknown column 'S1' in 'field list'
mysql> INSERT INTO S VALUES('S1','Smith',20,'London'),('S2','Jones',10,'Paris'),('S3','Blake',30,'Paris'),('S4','Clark',20,'London'),('S5','Adams',30,'Athen
s');
Query OK, 5 rows affected (0.785 sec)
Records: 5  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM S;
+------+--------+--------+--------+
| S#   | Snamne | status | city   |
+------+--------+--------+--------+
| S1   | Smith  |     20 | London |
| S2   | Jones  |     10 | Paris  |
| S3   | Blake  |     30 | Paris  |
| S4   | Clark  |     20 | London |
| S5   | Adams  |     30 | Athens |
+------+--------+--------+--------+
5 rows in set (0.005 sec)

mysql> CREATE TABLE P(`P#` CHAR(6),Pnamne CHAR(20),color CHAR(6),weight SMALLINT ,city CHAR(15));
Query OK, 0 rows affected (1.017 sec)

mysql> INSERT INTO P VALUES('Nut','Red',12,'London'),('Bolt','Green',17,'Paris'),('Screw','Blue',17,'Rome'),('Screw','Red',14,'London'),('Cam','Blue',12,'Pa
```

```
Administrator: Command Pro    Administrator: Windows Powe

mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
    '> ;
    '> ;
    '>
    '> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''
,'Red',19,'London');
;
;

INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('' at line 1
mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6','Cog','Red',19,'London');
Query OK, 6 rows affected (0.820 sec)
Records: 6  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM P
    -> SELECT * FROM P;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'S
ELECT * FROM P' at line 2
mysql> SELECT * FROM P;
+------+--------+-------+--------+--------+
| P#   | Pnamne | color | weight | city   |
+------+--------+-------+--------+--------+
| P1   | Nut    | Red   |     12 | London |
| P2   | Bolt   | Green |     17 | Paris  |
| P3   | Screw  | Blue  |     17 | Rome   |
| P4   | Screw  | Red   |     14 | London |
| P5   | Cam    | Blue  |     12 | Paris  |
| P6   | Cog    | Red   |     19 | London |
+------+--------+-------+--------+--------+
6 rows in set (0.005 sec)

mysql>
```

```
Administrator: Command Pro    Administrator: Windows Powe

| S5   | Adams  |     30 | Athens |
+------+--------+--------+--------+
5 rows in set (0.005 sec)

mysql> CREATE TABLE P(`P#` CHAR(6),Pnamne CHAR(20),color CHAR(6),weight SMALLINT ,city CHAR(15));
Query OK, 0 rows affected (1.017 sec)

mysql> INSERT INTO P VALUES('Nut','Red',12,'London'),('Bolt','Green',17,'Paris'),('Screw','Blue',17,'Rome'),('Screw','Red',14,'London'),('Cam','Blue',12,'Pa
ris'),('Cog','Red',19,'London');
ERROR 1136 (21S01): Column count doesn't match value count at row 1
mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
    '>
    '> ;
    '> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''
,'Red',19,'London');

;
INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2' at line 1
mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
    '> ;
    '> ;
    '>
    '> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''
,'Red',19,'London');
;
;

INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('' at line 1
mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6','Cog','Red',19,'London');
Query OK, 6 rows affected (0.820 sec)
Records: 6  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM P
    -> SELECT * FROM P;
```

```
('P5','Cam','Blue',12,'Paris'),('P6',Cog','Red',19,'London');
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''
,'Red',19,'London');
;
;
;

INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('' at line 1
mysql> INSERT INTO P VALUES('P1','Nut','Red',12,'London'),('P2','Bolt','Green',17,'Paris'),('P3','Screw','Blue',17,'Rome'),('P4','Screw','Red',14,'London'),
('P5','Cam','Blue',12,'Paris'),('P6','Cog','Red',19,'London');
Query OK, 6 rows affected (0.820 sec)
Records: 6  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM P
    -> SELECT * FROM P;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'S
ELECT * FROM P' at line 2
mysql> SELECT * FROM P;
+------+--------+-------+--------+--------+
| P#   | Pnamne | color | weight | city   |
+------+--------+-------+--------+--------+
| P1   | Nut    | Red   |     12 | London |
| P2   | Bolt   | Green |     17 | Paris  |
| P3   | Screw  | Blue  |     17 | Rome   |
| P4   | Screw  | Red   |     14 | London |
| P5   | Cam    | Blue  |     12 | Paris  |
| P6   | Cog    | Red   |     19 | London |
+------+--------+-------+--------+--------+
6 rows in set (0.005 sec)

mysql> DESCRIBE S;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| S#     | char(5)  | YES  |     | NULL    |       |
| Snamne | char(20) | YES  |     | NULL    |       |
| status | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
4 rows in set (0.038 sec)

mysql>
```

Administrator: Command Pro | Administrator: Windows Powe

```
mysql> SELECT * FROM P
    -> SELECT * FROM P;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'S
ELECT * FROM P' at line 2
mysql> SELECT * FROM P;
+------+--------+-------+--------+--------+
| P#   | Pnamne | color | weight | city   |
+------+--------+-------+--------+--------+
| P1   | Nut    | Red   |     12 | London |
| P2   | Bolt   | Green |     17 | Paris  |
| P3   | Screw  | Blue  |     17 | Rome   |
| P4   | Screw  | Red   |     14 | London |
| P5   | Cam    | Blue  |     12 | Paris  |
| P6   | Cog    | Red   |     19 | London |
+------+--------+-------+--------+--------+
6 rows in set (0.005 sec)

mysql> DESCRIBE S;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| S#     | char(5)  | YES  |     | NULL    |       |
| Snamne | char(20) | YES  |     | NULL    |       |
| status | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
4 rows in set (0.038 sec)

mysql> DESCRIBE P;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| P#     | char(6)  | YES  |     | NULL    |       |
| Pnamne | char(20) | YES  |     | NULL    |       |
| color  | char(6)  | YES  |     | NULL    |       |
| weight | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
5 rows in set (0.017 sec)

mysql>
```

Administrator: Command Pro | Administrator: Windows Powe

```
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| S#     | char(5)  | YES  |     | NULL    |       |
| Snamne | char(20) | YES  |     | NULL    |       |
| status | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
4 rows in set (0.038 sec)

mysql> DESCRIBE P;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| P#     | char(6)  | YES  |     | NULL    |       |
| Pnamne | char(20) | YES  |     | NULL    |       |
| color  | char(6)  | YES  |     | NULL    |       |
| weight | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
5 rows in set (0.017 sec)

mysql> CREATE TABLE J(`J#` CHAR(6) NOT NULL,Jnamne CHAR(10),city CHAR(15));
Query OK, 0 rows affected (1.038 sec)

mysql> INSERT INTO J VALUES('J1','Sorter','Paris'),('J2','Punch','Rome'),('J
3','Reader','Athens'),('J4','Console','Athens'),('J5','Collator','London'),(
'J6','Terminal','Oslo'),('J7','Tape','London');
Query OK, 7 rows affected (0.793 sec)
Records: 7  Duplicates: 0  Warnings: 0

mysql> DESCRIBE J;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| J#     | char(6)  | NO   |     | NULL    |       |
| Jnamne | char(10) | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
3 rows in set (0.018 sec)

mysql>
```

```
Administrator: Command Pro    Administrator: Windows Powe

| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| S#     | char(5)  | YES  |     | NULL    |       |
| Snamne | char(20) | YES  |     | NULL    |       |
| status | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
4 rows in set (0.038 sec)

mysql> DESCRIBE P;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| P#     | char(6)  | YES  |     | NULL    |       |
| Pnamne | char(20) | YES  |     | NULL    |       |
| color  | char(6)  | YES  |     | NULL    |       |
| weight | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
5 rows in set (0.017 sec)

mysql> CREATE TABLE J(`J#` CHAR(6) NOT NULL,Jnamne CHAR(10),city CHAR(15));
Query OK, 0 rows affected (1.038 sec)

mysql> INSERT INTO J VALUES('J1','Sorter','Paris'),('J2','Punch','Rome'),('J3','Reader','Athens'),('J4','Console','Athens'),('J5','Collator','London'),('J6'
,'Terminal','Oslo'),('J7','Tape','London');
Query OK, 7 rows affected (0.793 sec)
Records: 7  Duplicates: 0  Warnings: 0

mysql> DESCRIBE J;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| J#     | char(6)  | NO   |     | NULL    |       |
| Jnamne | char(10) | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
3 rows in set (0.018 sec)

mysql> |
```

```
Administrator: Command Pro    Administrator: Windows Powe

| P#     | char(6)  | YES  |     | NULL    |       |
| Pnamne | char(20) | YES  |     | NULL    |       |
| color  | char(6)  | YES  |     | NULL    |       |
| weight | smallint | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
5 rows in set (0.017 sec)

mysql> CREATE TABLE J(`J#` CHAR(6) NOT NULL,Jnamne CHAR(10),city CHAR(15));
Query OK, 0 rows affected (1.038 sec)

mysql> INSERT INTO J VALUES('J1','Sorter','Paris'),('J2','Punch','Rome'),('J3','Reader','Athens'),('J4','Console','Athens'),('J5','Collator','London'),('J6'
,'Terminal','Oslo'),('J7','Tape','London');
Query OK, 7 rows affected (0.793 sec)
Records: 7  Duplicates: 0  Warnings: 0

mysql> DESCRIBE J;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| J#     | char(6)  | NO   |     | NULL    |       |
| Jnamne | char(10) | YES  |     | NULL    |       |
| city   | char(15) | YES  |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
3 rows in set (0.018 sec)

mysql> SELECT * FROM J;
+----+----------+--------+
| J# | Jnamne   | city   |
+----+----------+--------+
| J1 | Sorter   | Paris  |
| J2 | Punch    | Rome   |
| J3 | Reader   | Athens |
| J4 | Console  | Athens |
| J5 | Collator | London |
| J6 | Terminal | Oslo   |
| J7 | Tape     | London |
+----+----------+--------+
7 rows in set (0.005 sec)

mysql> |
```

```
| J6 | Terminal | Oslo   |
| J7 | Tape     | London |
+----+----------+--------+
7 rows in set (0.005 sec)

mysql> SHOW DATABASES;
+--------------------+
| Database           |
+--------------------+
| classwork          |
| information_schema |
| performance_schema |
| spj                |
+--------------------+
4 rows in set (0.014 sec)

mysql> CREATE TABLE sp(S# CHAR(4) NOT NULL,P# CHAR(4) NOT NULL,J# CHAR(4) NOT NULL,QTY INT);
    ->
    ->
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''
 at line 1
mysql> CREATE TABLE sp(`S#` CHAR(4) NOT NULL,`P#` CHAR(4) NOT NULL,`J#` CHAR(4) NOT NULL,QTY INT);
Query OK, 0 rows affected (1.008 sec)

mysql> INSERT INTO sp VALUES('S1', 'P1', 'J1', 200), ('S1', 'P1', 'J4', 700), ('S2', 'P3', 'J1', 400), ('S2', 'P3', 'J2', 200), ('S2', 'P3', 'J3', 200), ('S
2', 'P3', 'J4', 500), ('S2', 'P3', 'J5', 600), ('S2', 'P3', 'J6', 400), ('S2', 'P3', 'J7', 800), ('S2', 'P5', 'J2', 100), ('S3', 'P3', 'J1', 200), ('S3', 'P
4', 'J2', 500), ('S4', 'P6', 'J3', 300), ('S4', 'P6', 'J7', 300), ('S5', 'P2', 'J2', 200), ('S5', 'P2', 'J4', 100), ('S5', 'P5', 'J5', 500), ('S5', 'P5', 'J
7', 100), ('S5', 'P6', 'J2', 200), ('S5', 'P1', 'J4', 100), ('S5', 'P3', 'J4', 200), ('S5', 'P4', 'J4', 800), ('S5', 'P5', 'J4', 400), ('S5', 'P6', 'J4', 50
0);
Query OK, 24 rows affected (0.778 sec)
Records: 24  Duplicates: 0  Warnings: 0

mysql>
```

```
mysql> INSERT INTO sp VALUES('S1', 'P1', 'J1', 200), ('S1', 'P1', 'J4', 700), ('S2', 'P3', 'J1', 400), ('S2', 'P3', 'J2', 200), ('S2', 'P3', 'J3', 200), ('S
2', 'P3', 'J4', 500), ('S2', 'P3', 'J5', 600), ('S2', 'P3', 'J6', 400), ('S2', 'P3', 'J7', 800), ('S2', 'P5', 'J2', 100), ('S3', 'P3', 'J1', 200), ('S3', 'P
4', 'J2', 500), ('S4', 'P6', 'J3', 300), ('S4', 'P6', 'J7', 300), ('S5', 'P2', 'J2', 200), ('S5', 'P2', 'J4', 100), ('S5', 'P5', 'J5', 500), ('S5', 'P5', 'J
7', 100), ('S5', 'P6', 'J2', 200), ('S5', 'P1', 'J4', 100), ('S5', 'P3', 'J4', 200), ('S5', 'P4', 'J4', 800), ('S5', 'P5', 'J4', 400), ('S5', 'P6', 'J4', 50
0);
Query OK, 24 rows affected (0.778 sec)
Records: 24  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM sp;
+----+----+----+------+
| S# | P# | J# | QTY  |
+----+----+----+------+
| S1 | P1 | J1 |  200 |
| S1 | P1 | J4 |  700 |
| S2 | P3 | J1 |  400 |
| S2 | P3 | J2 |  200 |
| S2 | P3 | J3 |  200 |
| S2 | P3 | J4 |  500 |
| S2 | P3 | J5 |  600 |
| S2 | P3 | J6 |  400 |
| S2 | P3 | J7 |  800 |
| S2 | P5 | J2 |  100 |
| S3 | P3 | J1 |  200 |
| S3 | P4 | J2 |  500 |
| S4 | P6 | J3 |  300 |
| S4 | P6 | J7 |  300 |
| S5 | P2 | J2 |  200 |
| S5 | P2 | J4 |  100 |
| S5 | P5 | J5 |  500 |
| S5 | P5 | J7 |  100 |
| S5 | P6 | J2 |  200 |
| S5 | P1 | J4 |  100 |
| S5 | P3 | J4 |  200 |
| S5 | P4 | J4 |  800 |
| S5 | P5 | J4 |  400 |
| S5 | P6 | J4 |  500 |
+----+----+----+------+
24 rows in set (0.005 sec)

mysql>
```

```
| S# | P# | J# | QTY  |
+----+----+----+------+
| S1 | P1 | J1 |  200 |
| S1 | P1 | J4 |  700 |
| S2 | P3 | J1 |  400 |
| S2 | P3 | J2 |  200 |
| S2 | P3 | J3 |  200 |
| S2 | P3 | J4 |  500 |
| S2 | P3 | J5 |  600 |
| S2 | P3 | J6 |  400 |
| S2 | P3 | J7 |  800 |
| S2 | P5 | J2 |  100 |
| S3 | P3 | J1 |  200 |
| S3 | P4 | J2 |  500 |
| S4 | P6 | J3 |  300 |
| S4 | P6 | J7 |  300 |
| S5 | P2 | J2 |  200 |
| S5 | P2 | J4 |  100 |
| S5 | P5 | J5 |  500 |
| S5 | P5 | J7 |  100 |
| S5 | P6 | J2 |  200 |
| S5 | P1 | J4 |  100 |
| S5 | P3 | J4 |  200 |
| S5 | P4 | J4 |  800 |
| S5 | P5 | J4 |  400 |
| S5 | P6 | J4 |  500 |
+----+----+----+------+
24 rows in set (0.005 sec)

mysql> DESCRIBE sp;
+-------+---------+------+-----+---------+-------+
| Field | Type    | Null | Key | Default | Extra |
+-------+---------+------+-----+---------+-------+
| S#    | char(4) | NO   |     | NULL    |       |
| P#    | char(4) | NO   |     | NULL    |       |
| J#    | char(4) | NO   |     | NULL    |       |
| QTY   | int     | YES  |     | NULL    |       |
+-------+---------+------+-----+---------+-------+
4 rows in set (0.020 sec)

mysql>
```

```
Query OK, 1 row affected (0.027 sec)

Query OK, 1 row affected (0.026 sec)

Query OK, 1 row affected (0.029 sec)

Query OK, 1 row affected (0.032 sec)

Query OK, 1 row affected (0.024 sec)

Query OK, 1 row affected (0.031 sec)

Query OK, 1 row affected (0.100 sec)

Query OK, 1 row affected (0.041 sec)

Query OK, 1 row affected (0.040 sec)

Query OK, 1 row affected (0.025 sec)

Query OK, 1 row affected (0.023 sec)

Query OK, 1 row affected (0.023 sec)

Query OK, 1 row affected (0.023 sec)

mysql> describe hr;
ERROR 1146 (42S02): Table 'sales.hr' doesn't exist
mysql> describe sales;
ERROR 1146 (42S02): Table 'sales.sales' doesn't exist
mysql> show tables;
+----------------+
| Tables_in_sales |
+----------------+
| customers      |
| orders         |
| salespeople    |
+----------------+
3 rows in set (0.781 sec)

mysql>
```

```
Administrator: Command Pro    Administrator: Windows Powe
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
mysql> USE sales;
Database changed
mysql> source E://gitsunbeam//dbt//dbs//sales-db.sql
Query OK, 0 rows affected, 1 warning (1.076 sec)

Query OK, 0 rows affected, 3 warnings (0.253 sec)

Query OK, 0 rows affected, 3 warnings (0.189 sec)

Query OK, 1 row affected (0.041 sec)

Query OK, 1 row affected (0.032 sec)

Query OK, 1 row affected (0.026 sec)

Query OK, 1 row affected (0.029 sec)

Query OK, 1 row affected (0.029 sec)

Query OK, 1 row affected (0.033 sec)
```

```
Administrator: Command Pro    Administrator: Windows Powe
Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.001 sec)

ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.003 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.003 sec)

Query OK, 0 rows affected (0.003 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.001 sec)

mysql> CREATE database sales;
Query OK, 1 row affected (0.867 sec)

mysql> source E://gitsunbeam//dbt//dbs//sales-db.sql
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
ERROR 1046 (3D000): No database selected
```

```
+--------------------+
| Database           |
+--------------------+
| classwork          |
| hr                 |
| information_schema |
| mysql              |
| performance_schema |
| spj                |
| sys                |
+--------------------+
7 rows in set (0.024 sec)

mysql> source E://gitsunbeam//dbt//dbs//new-hr-db.sql
Query OK, 0 rows affected (0.003 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.002 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.001 sec)

Query OK, 0 rows affected (0.001 sec)
```

```
+--------------------+
| classwork          |
| hr                 |
| information_schema |
| mysql              |
| performance_schema |
| sales              |
| spj                |
| sys                |
+--------------------+
8 rows in set (0.012 sec)

mysql> USE hr;
Database changed
mysql> show tables;
+--------------+
| Tables_in_hr |
+--------------+
| addr         |
| books        |
| countries    |
| customers    |
| departments  |
| dept         |
| depts        |
| emp          |
| emp_meeting  |
| employees    |
| emps         |
| job_history  |
| jobs         |
| locations    |
| meeting      |
| orders       |
| regions      |
| salespeople  |
| salgrade     |
+--------------+
19 rows in set (0.017 sec)

mysql>
```

1. How many orders data is present in the database?
   10
2. How many customers are present in the database?

   7

3. How many salespeople are present in the database?
   5
4. On which date order with highest amount is placed?
   1990-10-04
5. For which order salesman got maximum commission? Hint: you need to refer data of two tables.
   3001 and 3006
6. Which salesmen are handling more than two customers? Hint: you need to refer data of two tables.
   1002
7. Which city have single customer?
   berlin
8. Which city has multiple salespeople?
   Rome and san hose
9. What is name of customer and salesman of the maximum amount order?
   Clemens and peel
10. Study relationship between the tables in sales database.

    >>>Salesman Number is common (snum), between customers and orders.