

(DBT) ASSIGNMENT-06

1. Write a query that counts the number of salespeople registering orders for each day. (If a salesperson has more than one order on a given day, he or she should be counted only once.).

```
KD3-98839-Himanshu SELECT odate,COUNT(DISTINCT snum) FROM orders
-> GROUP BY odate;
+-----+-----+
| odate   | COUNT(DISTINCT snum) |
+-----+-----+
| 1990-10-03 | 4 |
| 1990-10-04 | 3 |
+-----+-----+
2 rows in set (0.00 sec)
```

2. Write a query on the Customers table that will find the highest rating in each city. Put the output in this form: For the city (city), the highest rating is: (rating).

```
KD3-98839-Himanshu SELECT CONCAT('For the city',' ',city,' ', 'highest rating is :',MAX(rating)) AS RATINGS FROM customers
-> GROUP BY city;
+-----+
| RATINGS |
+-----+
| For the city London , highest rating is :100 |
| For the city Rome , highest rating is :200 |
| For the city San Jose , highest rating is :300 |
| For the city Berlin , highest rating is :300 |
+-----+
4 rows in set (0.00 sec)
```

3 Write an SQL query to calculate the total order amount for each day and display the results in descending order of total orders.

```
KD3-98839-Himanshu SELECT odate, SUM(amt) FROM orders
-> GROUP BY odate
-> ORDER BY SUM(amt) DESC;
+-----+-----+
| odate   | SUM(amt) |
+-----+-----+
| 1990-10-04 | 16713.81 |
| 1990-10-03 | 8944.59 |
+-----+-----+
2 rows in set (0.00 sec)
```

4. Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the average amount of the order in the table. (Note Use the average amount value directly →2565.84)

```
KD3-98839-Himanshu SELECT snum, SUM(amt) FROM orders
-> GROUP BY snum
-> HAVING SUM(amt) > 2565.84;
+-----+-----+
| snum | SUM(amt) |
+-----+-----+
| 1001 | 15382.07 |
| 1002 | 5546.15 |
+-----+-----+
2 rows in set (0.01 sec)
```

5. Write a query that selects the highest rating in each city.

```
KD3-98839-Himanshu SELECT city,MAX(rating) FROM customers
-> GROUP BY city;
```

city	MAX(rating)
London	100
Rome	200
San Jose	300
Berlin	300

```
4 rows in set (0.00 sec)
```

6. Retrieve the maximum order amount for each salesperson from the orders table, including only those orders whose value exceeds Rs. 3000.

```
KD3-98839-Himanshu SELECT snum,MAX(amt) FROM orders
-> GROUP BY snum
-> HAVING MAX(amt) > 3000;
```

snum	MAX(amt)
1001	9891.88
1002	5160.45

```
2 rows in set (0.00 sec)
```

7. Write an SQL query to find the smallest order placed by every customer.

```
KD3-98839-Himanshu SELECT cnum,MIN(amt) FROM orders
-> GROUP BY cnum;
```

cnum	MIN(amt)
2008	18.69
2001	767.19
2007	1900.10
2003	5160.45
2002	1713.23
2004	75.75
2006	4723.00

```
7 rows in set (0.00 sec)
```