

ASSIGNMENT -02

Q1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
KD3-98843-Nandini> SELECT * FROM customers WHERE snum = 1001;
+-----+-----+-----+-----+-----+
| cnum | cname  | city  | rating | snum |
+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100    | 1001 |
| 2006 | Clemens | London | 100    | 1001 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

Q2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
KD3-98843-Nandini> SELECT rating, cname FROM customers WHERE city = 'San Jose';
+-----+-----+
| rating | cname |
+-----+-----+
| 200    | Liu   |
| 300    | Cisneros |
+-----+-----+
2 rows in set (0.00 sec)
```

Q3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
KD3-98843-Nandini> SELECT DISTINCT snum FROM orders;
+-----+
| snum |
+-----+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+-----+
5 rows in set (0.02 sec)
```

Q4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
KD3-98843-Nandini> SELECT * FROM orders WHERE amt > 1000.00;
+-----+-----+-----+-----+-----+
| onum | amt      | odate      | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

Q5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
KD3-98843-Nandini> SELECT sname, city FROM salespeople WHERE city = 'London' AND comm > 0.10;
+-----+-----+
| sname | city |
+-----+-----+
| Peel  | London |
| Motika | London |
+-----+-----+
2 rows in set (0.00 sec)
```

Q6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
KD3-98843-Nandini> SELECT * FROM customers WHERE rating > 100 OR city = 'Rome';
+-----+-----+-----+-----+-----+
| cnum | cname    | city      | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome      | 200    | 1003 |
| 2003 | Liu      | San Jose  | 200    | 1002 |
| 2004 | Grass    | Berlin    | 300    | 1002 |
| 2008 | Cisneros | San Jose  | 300    | 1007 |
| 2007 | Pereira  | Rome      | 100    | 1004 |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

Q7. What will be the output from the following query?

Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```
KD3-98843-Nandini> Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
+-----+-----+-----+-----+-----+
| onum | amt      | odate      | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69    | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19   | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45  | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23  | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75    | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00  | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95   | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88  | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

Q8. What will be the output of the following query?

Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;

```
KD3-98843-Nandini> Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
3 rows in set (0.02 sec)
```

Q9. What is a simpler way to write this query?

Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
KD3-98843-Nandini> SELECT snum, sname, city, comm FROM Salespeople WHERE comm BETWEEN 0.12 AND 0.14;
+-----+-----+-----+-----+
| snum | sname | city   | comm |
+-----+-----+-----+-----+
| 1001 | Peel  | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

Q10. Write a query that selects all orders except those with amount less than 100.

```
KD3-98843-Nandini> SELECT * FROM orders WHERE amt > 100;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```