

ASSIGNMENT - 07

Q1. Write a query that lists each order number followed by the name of the customer who made the order.

```
KD3-98843-Nandini> SELECT C.cname, O.onum FROM customers C INNER JOIN orders
O ON C.cnum = O.Cnum;
```

cname	onum
Cisneros	3001
Hoffman	3003
Pereira	3002
Liu	3005
Cisneros	3006
Giovanni	3009
Grass	3007
Clemens	3008
Grass	3010
Clemens	3011

```
10 rows in set (0.00 sec)
```

Q2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
KD3-98843-Nandini> SELECT s.sname, o.onum, c.cname FROM salespeople S INNER
JOIN orders o on s.snum = o.snum INNER JOIN customers c ON c.cnum = o.cnum;
```

sname	onum	cname
Peel	3003	Hoffman
Axelrod	3009	Giovanni
Serres	3005	Liu
Serres	3010	Grass
Serres	3007	Grass
Peel	3011	Clemens
Peel	3008	Clemens
Rifkin	3006	Cisneros
Rifkin	3001	Cisneros
Motika	3002	Pereira

```
10 rows in set (0.00 sec)
```

Q3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
KD3-98843-Nandini> SELECT s.sname, c.cname, s.comm FROM salespeople S INNER
JOIN customers c ON c.snum = s.snum WHERE s.comm > 0.12;
+-----+-----+-----+
| sname | cname | comm |
+-----+-----+-----+
| Serres | Liu   | 0.13 |
| Serres | Grass | 0.13 |
| Rifkin | Cisneros | 0.15 |
+-----+-----+-----+
3 rows in set (0.00 sec)
```

Q4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
KD3-98843-Nandini> SELECT onum, o.cnum, (comm * amt) commission FROM orders o
-> INNER JOIN salespeople s ON o.snum = s.snum
-> INNER JOIN customers c ON o.cnum = c.cnum
-> WHERE c.rating > 100 ;
+-----+-----+-----+
| onum | cnum | commission |
+-----+-----+-----+
| 3010 | 2004 | 40.2935 |
| 3007 | 2004 | 9.8475 |
| 3005 | 2003 | 670.8585 |
| 3006 | 2008 | 164.7240 |
| 3001 | 2008 | 2.8035 |
| 3009 | 2002 | 171.3230 |
+-----+-----+-----+
6 rows in set (0.00 sec)
```

Q5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```
KD3-98843-Nandini> SELECT sa.sname AS SalespersonA, sb.sname AS SalespersonB,
-> sa.city AS City FROM salespeople sa INNER JOIN salespeople sb
-> ON sa.city = sb.city WHERE
-> sa.sname < sb.sname;
+-----+-----+-----+
| SalespersonA | SalespersonB | City |
+-----+-----+-----+
| Motika       | Peel         | London |
+-----+-----+-----+
1 row in set (0.00 sec)
```