

ASSIGNMENT 6

Q1.

```
kd3_98850_pranit> SELECT odate,COUNT(DISTINCT snum) FROM orders
-> GROUP BY odate;
```

odate	COUNT(DISTINCT snum)
1990-10-03	4
1990-10-04	3

```
2 rows in set (0.00 sec)
```

Q2.

```
kd3_98850_pranit> SELECT CONCAT('FOR the city ',city, ' highest rating is : ',MAX(r
ating)) AS rating FROM customers
-> GROUP BY city;
```

rating
FOR the city London highest rating is : 100
FOR the city Rome highest rating is : 200
FOR the city San Jose highest rating is : 300
FOR the city Berlin highest rating is : 300

```
4 rows in set (0.00 sec)
```

Q3.

```
kd3_98850_pranit> SELECT odate,SUM(amt) total FROM orders
-> GROUP BY odate
-> ORDER BY total DESC;
```

odate	total
1990-10-04	16713.81
1990-10-03	8944.59

```
2 rows in set (0.00 sec)
```

ASSIGNMENT 6

Q4.

```
kd3_98850_pranit> SELECT snum, SUM(amt) total FROM orders
-> GROUP BY snum
-> HAVING total > 2565.84;
+-----+-----+
| snum | total |
+-----+-----+
| 1001 | 15382.07 |
| 1002 | 5546.15 |
+-----+-----+
2 rows in set (0.00 sec)
```

Q5.

```
kd3_98850_pranit> SELECT city, MAX(rating) AS highest FROM customers
-> GROUP BY city;
+-----+-----+
| city | highest |
+-----+-----+
| London | 100 |
| Rome | 200 |
| San Jose | 300 |
| Berlin | 300 |
+-----+-----+
4 rows in set (0.00 sec)
```

Q6

```
kd3_98850_pranit> SELECT snum, MAX(amt) AS max FROM orders
-> GROUP BY snum
-> HAVING max > 3000;
+-----+-----+
| snum | max |
+-----+-----+
| 1001 | 9891.88 |
| 1002 | 5160.45 |
+-----+-----+
2 rows in set (0.00 sec)
```

ASSIGNMENT 6

Q7.

```
kd3_98850_pranit> SELECT cnum, MIN(amt) AS min FROM orders
-> GROUP BY cnum
-> ORDER BY cnum;
```

cnum	min
2001	767.19
2002	1713.23
2003	5160.45
2004	75.75
2006	4723.00
2007	1900.10
2008	18.69

7 rows in set (0.00 sec)