

ASSIGNMENT 8

Q1.

```
kd3_98850_pranit> SELECT * FROM orders
-> WHERE snum = (SELECT snum FROM customers WHERE cname = 'Cisneros');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)

kd3_98850_pranit> |
```

Q7.

```
kd3_98850_pranit> SELECT * FROM orders
-> WHERE snum = (SELECT snum FROM salespeople WHERE sname = 'Motika');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

Q8.

```
kd3_98850_pranit> SELECT * FROM orders
-> WHERE snum IN ( SELECT snum FROM customers WHERE city = 'London');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

ASSIGNMENT 8

Q6.

```
kd3_98850_pranit> SELECT * FROM orders
-> WHERE amt > ANY(SELECT amt FROM orders WHERE cnum IN ( SELECT cnum FR
OM customers WHERE city = 'London'));
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.01 sec)
```

Q4

```
kd3_98850_pranit> SELECT * FROM customers
-> WHERE rating >= ANY( SELECT rating FROM customers WHERE snum = ( SELE
CT snum FROM salespeople WHERE sname = 'Serres'));
+-----+-----+-----+-----+-----+
| cnum | cname   | city    | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome    | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

Q11.

```
kd3_98850_pranit> SELECT * FROM customers
-> WHERE rating > ANY ( SELECT rating FROM customers WHERE city = 'Rome')
;
+-----+-----+-----+-----+-----+
| cnum | cname   | city    | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome    | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

ASSIGNMENT 8

Q12.

```
kd3_98850_pranit> SELECT * FROM orders
-> WHERE amt > ANY( SELECT amt FROM orders WHERE odate = '1990-10-04');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

Q13.

```
kd3_98850_pranit> SELECT * FROM orders
-> WHERE amt < ANY (SELECT amt FROM orders WHERE snum IN ( SELECT snum F
ROM customers WHERE city = 'San Jose'));
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

Q2.

```
kd3_98850_pranit> SELECT o.amt, c.cname, c.rating FROM orders o
-> INNER JOIN customers c
-> ON o.cnum = c.cnum
-> WHERE o.amt > (SELECT AVG(amt) FROM orders );
+-----+-----+-----+
| amt   | cname   | rating |
+-----+-----+-----+
| 5160.45 | Liu     | 200    |
| 9891.88 | Clemens | 100    |
| 4723.00 | Clemens | 100    |
+-----+-----+-----+
3 rows in set (0.00 sec)
```

ASSIGNMENT 8

Q14.

```
kd3_98850_pranit> SELECT * FROM customers
-> WHERE rating > (SELECT MAX(rating) FROM customers WHERE city = 'London');
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

Q5.

```
kd3_98850_pranit> SELECT * FROM salespeople s
-> WHERE snum != ALL(SELECT snum FROM customers WHERE city = s.city);
+-----+-----+-----+-----+
| snum | sname   | city   | comm |
+-----+-----+-----+-----+
| 1004 | Motika  | London | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York | 0.10 |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

Q9

```
kd3_98850_pranit> SELECT sname,snum FROM salespeople s
-> WHERE (SELECT COUNT(snum) FROM customers c WHERE s.snum = c.snum) > 1
;
+-----+-----+
| sname | snum |
+-----+-----+
| Peel  | 1001 |
| Serres | 1002 |
+-----+-----+
2 rows in set (0.00 sec)
```

Q10

```
kd3_98850_pranit> SELECT snum, sname,city,(SELECT COUNT(snum) FROM customers c WHERE s.snum = c.snum) customer_count FROM salespeople s
-> WHERE (SELECT COUNT(snum) FROM customers c WHERE s.snum = c.snum) > 1;
+-----+-----+-----+-----+
| snum | sname | city   | customer_count |
+-----+-----+-----+-----+
| 1001 | Peel  | London | 2 |
| 1002 | Serres | San Jose | 2 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

ASSIGNMENT 8

Q11.

```
kd3_98850_pranit> SELECT snum, SUM(amt) FROM orders
-> GROUP BY snum
-> HAVING SUM(amt) > (SELECT MAX(amt) FROM orders);
+-----+-----+
| snum | SUM(amt) |
+-----+-----+
| 1001 | 15382.07 |
+-----+-----+
1 row in set (0.00 sec)
```