

ASSIGNMENT 7

Q1.

```
kd3_98850_pranit> SELECT o.onum, c.cname FROM orders o
-> INNER JOIN customers c
-> ON o.cnum = c.cnum;
```

onum	cname
3001	Cisneros
3003	Hoffman
3002	Pereira
3005	Liu
3006	Cisneros
3009	Giovanni
3007	Grass
3008	Clemens
3010	Grass
3011	Clemens

10 rows in set (0.00 sec)

Q2.

```
kd3_98850_pranit> SELECT o.onum, c.cname, s.sname FROM orders o
-> INNER JOIN customers c
-> ON o.cnum = c.cnum
-> INNER JOIN salespeople s
-> ON o.snum = s.snum;
```

onum	cname	sname
3003	Hoffman	Peel
3009	Giovanni	Axelrod
3005	Liu	Serres
3010	Grass	Serres
3007	Grass	Serres
3011	Clemens	Peel
3008	Clemens	Peel
3006	Cisneros	Rifkin
3001	Cisneros	Rifkin
3002	Pereira	Motika

10 rows in set (0.00 sec)

ASSIGNMENT 7

Q3.

```
kd3_98850_pranit> SELECT c.cname, s.sname, s.comm FROM customers c
-> INNER JOIN salespeople s
-> ON c.snum = s.snum
-> WHERE s.comm > 0.12;
+-----+-----+-----+
| cname | sname | comm |
+-----+-----+-----+
| Liu   | Serres | 0.13 |
| Grass | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+-----+-----+-----+
3 rows in set (0.00 sec)
```

Q4.

```
kd3_98850_pranit> SELECT o.onum, c.rating, s.comm * o.amt FROM orders o
-> INNER JOIN customers c ON o.cnum = c.cnum
-> INNER JOIN salespeople s ON c.snum = s.snum
-> WHERE c.rating > 100;
+-----+-----+-----+
| onum | rating | s.comm * o.amt |
+-----+-----+-----+
| 3001 | 300 | 2.8035 |
| 3005 | 200 | 670.8585 |
| 3006 | 300 | 164.7240 |
| 3009 | 200 | 171.3230 |
| 3007 | 300 | 9.8475 |
| 3010 | 300 | 40.2935 |
+-----+-----+-----+
6 rows in set (0.00 sec)
```

Q5.

```
kd3_98850_pranit> SELECT s1.sname sal1, s2.sname sal2, s1.city FROM salespeople s1
-> INNER JOIN salespeople s2
-> ON s1.city = s2.city
-> WHERE s1.sname > s2.sname;
+-----+-----+-----+
| sal1 | sal2 | city |
+-----+-----+-----+
| Peel | Motika | London |
+-----+-----+-----+
1 row in set (0.00 sec)
```