

Assignment 2

1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
RD3_98823_pranoti@localhost> SELECT * FROM Customers WHERE snum = 1001;
```

cnum	cname	city	rating	snum
2001	Hoffman	London	100	1001
2006	Clemens	London	100	1001

2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
RD3_98823_pranoti@localhost> SELECT rating ,cname FROM Customers WHERE city='San Jose';
```

rating	cname
200	Liu
300	Cisneros

2 rows in set (0.00 sec)

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
RD3_98823_pranoti@localhost> SELECT DISTINCT snum FROM Customers
```

snum
1001
1003
1002
1007
1004

5 rows in set (0.00 sec)

4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
KD3_98823_pranoti@localhost> SELECT * FROM orders WHERE amt>1000;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
KD3_98823_pranoti@localhost> SELECT sname,city from salespeople WHERE city ='London'
;
+-----+-----+
| sname | city |
+-----+-----+
| Peel  | London |
| Motika | London |
+-----+-----+
2 rows in set (0.00 sec)
```

6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
KD3_98823_pranoti@localhost> SELECT * from Customers where rating>100 OR city='Rome';
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome    | 100    | 1004 |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

7. What will be the output from the following query? Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```
KD3_98823_pranoti@localhost> SELECT * FROM orders where (amt<1000 OR NOT(odate ='1990-10-03' AND cnum>2003));
```

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3005	5160.45	1990-10-03	2003	1002
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

8 rows in set (0.02 sec)

8. What will be the output of the following query? Select * from Orders where NOT (odate = '1990-10-03' OR snum > 1006) AND amt >= 1500;

```
KD3_98823_pranoti@localhost> SELECT * FROM orders WHERE NOT (odate ='1990-10-03' OR snum>1006) AND amt>=1500;
```

onum	amt	odate	cnum	snum
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

3 rows in set (0.00 sec)

9. What is a simpler way to write this query? Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
KD3_98823_pranoti@localhost> SELECT snum,sname,city FROM salespeople WHERE (comm>= .12 AND comm <=.14);
```

snum	sname	city
1001	Peel	London
1002	Serres	San Jose

2 rows in set (0.00 sec)

10. Write a query that selects all orders except those with amount less than 100.

```
MD3_98823_pranoti@localhost> SELECT * FROM orders WHERE amt>100;
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.00 sec)
```