

ASSIGNMENT 1

1. CREATE TABLE S (S# CHAR(5) NOT NULL, Sname CHAR(20), status SMALLINT, city CHAR(15));

```
KD3_98823_pranoti@localhost> INSERT INTO S VALUES(S1,'smith',20,'london');
ERROR 1054 (42S22): Unknown column 'S1' in 'field list'
KD3_98823_pranoti@localhost> INSERT INTO S VALUES('S1','smith',20,'london');
Query OK, 1 row affected (0.03 sec)

KD3_98823_pranoti@localhost> INSERT INTO S VALUES('S2','jones',10,'paries');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO S VALUES('S3','blake',30,'paries');
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual th
'blake',30,'paries')' at line 1
KD3_98823_pranoti@localhost> INSERT INTO S VALUES('S3','blake',30,'paries');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO S VALUES('S4','clark',20,'London');
Query OK, 1 row affected (0.01 sec)

KD3_98823_pranoti@localhost> INSERT INTO S VALUES('S5','Adams',30,'Athens');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> SELECT *FROM S;
+-----+-----+-----+-----+
| S#    | Sname | status | city  |
+-----+-----+-----+-----+
| S1    | smith | 20     | london|
| S2    | jones | 10     | paries|
| S3    | blake | 30     | paries|
| S4    | clark | 20     | London|
| S5    | Adams | 30     | Athens|
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

- 2.CREATE TABLE P (P# CHAR(6) NOT NULL, Pname CHAR(20), color CHAR(6), weight SMALLINT, city CHAR(15));

```
KD3_98823_pranoti@localhost> INSERT INTO P VALUES('p1','nut','Red',12,'London');
Query OK, 1 row affected (0.03 sec)

KD3_98823_pranoti@localhost> INSERT INTO P VALUES('p2','Bolt','Green',17,'Paries');
Query OK, 1 row affected (0.03 sec)

KD3_98823_pranoti@localhost> INSERT INTO P VALUES('P3','Screw','Blue',17,'Rome');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO P VALUES('P4','Cam','Blue',12,'Paries');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO P VALUES('P5','cog','Red',19,'London');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> SELECT *FROM P;
+-----+-----+-----+-----+-----+
| P#    | Pname | color | weight | city  |
+-----+-----+-----+-----+-----+
| p1    | nut   | Red   | 12     | London|
| p2    | Bolt  | Green | 17     | Paries|
| P3    | Screw | Blue  | 17     | Rome  |
| P4    | Cam   | Blue  | 12     | Paries|
| P5    | cog   | Red   | 19     | London|
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

2. CREATE TABLE J (J# CHAR(4) NOT NULL, Jname CHAR(10), City CHAR(15));

```
KD3_98823_pranoti@localhost> INSERT INTO J VALUES('J1','sorter','paries');
Query OK, 1 row affected (0.03 sec)

KD3_98823_pranoti@localhost> INSERT INTO J VALUES('J2','punch','Rome');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO J VALUES('J3','Reader','Athens');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO J VALUES('J4','console','Athens');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO J VALUES('J5','collator','London');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO J VALUES('J6','Terminal','Oslo');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO J VALUES('J7','Tape','London');
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> SELECT *FROM J;
+-----+-----+-----+
| J#    | Jname  | city   |
+-----+-----+-----+
| J1    | sorter | paries |
| J2    | punch  | Rome   |
| J3    | Reader | Athens |
| J4    | console| Athens |
| J5    | collator| London |
| J6    | Terminal| Oslo   |
| J7    | Tape   | London |
+-----+-----+-----+
7 rows in set (0.00 sec)
```

3. CREATE TABLE sp (S# CHAR(4) NOT NULL, P# CHAR(4) NOT NULL, J# CHAR(4) NOT NULL, QTY INT);

```

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s1','p1','j1',200);
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s1','p1','j4',700);
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s2','p3','j1',400);
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s2','p3','j2',200);
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s2','p3','j3',200);
Query OK, 1 row affected (0.00 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s2','p3','j4',500);
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s2','p3','j5',600);
Query OK, 1 row affected (0.03 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s2','p3','j6',400);
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s2','p3','j7',800);
Query OK, 1 row affected (0.02 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s3','p4','j2',100);
Query OK, 1 row affected (0.03 sec)

KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s3','p5','j1',200),('s3','p4','j2',500)
-> 'C
KD3_98823_pranoti@localhost> INSERT INTO SP VALUES('s3','p5','j1',200),('s3','p4','j2',500),('s4','p6','j7',300),('s5','p2','j2',200),('s5','p2','j2',200),('
's5','p5','j5',500),('s5','p5','j7',100),('s5','p4','j4',200),('s5','p4','j4',400),('s5','p6','j4',500);
Query OK, 10 rows affected (0.03 sec)
Records: 10 Duplicates: 0 Warnings: 0

```

```

KD3_98823_pranoti@localhost> SELECT *FROM SP;

```

S#	P#	J#	QTY
s1	p1	j1	200
s1	p1	j4	700
s2	p3	j1	400
s2	p3	j2	200
s2	p3	j3	200
s2	p3	j4	500
s2	p3	j5	600
s2	p3	j6	400
s2	p3	j7	800
s3	p4	j2	100
s3	p5	j1	200
s3	p4	j2	500
s4	p6	j7	300
s5	p2	j2	200
s5	p2	j2	200
s5	p5	j5	500
s5	p5	j7	100
s5	p4	j4	200
s5	p4	j4	400
s5	p6	j4	500

```

20 rows in set (0.00 sec)

```

1. How many orders data is present in the database?

ANS -10 order

2. How many customers are present in the database?

ANS. 7 customers

3. How many salespeople are present in the database?

ANS. 5 salespeople

4. On which date order with highest amount is placed?

ANS. 1990-10-04

5. For which order salesman got maximum commission?

Hint: you need to refer data of two tables.

ANS. Order 3011 -peel(maximum commission = 1187.03)

6. Which salesmen are handling more than two customers? Hint: you need to refer data of two tables.

ANS. No salesman handling more than two customers.

7. Which city have single customer?

ANS. Berlin.

8. Which city has multiple salespeople?

Ans . London

9. What is name of customer and salesman of the maximum amount order?

Ans.Clemens-peel

10. Study relationship between the tables in sales database.

Ans. Salespeople ->customers->orders; one salesman handle many customers, and one customer can have many orders.