

ASSIGNMENT 7

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
-> where ^C
KD3_98823_pranoti@localhost> select DISTINCT o.onum,c.cname from orders o
-> INNER JOIN customers c ON c.cnum =o.cnum;
+-----+-----+
| onum | cname |
+-----+-----+
| 3001 | Cisneros |
| 3003 | Hoffman |
| 3002 | Pereira |
| 3005 | Liu |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass |
| 3008 | Clemens |
| 3010 | Grass |
| 3011 | Clemens |
+-----+-----+
10 rows in set (0.03 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
ERROR 1064 (42002): Unknown column 'sname' in 'field list'
KD3_98823_pranoti@localhost> SELECT onum,cname,sname FROM orders o
-> INNER JOIN customers c ON c.cnum =o.cnum
-> INNER JOIN salespeople s ON s.snum = o.snum;
+-----+-----+-----+
| onum | cname | sname |
+-----+-----+-----+
| 3003 | Hoffman | Peel |
| 3009 | Giovanni | Axelrod |
| 3005 | Liu | Serres |
| 3010 | Grass | Serres |
| 3007 | Grass | Serres |
| 3011 | Clemens | Peel |
| 3008 | Clemens | Peel |
| 3006 | Cisneros | Rifkin |
| 3001 | Cisneros | Rifkin |
| 3002 | Pereira | Motika |
+-----+-----+-----+
10 rows in set (0.00 sec)
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
KD3_98823_pranoti@localhost> SELECT sname, cname ,comm from customers c
-> INNER JOIN salespeople s ON s.snum =c.snum
-> where comm> 0.12;

+-----+-----+-----+
| sname | cname | comm |
+-----+-----+-----+
| Serres | Liu   | 0.13 |
| Serres | Grass | 0.13 |
| Rifkin | Cisneros | 0.15 |
+-----+-----+-----+
3 rows in set (0.02 sec)
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
-> ^C
KD3_98823_pranoti@localhost> SELECT onum, comm ,s.comm*o.amt from orders o
-> INNER JOIN salespeople s ON s.snum=o.snum
-> INNER JOIN customers c ON c.cnum =o.cnum
-> where c.rating >100;

+-----+-----+-----+
| onum | comm | s.comm*o.amt |
+-----+-----+-----+
| 3010 | 0.13 | 40.2935 |
| 3007 | 0.13 | 9.8475 |
| 3005 | 0.13 | 670.8585 |
| 3006 | 0.15 | 164.7240 |
| 3001 | 0.15 | 2.8035 |
| 3009 | 0.10 | 171.3230 |
+-----+-----+-----+
6 rows in set (0.00 sec)
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```
KD3_98823_pranoti@localhost> select  s.sname AS salesperson1,c.sname AS salesperson2,s.city from salespeople s
-> INNER JOIN salespeople c ON s.city =c.city
-> where s.sname<c.sname;

+-----+-----+-----+
| salesperson1 | salesperson2 | city |
+-----+-----+-----+
| Motika       | Peel         | London |
+-----+-----+-----+
1 row in set (0.00 sec)

KD3_98823_pranoti@localhost> |
```