ASSIGNMENT -7

1.Write a query that lists each order number followed by the name of the customer who made the order.

```
KD3-Prerana-96192>SELECT o.onum, c.cname FROM orders o INNER JOIN customers c ON o.cnum = c.cnum;
+------+----------+
| onum | cname    |
+------+----------+
| 3001 | Cisneros |
| 3003 | Hoffman  |
| 3002 | Pereira  |
| 3005 | Liu      |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass    |
| 3008 | Clemens  |
| 3010 | Grass    |
| 3011 | Clemens  |
+------+----------+
10 rows in set (0.00 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
KD3-Prerana-96192>SELECT o.onum, c.cname, s.sname FROM orders o INNER JOIN customers c ON o.cnum = c.cnum INNER JOIN s
alespeople s ON s.snum = o.snum;
+------+----------+---------+
| onum | cname    | sname   |
+------+----------+---------+
| 3003 | Hoffman  | Peel    |
| 3009 | Giovanni | Axelrod |
| 3005 | Liu      | Serres  |
| 3010 | Grass    | Serres  |
| 3007 | Grass    | Serres  |
| 3011 | Clemens  | Peel    |
| 3008 | Clemens  | Peel    |
| 3006 | Cisneros | Rifkin  |
| 3001 | Cisneros | Rifkin  |
| 3002 | Pereira  | Motika  |
+------+----------+---------+
10 rows in set (0.00 sec)
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's

rate of commission

```
KD3-Prerana-96192>SELECT c.cname, s.sname, s.comm FROM customers c INNER JOIN salespeople s ON  c.snum=s.snum WHERE s.
comm>0.12;
+----------+--------+------+
| cname    | sname  | comm |
+----------+--------+------+
| Liu      | Serres | 0.13 |
| Grass    | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+----------+--------+------+
3 rows in set (0.01 sec)
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
KD3-Prerana-96192>SELECT s.sname, s.comm, o.amt * s.comm, c.rating FROM salespeople s INNER JOIN orders o on o.snum =s.s
num inner join customers c on c.cnum = o.cnum WHERE c.rating>100;
+---------+------+---------------+--------+
| sname   | comm | o.amt * s.comm | rating |
+---------+------+---------------+--------+
| Serres  | 0.13 |       40.2935 |    300 |
| Serres  | 0.13 |        9.8475 |    300 |
| Serres  | 0.13 |      670.8585 |    200 |
| Rifkin  | 0.15 |      164.7240 |    300 |
| Rifkin  | 0.15 |        2.8035 |    300 |
| Axelrod | 0.10 |      171.3230 |    200 |
+---------+------+---------------+--------+
6 rows in set (0.00 sec)
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed.

```
KD3-Prerana-96192>SELECT s.sname sname1, p.sname sname2, s.city FROM salespeople s INNER JOIN salespeopl
e p ON s.city = p.city WHERE s.sname < p.sname ;
+--------+--------+--------+
| sname1 | sname2 | city   |
+--------+--------+--------+
| Motika | Peel   | London |
+--------+--------+--------+
1 row in set (0.00 sec)
```