Assignment No-2

1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
mysql> select * from customers where snum = 1001;
+------+---------+--------+--------+------+
| cnum | cname   | city   | rating | snum |
+------+---------+--------+--------+------+
| 2001 | Hoffman | London |    100 | 1001 |
| 2006 | Clemens | London |    100 | 1001 |
+------+---------+--------+--------+------+
2 rows in set (0.018 sec)
```

2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
mysql> select cname, rating from customers where city = 'San Jose';
+----------+--------+
| cname    | rating |
+----------+--------+
| Liu      |    200 |
| Cisneros |    300 |
+----------+--------+
2 rows in set (0.010 sec)
```

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
mysql> select DISTINCT snum from orders;
+------+
| snum |
+------+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+------+
5 rows in set (0.142 sec)
```

4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
mysql> SELECT * FROM orders WHERE amt > 1000;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
6 rows in set (0.057 sec)
```

5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
mysql> select sname, city FROM salespeople WHERE city = 'London' AND comm > 0.10;
+--------+--------+
| sname  | city   |
+--------+--------+
| Peel   | London |
| Motika | London |
+--------+--------+
2 rows in set (0.010 sec)
```

6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
mysql> SELECT cname, city, rating FROM customers WHERE (rating > 100) OR (city = 'Rome');
+----------+----------+--------+
| cname    | city     | rating |
+----------+----------+--------+
| Giovanni | Rome     |    200 |
| Liu      | San Jose |    200 |
| Grass    | Berlin   |    300 |
| Cisneros | San Jose |    300 |
| Pereira  | Rome     |    100 |
+----------+----------+--------+
5 rows in set (0.024 sec)
```

7. What will be the output from the following query?

Select * from Orders where (amt < 1000 OR NOT (odate = ‘1990-10- 03’ AND cnum > 2003));

```
KD3_rutuja_96226>Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
8 rows in set (0.524 sec)
```

8. What will be the output of the following query?

Select * from Orders where NOT (odate = ‘1990-10-03’ OR snum >1006) AND amt >= 1500;

```
KD3_rutuja_96226>Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
3 rows in set (0.013 sec)
```

9. What is a simpler way to write this query? Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
KD3_rutuja_96226>Select * from Salespeople WHERE (comm >= .12 AND comm <= .14);
+------+--------+----------+------+
| snum | sname  | city     | comm |
+------+--------+----------+------+
| 1001 | Peel   | London   | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
+------+--------+----------+------+
2 rows in set (0.010 sec)
```

10. Write a query that selects all orders except those with amount less than 100.

```
KD3_rutuja_96226>select * from orders WHERE amt > 100;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
8 rows in set (0.011 sec)
```