Assignment N0 – 6

1. **Write a query that counts the number of salespeople registering orders for each day. (If a salesperson has more than one order on a given day, he or she should be counted only once.).**

```
KD3_rutuja_96226>SELECT odate, COUNT(DISTINCT snum) FROM orders GROUP BY odate;
+------------+----------------------+
| odate      | COUNT(DISTINCT snum) |
+------------+----------------------+
| 1990-10-03 |                    4 |
| 1990-10-04 |                    3 |
+------------+----------------------+
2 rows in set (0.053 sec)
```

2. **Write a query on the Customers table that will find the highest rating in each city. Put the output in this form: For the city (city), the highest rating is: (rating).**

```
KD3_rutuja_96226>select concat('For the city ',city,' the highest rating is: ',max(rating)) as highest_rating FROM
 customers GROUP BY city;
+-----------------------------------------------+
| highest_rating                                |
+-----------------------------------------------+
| For the city London the highest rating is: 100   |
| For the city Rome the highest rating is: 200     |
| For the city San Jose the highest rating is: 300 |
| For the city Berlin the highest rating is: 300   |
+-----------------------------------------------+
4 rows in set (0.013 sec)
```

3. Write an SQL query to calculate the total order amount for each day and display the results in descending order of total orders.

```
KD3_rutuja_96226>SELECT odate, SUM(amt) FROM orders GROUP BY odate ORDER BY SUM(amt) DESC;
+------------+----------+
| odate      | SUM(amt) |
+------------+----------+
| 1990-10-04 | 16713.81 |
| 1990-10-03 |  8944.59 |
+------------+----------+
2 rows in set (0.085 sec)
```

4. Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the average amount of the order in the table. (Note Use the average amount value directly →2565.84)

```
KD3_rutuja_96226>SELECT snum, SUM(amt) FROM orders GROUP BY snum HAVING SUM(amt) > 2565.84;
+------+----------+
| snum | SUM(amt) |
+------+----------+
| 1001 | 15382.07 |
| 1002 |  5546.15 |
+------+----------+
2 rows in set (0.136 sec)
```

5. Write a query that selects the highest rating in each city.

```
KD3_rutuja_96226> SELECT city, MAX(rating) FROM customers GROUP BY city;
+----------+-------------+
| city     | MAX(rating) |
+----------+-------------+
| London   |         100 |
| Rome     |         200 |
| San Jose |         300 |
| Berlin   |         300 |
+----------+-------------+
4 rows in set (0.094 sec)
```

6. Retrieve the maximum order amount for each salesperson from the orders table, including only those orders whose value exceeds Rs. 3000.

```
KD3_rutuja_96226>SELECT snum, MAX(amt) FROM orders GROUP BY snum HAVING MAX(amt) > 3000;
+------+----------+
| snum | MAX(amt) |
+------+----------+
| 1001 |  9891.88 |
| 1002 |  5160.45 |
+------+----------+
2 rows in set (0.088 sec)
```

7. Write an SQL query to find the smallest order placed by every customer.

```
KD3_rutuja_96226>SELECT cnum, MIN(amt) FROM orders GROUP BY cnum;
+------+----------+
| cnum | MIN(amt) |
+------+----------+
| 2008 |    18.69 |
| 2001 |   767.19 |
| 2007 |  1900.10 |
| 2003 |  5160.45 |
| 2002 |  1713.23 |
| 2004 |    75.75 |
| 2006 |  4723.00 |
+------+----------+
7 rows in set (0.014 sec)
```