Q.1)

```
sunbeam@mohit:~$ cat > data.txt
Linux is open source.
In Linux everything is file
files have permissions.
files have inode no.
files have size.
there are several types of files
sunbeam@mohit:~$
```

Q.2)

```
sunbeam@mohit:~$ man wc
sunbeam@mohit:~$ wc data.txt
  6  25 145 data.txt
sunbeam@mohit:~$
```

Q.3)

```
sunbeam@mohit:~$ grep "files" data.txt
files have permissions.
files have inode no.
files have size.
there are several types of files
sunbeam@mohit:~$
```

Q.4)

```
sunbeam@mohit:~$ grep "file" data.txt
In Linux everything is file
files have permissions.
files have inode no.
files have size.
there are several types of files
sunbeam@mohit:~$
```

Q.5)

```
sunbeam@mohit:~$ man grep
sunbeam@mohit:~$ grep -v "files" data.txt
Linux is open source.
In Linux everything is file
sunbeam@mohit:~$
```

Q.6)

```
sunbeam@mohit:~$ grep "have" data.txt
files have permissions.
files have inode no.
files have size.
sunbeam@mohit:~$
```

Q.7)

```
sunbeam@mohit:~$ grep "^f" data.txt
files have permissions.
files have inode no.
files have size.
sunbeam@mohit:~$
```

Q.8)

```
sunbeam@mohit:~$ grep "\.$" data.txt
Linux is open source.
files have permissions.
files have inode no.
files have size.
sunbeam@mohit:~$
```

Q.9)

```
sunbeam@mohit:~$ man head
sunbeam@mohit:~$ head -n 2 data.txt
Linux is open source.
In Linux everything is file
sunbeam@mohit:~$
```

Q.10)

```
sunbeam@mohit:~$ man tail
sunbeam@mohit:~$ tail -n 3 data.txt
files have inode no.
files have size.
there are several types of files
sunbeam@mohit:~$
```

Q.11)

```
sunbeam@mohit:~$ head -n 5 data.txt | tail -n 3
files have permissions.
files have inode no.
files have size.
sunbeam@mohit:~$
```