

1. Write a query that counts the number of salespeople registering orders for each day. (If a salesperson has more than one order on a given day, he or she should be counted only once.).

```
KD3-98849-sakshi@localhost> SELECT odate,COUNT(DISTINCT snum)
-> FROM orders
-> GROUP BY odate;
```

odate	COUNT(DISTINCT snum)
1990-10-03	4
1990-10-04	3

2 rows in set (0.081 sec)

2. Write a query on the Customers table that will find the highest rating in each city. Put the output in this form: For the city (city), the highest rating is: (rating).

```
KD3-98849-sakshi@localhost> SELECT CONCAT('For the city ', city,
-> ' ', the highest rating is: ', MAX(rating), '.')
-> FROM customers
-> GROUP BY city;
```

CONCAT('For the city ', city, ' ', the highest rating is: ', MAX(rating), '.')
For the city London, the highest rating is: 100.
For the city Rome, the highest rating is: 200.
For the city San Jose, the highest rating is: 300.
For the city Berlin, the highest rating is: 300.

4 rows in set (0.019 sec)

- 3 Write an SQL query to calculate the total order amount for each day and display the results in descending order of total orders.

```
KD3-98849-sakshi@localhost> SELECT odate,SUM(amt) AS total_orders
-> FROM orders
-> GROUP BY odate
-> ORDER BY total_orders DESC;
```

odate	total_orders
1990-10-04	16713.81
1990-10-03	8944.59

2 rows in set (0.018 sec)

4. Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the average amount of the order in the table. (Note Use the average amount value directly → 2565.84)

```
KD3-98849-sakshi@localhost> SELECT snum,SUM(amt)AS total_amount
-> FROM orders
-> GROUP BY snum
-> HAVING SUM(amt)>2565.84;
```

snum	total_amount
1001	15382.07
1002	5546.15

```
2 rows in set (0.014 sec)
```

5. Write a query that selects the highest rating in each city.

```
KD3-98849-sakshi@localhost> SELECT city,MAX(rating)AS highest_rating
-> FROM customers
-> GROUP BY city;
```

city	highest_rating
London	100
Rome	200
San Jose	300
Berlin	300

```
4 rows in set (0.007 sec)
```

6. Retrieve the maximum order amount for each salesperson from the orders table, including only those orders whose value exceeds Rs. 3000.

```
KD3-98849-sakshi@localhost> SELECT snum,MAX(amt)AS max_order_amt
-> FROM orders
-> WHERE amt>3000
-> GROUP BY snum;
```

snum	max_order_amt
1002	5160.45
1001	9891.88

```
2 rows in set (0.013 sec)
```

7. Write an SQL query to find the smallest order placed by every customer.

```
D3-98849-sakshi@localhost> SELECT cnum,MIN(amt) AS smallest_order  
-> FROM orders  
-> GROUP BY cnum;
```

cnum	smallest_order
2008	18.69
2001	767.19
2007	1900.10
2003	5160.45
2002	1713.23
2004	75.75
2006	4723.00

7 rows in set (0.014 sec)