

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
KD3-98849-sakshi@localhost> SELECT o.onum,c.cname FROM orders o
-> INNER JOIN customers c ON c.snum=o.snum;

+-----+-----+
| onum | cname |
+-----+-----+
| 3001 | Cisneros |
| 3003 | Clemens |
| 3003 | Hoffman |
| 3002 | Pereira |
| 3005 | Grass |
| 3005 | Liu |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass |
| 3007 | Liu |
| 3008 | Clemens |
| 3008 | Hoffman |
| 3010 | Grass |
| 3010 | Liu |
| 3011 | Clemens |
| 3011 | Hoffman |
+-----+-----+
16 rows in set (0.011 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
KD3-98849-sakshi@localhost> SELECT onum,cname,sname FROM orders o
-> INNER JOIN customers c ON c.cnum=o.cnum
-> INNER JOIN salespeople s ON s.snum=o.snum;

+-----+-----+-----+
| onum | cname | sname |
+-----+-----+-----+
| 3003 | Hoffman | Peel |
| 3009 | Giovanni | Axelrod |
| 3005 | Liu | Serres |
| 3010 | Grass | Serres |
| 3007 | Grass | Serres |
| 3011 | Clemens | Peel |
| 3008 | Clemens | Peel |
| 3006 | Cisneros | Rifkin |
| 3001 | Cisneros | Rifkin |
| 3002 | Pereira | Motika |
+-----+-----+-----+
10 rows in set (0.036 sec)
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
KD3-98849-sakshi@localhost> SELECT sname,cname,comm FROM customers c
-> INNER JOIN salespeople s ON c.snum=s.snum
-> WHERE comm>0.12;
```

sname	cname	comm
Serres	Liu	0.13
Serres	Grass	0.13
Rifkin	Cisneros	0.15

3 rows in set (0.020 sec)

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
KD3-98849-sakshi@localhost> SELECT o.onum,s.comm ,o.amt*s.comm FROM orders o
-> INNER JOIN salespeople s ON s.snum=o.snum
-> INNER JOIN customers c ON c.cnum=o.cnum
-> WHERE c.rating >100;
```

onum	comm	o.amt*s.comm
3010	0.13	40.2935
3007	0.13	9.8475
3005	0.13	670.8585
3006	0.15	164.7240
3001	0.15	2.8035
3009	0.10	171.3230

6 rows in set (0.098 sec)

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```

KD3-98849-sakshi@localhost> SELECT c.cname,s.sname ,s.city from salespeople
5
-> INNER JOIN customers c ON c.cname=s.sname
-> INNER JOIN salespeople s ON s.city=c.city;
ERROR 1066 (42000): Not unique table/alias: 's'
KD3-98849-sakshi@localhost> SELECT
->     a.sname AS salesperson_1,
->     b.sname AS salesperson_2,
->     a.city
-> FROM
->     salespeople a
-> JOIN
->     salespeople b ON a.city = b.city AND a.snum < b.snum;
+-----+-----+-----+
| salesperson_1 | salesperson_2 | city |
+-----+-----+-----+
| Peel          | Motika        | London |
+-----+-----+-----+
1 row in set (0.017 sec)

```