

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
KD3-99107-shashank@localhost> select o.onum, c.cname from orders o inner join customers c on o.cnum = c.cnum;
```

onum	cname
3001	Cisneros
3003	Hoffman
3002	Pereira
3005	Liu
3006	Cisneros
3009	Giovanni
3007	Grass
3008	Clemens
3010	Grass
3011	Clemens

```
10 rows in set (0.001 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
KD3-99107-shashank@localhost> select o.onum, c.cname, s.sname from orders o inner join customers c on o.cnum = c.cnum inner join salespeople s on o.snum = s.snum;
```

onum	cname	sname
3003	Hoffman	Peel
3009	Giovanni	Axelrod
3005	Liu	Serres
3010	Grass	Serres
3007	Grass	Serres
3011	Clemens	Peel
3008	Clemens	Peel
3006	Cisneros	Rifkin
3001	Cisneros	Rifkin
3002	Pereira	Motika

```
10 rows in set (0.001 sec)
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
KD3-99107-shashank@localhost> select c.cname, s.sname, s.comm from customers c inner join salespeople s on c.snum = s.snum where s.comm > 0.12;
```

cname	sname	comm
Liu	Serres	0.13
Grass	Serres	0.13
Cisneros	Rifkin	0.15

```
3 rows in set (0.001 sec)
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
[KD3-99107-shashank@localhost> select o.onum, s.comm, o.amt * s.comm from orders o inner join salespe
ople s on o.snum = s.snum inner join customers c on o.cnum = c.cnum where c.rating > 100;
+-----+-----+-----+
| onum | comm | o.amt * s.comm |
+-----+-----+-----+
| 3010 | 0.13 | 40.2935 |
| 3007 | 0.13 | 9.8475 |
| 3005 | 0.13 | 670.8585 |
| 3006 | 0.15 | 164.7240 |
| 3001 | 0.15 | 2.8035 |
| 3009 | 0.10 | 171.3230 |
+-----+-----+-----+
6 rows in set (0.001 sec)
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```
[KD3-99107-shashank@localhost> select s.sname, s2.sname, s.city from salespeople s inner join salespe
ople s2 on s.city = s2.city AND s.sname > s2.sname;
+-----+-----+-----+
| sname | sname | city |
+-----+-----+-----+
| Peel | Motika | London |
+-----+-----+-----+
1 row in set (0.001 sec)
```