

1. Write a query that produces all rows from the Customer table for which the salesperson's number is 1001.

```
KD3-99107-shashank@localhost> select * from customers where snum = 1001;
+-----+-----+-----+-----+-----+
| cnum | cname | city | rating | snum |
+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
+-----+-----+-----+-----+
2 rows in set (0.001 sec)
```

Write a select command that produces the rating followed by the name of each customer in San Jose.

```
+-----+-----+
| rating | cname |
+-----+-----+
| 200 | Liu |
| 300 | Cisneros |
+-----+-----+
2 rows in set (0.001 sec)

KD3-99107-shashank@localhost> █
```

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
[KD3-99107-shashank@localhost> select DISTINCT snum from orders;
+-----+
| snum |
+-----+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+-----+
5 rows in set (0.003 sec)

KD3-99107-shashank@localhost> █
```

4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
[KD3-99107-shashank@localhost> select * from orders where amt > 1000;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.001 sec)
```

5. 5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
ERROR 1054 (42S22): Unknown column 'sname' in 'field list'
[KD3-99107-shashank@localhost> select sname, city from salespeople where comm > .10;
+-----+-----+
| sname | city |
+-----+-----+
| Peel  | London |
| Serres | San Jose |
| Motika | London |
| Rifkin | Barcelona |
+-----+-----+
4 rows in set (0.001 sec)

KD3-99107-shashank@localhost>
```

6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
KD3-99107-shashank@localhost> select * from customers where rating > 100 OR city = 'rome';
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome   | 100    | 1004 |
+-----+-----+-----+-----+-----+
5 rows in set (0.001 sec)

KD3-99107-shashank@localhost>
```

7. What will be the output from the following query?

Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```
KD3-99107-shashank@localhost> Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
```

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3005	5160.45	1990-10-03	2003	1002
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.002 sec)
```

8. What will be the output of the following query?

Select * from Orders where NOT (odate = '1990-10-03' OR snum>1006) AND amt >= 1500;

```
KD3-99107-shashank@localhost> Select * from Orders where NOT (odate = '1990-10-03' OR snum>1006) AND amt >= 1500;
```

onum	amt	odate	cnum	snum
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

```
3 rows in set (0.001 sec)
```

9. What is a simpler way to write this query?

Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
KD3-99107-shashank@localhost> select * from salespeople where comm between 0.12 AND 0.14;
```

snum	sname	city	comm
1001	Peel	London	0.12
1002	Serres	San Jose	0.13

```
2 rows in set (0.002 sec)
```

10. Write a query that selects all orders except those with amount less than 100.

```
KD3-99107-shashank@localhost> select * from orders where amt > 100;
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.001 sec)
```