

1. Write a query that counts the number of salespeople registering orders for each day. (If a salesperson has more than one order on a given day, he or she should be counted only once.)

```
KD3-99107-shashank@localhost> select odate, count(distinct(cnum)) from orders group by odate;
```

odate	count(distinct(cnum))
1990-10-03	4
1990-10-04	3

```
2 rows in set (0.001 sec)
```

2. Write a query on the Customers table that will find the highest rating in each city. Put the output in this form: For the city (city), the highest rating is: (rating).

```
KD3-99107-shashank@localhost> select concat('For the city ',city,', ', 'highest rating is : ', max(rating)) from customers group by city;
```

concat('For the city ',city,', ', 'highest rating is : ', max(rating))
For the city London, highest rating is : 100
For the city Rome, highest rating is : 200
For the city San Jose, highest rating is : 300
For the city Berlin, highest rating is : 300

```
4 rows in set (0.001 sec)
```

3 Write an SQL query to calculate the total order amount for each day and display the results in descending order of total orders.

```
KD3-99107-shashank@localhost> select sum(amt) , odate from orders group by odate order by sum(amt) desc;
```

sum(amt)	odate
16713.81	1990-10-04
8944.59	1990-10-03

```
2 rows in set (0.001 sec)
```

4. Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the average amount of the order in the table. (Note Use the average amount value directly →2565.84)

```
KD3-99107-shashank@localhost> select snum, sum(amt) from orders group by snum having sum(amt)> 2565.84;
+-----+-----+
| snum | sum(amt) |
+-----+-----+
| 1001 | 15382.07 |
| 1002 | 5546.15  |
+-----+-----+
2 rows in set (0.001 sec)
```

5. Write a query that selects the highest rating in each city.

```
KD3-99107-shashank@localhost> select city, max(rating) from customers group by city;
+-----+-----+
| city | max(rating) |
+-----+-----+
| London | 100 |
| Rome | 200 |
| San Jose | 300 |
| Berlin | 300 |
+-----+-----+
4 rows in set (0.001 sec)
```

6. Retrieve the maximum order amount for each salesperson from the orders table, including only those orders whose value exceeds Rs. 3000.

```
KD3-99107-shashank@localhost> select snum, max(amt) from orders where amt > 3000 group by snum ;
+-----+-----+
| snum | max(amt) |
+-----+-----+
| 1002 | 5160.45 |
| 1001 | 9891.88 |
+-----+-----+
2 rows in set (0.001 sec)
```

7. Write an SQL query to find the smallest order placed by every customer.

```
[KD3-99107-shashank@localhost> select cnum, min(amt) from orders group by cnum order by cnum;
```

cnum	min(amt)
2001	767.19
2002	1713.23
2003	5160.45
2004	75.75
2006	4723.00
2007	1900.10
2008	18.69

```
7 rows in set (0.001 sec)
```