

1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
KD3-98829-upendra> select * from customers where sname = 1001;
ERROR 1054 (42S22): Unknown column 'sname' in 'where clause'
KD3-98829-upendra> select * from customers where snum = 1001;
+-----+-----+-----+-----+-----+
| cnum | cname | city | rating | snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
KD3-98829-upendra> select cname , rating from customers where city = "San jose";
+-----+-----+
| cname | rating |
+-----+-----+
| Liu | 200 |
| Cisneros | 300 |
| Liu | 200 |
| Cisneros | 300 |
+-----+-----+
4 rows in set (0.00 sec)

KD3-98829-upendra>
```

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
KD3-98829-upendra> select distinct snum from orders;
+-----+
| snum |
+-----+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+-----+
5 rows in set (0.00 sec)
```

4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
KD3-98829-upendra> select * from orders where amt>1000;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
12 rows in set (0.00 sec)
```

5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
KD3-98829-upendra> select sname ,city from salespeople where city = london AND comm >0.10;
ERROR 1054 (42S22): Unknown column 'london' in 'where clause'
KD3-98829-upendra> select sname ,city from salespeople where city = "london" AND comm >0.10;
+-----+-----+
| sname | city |
+-----+-----+
| Peel  | London |
| Motika | London |
| Peel  | London |
| Motika | London |
+-----+-----+
4 rows in set (0.00 sec)

KD3-98829-upendra> █
```

- Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```

2 rows in set (0.00 sec)

KD3-98829-upendra> select *from customers where city = "Rome" OR rating>100;
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome   | 100    | 1004 |
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome   | 100    | 1004 |
+-----+-----+-----+-----+-----+
10 rows in set (0.00 sec)

```

- What will be the output from the following query? Select \* from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```

the right syntax to use near '?1990-10-03? AND cnum > 2003))' at line 1
KD3-98829-upendra> Select * from Orders where (amt < 1000 OR NOT (odate = 1990-10-03 AND cnum > 2003));
+-----+-----+-----+-----+-----+
| onum | amt     | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69   | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19  | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75   | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95  | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
| 3001 | 18.69   | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19  | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75   | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95  | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
20 rows in set, 1 warning (0.01 sec)

KD3-98829-upendra>

```

8. What will be the output of the following query? Select \* from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;

```
KD3-98829-upendra> Select * from Orders where NOT (odate = '1990-10-03' OR snum
-> Select * from Orders where NOT (odate = 1990-10-03 OR snum >1006) AND amt >= 1500;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version fo
the right syntax to use near '?1990-10-03? OR snum
Select * from Orders where NOT (odate = 1990-10-03 OR snum ' at line 1
KD3-98829-upendra> Select * from Orders where NOT (odate = 1990-10-03 OR snum >1006) AND amt >= 1500;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
10 rows in set, 1 warning (0.01 sec)
```

9. What is a simpler way to write this query? Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
+-----+-----+-----+-----+
10 rows in set (0.00 sec)

KD3-98829-upendra> Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);
+-----+-----+-----+-----+
| snum | sname | city   | comm |
+-----+-----+-----+-----+
| 1001 | Peel  | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
| 1001 | Peel  | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
+-----+-----+-----+-----+
4 rows in set (0.01 sec)

KD3-98829-upendra> Where (comm >= .12 AND comm <= .14);
```

10. Write a query that selects all orders except those with amount less than 100.

20 rows in set (0.00 sec)

```
KD3-98829-upendra> select * from orders where amont<100;  
ERROR 1054 (42S22): Unknown column 'amont' in 'where clause'  
KD3-98829-upendra> select * from orders where amt<100;
```

| onum | amt   | odate      | cnum | snum |
|------|-------|------------|------|------|
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |

4 rows in set (0.00 sec)