

ASSIGNMENT DBT 7

Use appropriate joins to solve following queries. Note: To solve below queries, use “sales” database.

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
Windows PowerShell
+-----+
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+
10 rows in set (0.006 sec)

KD4_98828_Gayatri@localhost>SELECT * FROM SALESPEOPLE;
+-----+
| snum | sname | city | comm |
+-----+
| 1001 | Peel | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
| 1004 | Motika | London | 0.11 |
| 1007 | Rifkin | Barcelona | 0.15 |
| 1003 | Axelrod | New York | 0.10 |
+-----+
5 rows in set (0.010 sec)

KD4_98828_Gayatri@localhost>SELECT o.onum , c.cname from ORDERS o INNER JOIN CUSTOMERS c ON o.cnum=c.cnum;
+-----+
| onum | cname |
+-----+
| 3001 | Cisneros |
| 3003 | Hoffman |
| 3002 | Pereira |
| 3005 | Liu |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass |
| 3008 | Clemens |
| 3010 | Grass |
| 3011 | Clemens |
+-----+
10 rows in set (0.009 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
Windows PowerShell
+-----+
| Giovanni | Axelrod | 3009 |
| Grass | Serres | 3007 |
| Liu | Serres | 3007 |
| Clemens | Peel | 3008 |
| Hoffman | Peel | 3008 |
| Grass | Serres | 3010 |
| Liu | Serres | 3010 |
| Clemens | Peel | 3011 |
| Hoffman | Peel | 3011 |
+-----+
16 rows in set (0.020 sec)

KD4_98828_Gayatri@localhost>SELECT c.cname ,s.sname, o.onum FROM salespeople s INNER JOIN customers c ON c.snum=s.snum
-> -> INNER JOIN orders o ON o.snum=c.cnum;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for
the right syntax to use near 'INNER JOIN orders o ON o.snum=c.cnum' at line 2
KD4_98828_Gayatri@localhost>SELECT c.cname , s.sname,o.onum FROM salespeople s INNER JOIN customers c ON c.snum=s.snum
-> INNER JOIN orders o ON o.cnum=c.cnum;
+-----+
| cname | sname | onum |
+-----+
| Cisneros | Rifkin | 3001 |
| Hoffman | Peel | 3003 |
| Pereira | Motika | 3002 |
| Liu | Serres | 3005 |
| Cisneros | Rifkin | 3006 |
| Giovanni | Axelrod | 3009 |
| Grass | Serres | 3007 |
| Clemens | Peel | 3008 |
| Grass | Serres | 3010 |
| Clemens | Peel | 3011 |
+-----+
10 rows in set (0.012 sec)

KD4_98828_Gayatri@localhost>
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
Windows PowerShell
+-----+
| sname | cname |
+-----+
| Peel  | Hoffman |
| Axelrod | Giovanni |
| Serres | Liu |
| Serres | Grass |
| Peel  | Clemens |
| Rifkin | Cisneros |
| Motika | Pereira |
+-----+
7 rows in set (0.009 sec)

KD4_98828_Gayatri@localhost>SELECT s.sname , c.cname FROM salespeople s INNER JOIN customers c ON s.snum=c.snum
-> WHERE comm>0.12;
+-----+
| sname | cname |
+-----+
| Serres | Liu |
| Serres | Grass |
| Rifkin | Cisneros |
+-----+
3 rows in set (0.009 sec)

KD4_98828_Gayatri@localhost>SELECT s.sname , c.cname, s.comm FROM salespeople s INNER JOIN customers c ON s.snum=c.snum
-> WHERE comm>0.12;
+-----+
| sname | cname | comm |
+-----+
| Serres | Liu | 0.13 |
| Serres | Grass | 0.13 |
| Rifkin | Cisneros | 0.15 |
+-----+
3 rows in set (0.014 sec)

KD4_98828_Gayatri@localhost>
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
Windows PowerShell
+-----+
| sname | cname |
+-----+
| Peel  | Hoffman |
| Axelrod | Giovanni |
| Serres | Liu |
| Serres | Grass |
| Peel  | Clemens |
| Rifkin | Cisneros |
| Motika | Pereira |
+-----+
7 rows in set (0.009 sec)

KD4_98828_Gayatri@localhost>SELECT s.sname , c.cname FROM salespeople s INNER JOIN customers c ON s.snum=c.snum
-> WHERE comm>0.12;
+-----+
| sname | cname |
+-----+
| Serres | Liu |
| Serres | Grass |
| Rifkin | Cisneros |
+-----+
3 rows in set (0.009 sec)

KD4_98828_Gayatri@localhost>SELECT s.sname , c.cname, s.comm FROM salespeople s INNER JOIN customers c ON s.snum=c.snum
-> WHERE comm>0.12;
+-----+
| sname | cname | comm |
+-----+
| Serres | Liu | 0.13 |
| Serres | Grass | 0.13 |
| Rifkin | Cisneros | 0.15 |
+-----+
3 rows in set (0.014 sec)

KD4_98828_Gayatri@localhost>
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed

```
Windows PowerShell
+-----+-----+
10 rows in set (0.015 sec)

KD4_98828_Gayatri@localhost>SELECT s1.sname, s2.sname ,s1.city from salesperson s1 inner join salesperson s2 on s1.c
ity =s2.city ;
ERROR 1146 (42S02): Table 'sales_db.salesperson' doesn't exist
KD4_98828_Gayatri@localhost>select s1.sname ,s2.sname ,s1.city from salespeople s1 inner join salespeople s2 on s1.c
ity=s2.city ;
+-----+-----+-----+
| sname | sname | city |
+-----+-----+-----+
| Motika | Peel | London |
| Peel | Peel | London |
| Serres | Serres | San Jose |
| Motika | Motika | London |
| Peel | Motika | London |
| Rifkin | Rifkin | Barcelona |
| Axelrod | Axelrod | New York |
+-----+-----+-----+
7 rows in set (0.016 sec)

KD4_98828_Gayatri@localhost>select s1.sname ,s2.sname ,s1.city from salespeople s1 inner join salespeople s2 on s1.c
ity=s2.city AND s1.snum<s2.snum;
+-----+-----+-----+
| sname | sname | city |
+-----+-----+-----+
| Peel | Motika | London |
+-----+-----+-----+
1 row in set (0.009 sec)

KD4_98828_Gayatri@localhost>SELECT * FROM salespeople;
+-----+-----+-----+
| sname | snum | city |
+-----+-----+-----+
| Motika | 1 | London |
| Peel | 2 | London |
| Serres | 3 | San Jose |
| Motika | 4 | London |
| Rifkin | 5 | Barcelona |
| Axelrod | 6 | New York |
+-----+-----+-----+
```