

1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
4 rows in set (0.011 sec)

KD4_98828_Gayatri@localhost>SELECT SNUM, MAX(AMT) AS MAX_ORDER_AMOUNT
-> FROM ORDERS
-> WHERE AMT > 3000
-> GROUP BY SNUM;
+-----+-----+
| SNUM | MAX_ORDER_AMOUNT |
+-----+-----+
| 1002 | 5160.45 |
| 1001 | 9891.88 |
+-----+-----+
2 rows in set (0.014 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM CUSTOMERS
-> WHERE SNUM = 1001;
+-----+-----+-----+-----+-----+
| cnum | cname | city | rating | snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
+-----+-----+-----+-----+-----+
2 rows in set (0.011 sec)

KD4_98828_Gayatri@localhost>SELECT RATING, CNAME
-> FROM CUSTOMERS
-> WHERE CITY = 'San Jose';
```

2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
+-----+-----+-----+-----+-----+
2 rows in set (0.011 sec)

KD4_98828_Gayatri@localhost>SELECT RATING, CNAME
-> FROM CUSTOMERS
-> WHERE CITY = 'San Jose';
+-----+-----+
| RATING | CNAME |
+-----+-----+
| 200 | Liu |
| 300 | Cisneros |
+-----+-----+
2 rows in set (0.007 sec)

KD4_98828_Gayatri@localhost>SELECT DISTINCT SNUM
-> FROM ORDERS;
+-----+
| SNUM |
+-----+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+-----+
5 rows in set (0.008 sec)

KD4_98828_Gayatri@localhost>SELECT *
```

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```

Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
| 200 | Liu |
| 300 | Cisneros |
+-----+
2 rows in set (0.007 sec)

KD4_98828_Gayatri@localhost>SELECT DISTINCT SNUM
-> FROM ORDERS;
+-----+
| SNUM |
+-----+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+-----+
5 rows in set (0.008 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE AMT > 1000;
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
+-----+-----+-----+-----+-----+

```

- Write a query that will display all the orders for amount more than Rs. 1,000.

```

Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
| 200 | Liu |
| 300 | Cisneros |
+-----+
2 rows in set (0.007 sec)

KD4_98828_Gayatri@localhost>SELECT DISTINCT SNUM
-> FROM ORDERS;
+-----+
| SNUM |
+-----+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+-----+
5 rows in set (0.008 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE AMT > 1000;
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
+-----+-----+-----+-----+-----+

```

- Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```

Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
| 1002 |
| 1003 |
+-----+
5 rows in set (0.008 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE AMT > 1000;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.008 sec)

KD4_98828_Gayatri@localhost>SELECT SNAME, CITY
-> FROM SALESPEOPLE
-> WHERE CITY = 'London'
-> AND COMM > 0.10;
+-----+-----+
| SNAME | CITY |
+-----+-----+
| Peel  | London |
+-----+-----+

```

6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```

Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
+-----+-----+-----+-----+-----+
6 rows in set (0.008 sec)

KD4_98828_Gayatri@localhost>SELECT SNAME, CITY
-> FROM SALESPEOPLE
-> WHERE CITY = 'London'
-> AND COMM > 0.10;
+-----+-----+
| SNAME | CITY |
+-----+-----+
| Peel  | London |
| Motika | London |
+-----+-----+
2 rows in set (0.010 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM CUSTOMERS
-> WHERE RATING > 100
-> OR CITY = 'Rome';
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome   | 100    | 1004 |
+-----+-----+-----+-----+-----+

```

7. What will be the output from the following query? Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```

Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
KD4_98828_Gayatri@localhost>SELECT *
-> FROM CUSTOMERS
-> WHERE RATING > 100
-> OR CITY = 'Rome';
+-----+-----+-----+-----+-----+
| cnum | cname | city | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome | 200 | 1003 |
| 2003 | Liu | San Jose | 200 | 1002 |
| 2004 | Grass | Berlin | 300 | 1002 |
| 2008 | Cisneros | San Jose | 300 | 1007 |
| 2007 | Pereira | Rome | 100 | 1004 |
+-----+-----+-----+-----+-----+
5 rows in set (0.010 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE (AMT < 1000
-> OR NOT (ODATE = '1990-10-03' AND CNUM > 2003));
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+

```

8. What will be the output of the following query? Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;

```

Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
5 rows in set (0.010 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE (AMT < 1000
-> OR NOT (ODATE = '1990-10-03' AND CNUM > 2003));
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
8 rows in set (0.031 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE NOT (ODATE = '1990-10-03' OR SNUM > 1006)
-> AND AMT >= 1500;
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
+-----+-----+-----+-----+-----+

```

9. What is a simpler way to write this query? Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
+-----+-----+-----+-----+-----+
8 rows in set (0.031 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE NOT (ODATE = '1990-10-03' OR SNUM > 1006)
-> AND AMT >= 1500;
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
3 rows in set (0.011 sec)

KD4_98828_Gayatri@localhost>SELECT SNUM, SNAME, CITY, COMM
-> FROM SALESPEOPLE
-> WHERE (COMM >= .12 AND COMM <= .14);
+-----+-----+-----+-----+
| SNUM | SNAME | CITY | COMM |
+-----+-----+-----+-----+
| 1001 | Peel | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
+-----+-----+-----+-----+
2 rows in set (0.011 sec)

KD4_98828_Gayatri@localhost>SELECT *
```

10. Write a query that selects all orders except those with amount less than 100.

```
Windows PowerShell x Windows PowerShell x Windows PowerShell x + v
3 rows in set (0.011 sec)

KD4_98828_Gayatri@localhost>SELECT SNUM, SNAME, CITY, COMM
-> FROM SALESPEOPLE
-> WHERE (COMM >= .12 AND COMM <= .14);
+-----+-----+-----+-----+
| SNUM | SNAME | CITY | COMM |
+-----+-----+-----+-----+
| 1001 | Peel | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
+-----+-----+-----+-----+
2 rows in set (0.011 sec)

KD4_98828_Gayatri@localhost>SELECT *
-> FROM ORDERS
-> WHERE NOT AMT < 100;
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
```