

03 — No-Battery Reference World (the hand-built "twin ship")

No battery; loads pre-inflated to average + FULL swing: propulsion **12 036.15** (11 463+573.15), hotel **3 876** (3 800+76). This is exactly the internal "world B" the Battery Benefit is computed against — built by hand so you can see it.

Battery Contribution

Absent — no battery configured. (Tiles in the form show nothing.)

Power Demands

$SG\ 3\ 250 \cdot AE\ 626 \cdot ME = 12\ 036.15 + 3\ 250 = \mathbf{15\ 286}$ (63.69 %) · Energy ME $15\ 286.15 \times 5\ 000 = \mathbf{76\ 430\ 750}$ (remember: ME energy includes driving the SG).

Baseline & IL1

No battery $\Rightarrow$ baseline default = **last row** (worst: 2 ME+SG, 2.7305 $\rightarrow$ **13 652.6 t/yr**), not 3rd-from-worst — the Krishna rule applies only when a battery is active. IL1 optimal = 2.69198 $\rightarrow$ **13 459.9 t/yr**; savings 192.7 t.

The proof this file exists for

13 459.9

-

13 286.2 (IL1 of test 01)

=

173.7

=

test 01's green badge

✓

13 459.9

-

13 371.2 (IL1 of test 02)

=

88.7

=

test 02's green badge

✓

One file proves both benefits, because the no-battery twin is the same ship in both comparisons.

Takeaway: the dual-scenario (R3a) mechanism reproduced with two imports and a subtraction — no trust in hidden code required.