

FIELDCOMMS

Incident Management System v1.0

INSTALLATION GUIDE

ASUS RT-BE58 Go · UniFi Switch Flex 2.5G · Raspberry Pi 5 · Pironman MAX 5

RACES · ARES · Starcom · K9ESV · June 22, 2026

Table of Contents

1.	Overview & What's Included	3
2.	Hardware Requirements	4
3.	Before You Begin — Prerequisites	11
4.	Step 1: Network Hardware Setup	13
5.	Step 2: Download & Run the Installer	16
6.	Step 3: Installer Configuration Options	19
7.	Step 4: Raspberry Pi 5 — Static IP Configuration	20
7b.	Step 4b: RAID 1 NVMe Setup — Pironman MAX 5	22
8.	Step 5: Kiwix Offline Library Setup	24
9.	Step 6: FCC Amateur Database	26
10.	Step 7: APRS Setup (Graywolf + YAAC)	27
11.	Step 8: Printer Setup	31
12.	Step 9: Pat Winlink — Verify & Configure	36
12.	Step 10: Windows Laptop — Winlink Express + JS8Call	37
13.	Step 11: First Boot Verification	41
14.	Network Architecture Reference	43
14.	Web Dashboard Reference	45
14.	Service & Port Reference	46
15.	Maintenance & Updates	47
16.	Troubleshooting	48
17.	Quick Reference Card	50

1. Overview & What's Included

FieldComms is a complete off-grid emergency communications server for Raspberry Pi. The ASUS RT-BE58 Go travel router provides a dedicated Wi-Fi access point called EMCOMM-NET — the Pi itself does not broadcast Wi-Fi. Any phone, tablet, or laptop on scene connects to EMCOMM-NET and accesses all EmComm tools through a standard web browser with no internet required. When Ethernet internet is available at the site, live features such as NWS weather alerts, HF propagation data, and APRS-IS automatically activate.

SAR Network Operations: The Starcom Net Logger includes a dedicated SAR Net mode (Search & Rescue) accessible directly from the Starcom / Public Safety dashboard. It provides a SAR-specific check-in log with unit type tracking, zone assignments, and resource status. The Starcom Resource Map provides the tactical overlay for SAR unit positions. These features are integrated into the main FieldComms platform — no separate module is required.

COMPONENT	DESCRIPTION	COMPONENT	DESCRIPTION
30 Web Pages	Full dashboard, net logs, ICS forms, maps, roster, cheat sheets	Dead Man's Switch	Per-net inactivity monitor with warning and trigger states
Net Control Logger	Amateur + Starcom nets, FCC autofill, ICS-309 export	Pre-Flight Checklist	GO/CAUTION/NO-GO deployment readiness check
ICS Platform	Command, Operations, Planning, Logistics, Finance sections	HF Propagation	Solar indices, band conditions, A/K-index
APRS Tactical Map	Graywolf + YAAC merged, offline tiles, overlays	Repeater Database	RepeaterBook CSV, filter by band, mode, ARES affiliation
Member Roster	MCESV/MCEMA directory with certs, equipment, activations	Reference Library	Upload and serve field reference docs across EMCOMM-NET
NTS Radiogram	ARRL-formatted radiogram generator with traffic log	Kiwix Library	WikiMed, Wikipedia, iFixit — offline at port 8081
ICS-213/214/309	Fillable ICS forms with print output and incident archiving	FCC Callsign Lookup	~800K licensees — instant offline search
Winlink Form Import	Import Winlink Express XML forms to incident archive	Pat Winlink	Browser-based backup Winlink client at port 8090
JS8Call Integration	Dashboard card opens JS8Call web API on Windows laptop	ICS Planning P	Interactive 15-phase planning cycle guide

2. Hardware Requirements

Supported Hardware — Raspberry Pi Servers

FieldComms v1.0 uses two Raspberry Pi 5 units: one as the FieldComms application server and one as the dedicated AMPRNet / 44Net gateway. Keeping them separate means the gateway can be rebooted, reconfigured, or upgraded without affecting the FieldComms server, net logs, or active incidents.

UNIT	HARDWARE	STORAGE	ROLE
FieldComms Server	Raspberry Pi 5 — 16 GB RAM / Pironman MAX 5 tower enclosure (dual M.2 NVMe, OLED, active cooling)	2× 1 TB NVMe SSD / configured as RAID 1	Runs all FieldComms services: web server, FCC database, net logging, ICS platform, APRS, Kiwix, Winlink, maps, and health monitor. Static IP: 192.168.50.1
44Net Gateway	Raspberry Pi 5 — 16 GB RAM / Argon NEO 5 M.2 BRED case (compact, passive-cooled, M.2 SATA slot) / Pi OS Desktop (64-bit)	256 GB M.2 SATA SSD (OS + WireGuard + routing + status service)	Dedicated AMPRNet / 44Net gateway. Runs WireGuard tunnel to amprgw.ampr.org, ip routing between EMCOMM-NET and 44.0.0.0/8, and a status page at 192.168.50.2. Completely independent from the FieldComms server.

Network Hardware

Wi-Fi is provided by the ASUS RT-BE58 Go travel router — neither Pi runs a Wi-Fi hotspot. The UniFi Switch Lite 16 PoE provides 16 wired gigabit ports for both Pi servers, the Windows laptop, four operator workstations, a network printer, and room for expansion. This replaces the original 5-port Flex 2.5G which is too small for the full deployment.

DEVICE	ROLE	NOTES
ASUS RT-BE58 Go	Wi-Fi 7 access point / DHCP server / WAN gateway	Dual-band Wi-Fi 7 (802.11be). 2.5G LAN uplink to switch. USB-C 18W power. Handles EMCOMM-NET Wi-Fi, DHCP for 192.168.50.100-200, and optional WAN routing.
UniFi Switch Lite 16 PoE	16-port gigabit managed switch / 8x PoE + 8x non-PoE / 2x 1G SFP uplink	Replaces the 5-port Flex 2.5G. Port layout: 1=ASUS router uplink, 2=FieldComms Pi, 3=44Net Gateway Pi, 4=Windows laptop, 5=color MFP printer, 6-9=Pi 500 workstations, 10=Starlink (optional), 11-16=spare. ~\$200. PoE powers future UniFi APs without a separate injector.

Accessories & Cables

ITEM	REQUIRED?	PURPOSE
USB-A drive (32 GB+, labeled FIELDCOMMS)	Recommended	Auto-backup trigger — insert to back up all runtime data instantly
External USB hard drive 1 TB+ (e.g. LaCie Rugged or LaCie Mobile Drive)	Recommended	Incident archive and full system backup. LaCie Rugged is shock/drop/crush resistant. Label FIELDCOMMS for auto-backup compatibility.
USB GPS receiver (u-blox or GlobalSat)	Optional	Live position for tactical map and NWS alerts
USB TNC — Digirig Mobile or Signalink USB	Optional	Required for APRS transmit/receive via Graywolf or YAAC. FieldComms assigns a stable /dev/tnc0 device name via udev.
Powered USB hub (4- or 7-port, with power supply)	Optional	Recommended if connecting GPS + TNC + backup drive simultaneously. Must be powered — unpowered hubs can cause instability.
USB Printer (e.g. Brother HL-L2350DW, HP LaserJet)	Optional	Shared across EMCOMM-NET via CUPS (installed automatically). Or connect a Wi-Fi printer directly to EMCOMM-NET.

USB Hub & Multi-Device Setup

The Pi 5 has four USB ports. A powered USB hub lets you connect GPS, TNC, backup drive, and other peripherals simultaneously. FieldComms uses udev rules to assign stable device names regardless of hub port or plug order.

DEVICE	STABLE NAME	HOW ASSIGNED	SERVICE
USB GPS receiver	/dev/gps0	udev rule matches by USB vendor/product ID	gpsd → tactical map
Digirig Mobile TNC	/dev/tnc0 /dev/digirig	udev rule matches by vendor ID + product string "Digirig Mobile". Distinguished from GPS even though both use CP2102 chip.	YAAC / Graywolf APRS
Signalink USB TNC	/dev/tnc0 /dev/signalink	udev rule matches by Texas Instruments PCM2904 chip. No conflict with GPS.	YAAC / Graywolf APRS
LaCie / USB backup drive (labeled FIELDCOMMS)	/dev/sdX (auto-mounted)	udev backup rule triggers on label FIELDCOMMS. Drive letter assigned dynamically.	fieldcomms-backup@.service

Both the Digirig Mobile TNC and GlobalSat BU-353-S4 GPS use the same USB chip (Silicon Labs CP2102, vendor 10c4:ea60). FieldComms distinguishes them by USB product description string. The GPS rule excludes Digirig; the TNC rule requires the Digirig product string. Verify with: `udevadm info -a -n /dev/ttyUSB0 | grep -E "idVendor|idProduct|product"`

```
# List all USB serial devices
ls -la /dev/ttyUSB* /dev/ttyACM* 2>/dev/null
# Check the stable symlinks
ls -la /dev/gps0 /dev/tnc0 2>/dev/null
# Confirm GPS is outputting NMEA sentences
sudo cat /dev/gps0
# Use /dev/tnc0 in YAAC → Configure → Ports → Serial TNC
```

Complete Bill of Materials

ITEM	MODEL / SPEC	WHERE TO BUY
— FieldComms Server (Pi 5 — 16 GB) —		
Raspberry Pi 5 — 16 GB RAM	Raspberry Pi 5 Model B (16 GB)	raspberrypi.com · Adafruit · PiShop.us
Pironman MAX 5 enclosure	Pironman MAX 5 (tower, dual M.2 NVMe, OLED display, active cooling fans)	52pi.com · Amazon
NVMe SSD × 2 (RAID 1)	1 TB M.2 2280 PCIe Gen 3/4 NVMe (e.g. WD Blue SN580 or Samsung 980)	Amazon · B&H · Newegg
Pi 5 USB-C power supply	Official Raspberry Pi 27W USB-C PD power supply	raspberrypi.com · Adafruit · Amazon
MicroSD card (boot / initial RAID setup)	32 GB Class 10 / A1 microSD (removed after RAID is built)	Amazon
— 44Net Gateway (Pi 5 — 8 GB) —		
Raspberry Pi 5 — 16 GB RAM	Raspberry Pi 5 Model B (16 GB) — dedicated AMPRNet gateway (matches FieldComms Pi for spare-parts commonality)	raspberrypi.com · Adafruit · PiShop.us

ITEM	MODEL / SPEC	WHERE TO BUY
Argon NEO 5 M.2 BRED case	Argon NEO 5 M.2 BRED (compact, passive-cooled, M.2 SATA slot, aluminum) — fits Pi 5	argon40.com · Amazon (~\$35)
M.2 SATA SSD (gateway OS + config)	256 GB M.2 2242 or 2280 SATA SSD — OS, WireGuard config, routing tables	Amazon · Newegg (~\$25)
Pi 5 USB-C power supply	Official Raspberry Pi 27W USB-C PD power supply — one per Pi	raspberrypi.com · Adafruit · Amazon
— Networking (upgraded from 5-port to 16-port) —		
ASUS RT-BE58 Go travel router	ASUS RT-BE58 Go (Wi-Fi 7, 2.5G LAN uplink, USB-C 18W power)	Amazon · Best Buy · B&H;
UniFi Switch Lite 16 PoE	Ubiquiti USW-Lite-16-PoE (16-port GbE, 8× PoE, 2× SFP uplink, 45W) — replaces Flex 2.5G-5	ui.com · Amazon · B&H; (~\$200)
CAT 6 Ethernet cables × 10	1 ft – 6 ft CAT 6 patch cables — router to switch, both Pis, laptop, printer, 4× workstations	Amazon · Monoprice
— Radio & Comms —		
Icom IC-7300 HF transceiver	Icom IC-7300 (HF/50 MHz, built-in USB sound card)	Ham Radio Outlet · DX Engineering · Amazon
USB-A to USB-B cable (IC-7300 to laptop)	USB-A to USB-B, shielded, 6 ft	Amazon · Monoprice
Windows laptop (Winlink Express + JS8Call)	Any Windows 10/11 laptop with USB-A port and Wi-Fi	Best Buy · Amazon
— Accessories — Backup & Connectivity —		
USB-A drive (32 GB+, labeled FIELDCOMMS)	32 GB+ USB 3.0 drive — auto-backup trigger when inserted	Amazon
External USB hard drive 1 TB+ (e.g. LaCie Rugged)	1 TB+ USB 3.0/USB-C portable drive — label FIELDCOMMS for auto-backup	B&H; · Amazon · Best Buy
USB GPS receiver (optional)	GlobalSat BU-353-S4 or u-blox USB GPS puck — provides live position to tactical map and NWS alerts	Amazon
USB TNC — Digirig Mobile (optional)	Digirig Mobile v1.x — USB soundcard + serial CAT in one compact unit	digirig.net · Amazon
USB TNC — Signalink USB (optional)	Tigertronics Signalink USB — requires rig-specific interface cable	tigertronics.com · Ham Radio Outlet · Amazon
Powered USB hub (optional)	Anker 7-Port USB 3.0 with AC power adapter — must be powered hub, not bus-powered	Amazon · Best Buy
Avery 5371 business card sheets (operator access cards)	Avery 5371 — 10 cards per sheet, laser or inkjet — for printed operator access cards	Office Depot · Amazon · Staples

ITEM	MODEL / SPEC	WHERE TO BUY
— Printers — Monochrome Laser (USB via CUPS or direct Wi-Fi) —		
Brother HL-L2350DW (recommended)	Monochrome laser — USB + Wi-Fi — excellent Linux driver — fast, duplex, durable	Best Buy · Amazon (~\$130)
HP LaserJet Pro M15w / P1102w	Monochrome laser — USB + Wi-Fi — HPLIP driver auto-installs with CUPS	Best Buy · Amazon (~\$150)
— Printers — Color Multifunction Laser (USB, Wi-Fi, or Ethernet) —		
Brother MFC-L3770CDW	Color laser MFP — print, scan, copy, fax — USB + Wi-Fi + Ethernet — full Linux CUPS support — prints color ICS maps and IAP packages	Amazon · Best Buy (~\$400)
HP Color LaserJet Pro MFP M479fdw	Color laser MFP — print, scan, copy, fax — USB + Wi-Fi + Ethernet — HPLIP driver works out of the box with CUPS	Amazon · B&H; (~\$500)
Canon imageCLASS MF743Cdw	Color laser MFP — letter + legal — USB + Wi-Fi + Ethernet — Linux CAPT driver — good for permanent EOC installations	Amazon · Office Depot (~\$450)
— Printers — Portable / Battery-Powered (field deployments without shore power) —		
Canon PIXMA TR150	Compact inkjet — built-in rechargeable battery — ~200 pages per charge — USB + Wi-Fi — letter size	Best Buy · Amazon (~\$200)
HP OfficeJet 200	Portable inkjet — larger paper tray — optional battery accessory — USB + Wi-Fi — good for shelter stations	Best Buy · Amazon (~\$180)
— Operator Workstations — Raspberry Pi 500 / 500+ (qty: 4 recommended) —		
Raspberry Pi 500 keyboard computer ×4	Pi 500 standalone — Pi 5 chip, 8 GB RAM, 32 GB A2 microSD, integrated keyboard — one per operator station	raspberrypi.com · Adafruit · Amazon (~\$90 each)
Raspberry Pi 500+ ×4 (alternative)	Pi 500+ — same as Pi 500 but with Pi 5 latest revision chip and 2× USB3 — specify if 501(c)(3) funding allows premium spec	raspberrypi.com · Adafruit (~\$110 each)
Raspberry Pi Monitor 15.6" ×4	15.6" Full HD IPS touchscreen — built-in speakers — kickstand — VESA mount — USB-C powered from Pi 500 — one per station	raspberrypi.com · GigaParts · Amazon (~\$100 each)
micro-HDMI to HDMI cable ×4	1m micro-HDMI to standard HDMI — Pi 500 to Monitor video connection — one per station	Included in Pi 500 Desktop Kit · Amazon (~\$8 each)
USB-C power supply for Pi 500 ×4	Official Raspberry Pi 27W USB-C PD supply — one per station — Pi 500 can also be powered from Monitor USB-C port	raspberrypi.com · Adafruit (~\$12 each)

ITEM	MODEL / SPEC	WHERE TO BUY
Raspberry Pi 500 Desktop Kit ×4 (bundle option)	Pi 500 + official mouse + micro-HDMI cable bundled — add Monitor separately — simpler ordering than individual parts	raspberrypi.com · Amazon (~\$120 each)

AiMesh Coverage Extension — Optional Bill of Materials

ITEM	MODEL / SPEC	WHERE TO BUY
AiMesh node router (wireless backhaul)	ASUS RT-BE58 Go (same as primary — simplest pairing) or any AiMesh-compatible ASUS router	Amazon · Best Buy · B&H;
AiMesh node router (high-capacity venues)	ASUS ZenWiFi Pro ET12 or RT-AX88U Pro — better range and capacity for large buildings	Amazon · B&H; · Costco
CAT 6 Ethernet cable (wired backhaul — recommended)	CAT 6 cable from UniFi switch to node LAN port. Length as needed.	Amazon · Monoprice · Home Depot
USB-C power bank (field power for node)	10,000+ mAh, 18W+ USB-C PD — one per node for field deployment without shore power	Amazon

DEPLOYMENT SCENARIO	RECOMMENDED SETUP
Single room EOC ($\leq 2,500$ sq ft)	1× RT-BE58 Go primary only — no extension needed
Multi-room EOC or large shelter (2,500–7,500 sq ft)	1× RT-BE58 Go primary + 1 AiMesh node (wireless or wired backhaul)
Large building or campus (7,500–20,000 sq ft)	1× primary + 2–3 nodes, wired backhaul recommended for all nodes
Outdoor SAR staging area	1× primary at command post + RT-BE58 Go nodes at field positions on battery



You do not need to pre-purchase AiMesh nodes for every deployment. Start with the primary RT-BE58 Go and add nodes only when coverage is insufficient. Pairing a new node takes under 5 minutes on site.

SD Card / Storage Sizing Guide

TIER	WHAT FITS / REQUIREMENT
Minimum (boot only)	8 GB — OS only, RAID boot loader. FieldComms runs from NVMe RAID.
Recommended	32 GB — OS + swap + logs + temp files during initial RAID setup.
Kiwix Tier 1	~3 GB additional on RAID — WikiMed + Wikipedia Mini + Wikivoyage.
Kiwix Tier 2	~10 GB additional on RAID — adds iFixit, Wikibooks, Wikiversity.
FCC Database	~600 MB on RAID — full US amateur license database (~800K records).

1 Flash OS & Build RAID 1 — Do This First

Step 1: Flash the OS and Build the RAID Array

These two tasks must be completed before anything else. The Raspberry Pi OS must be installed and the RAID 1 array assembled before the FieldComms installer runs. If you are using a single NVMe drive (no RAID), flash the OS to it directly and skip the RAID build section.

1A Flash the Operating System

OS EDITION	PROS	CONS
Raspberry Pi OS Lite (64-bit) — Recommended for production	Minimal overhead. All RAM available to FieldComms. Fast boot. Smaller attack surface.	No local browser or GUI. All interaction via SSH or via EMCOMM-NET browser on another device.
Raspberry Pi OS Desktop (64-bit) — Good for setup and troubleshooting	Local browser for testing. GUI for initial Wi-Fi setup and configuration. Easier for new users.	More RAM used by desktop environment. Slightly longer install time.
Ubuntu Server 24.04 LTS — Also supported	LTS kernel. Familiar to Linux admins. Long-term package support.	Some package names differ from Raspberry Pi OS. Slightly more manual setup.

Use **Raspberry Pi Imager** (download from raspberrypi.com/software) to flash the OS to either a microSD card (for single-drive setup) or directly to the NVMe SSD (if not using RAID). During the Imager advanced options, set:

IMAGER OPTION	VALUE / REASON
Hostname	fieldcomms.local — makes the Pi discoverable as fieldcomms.local on the network
Username	fieldcomms — the FieldComms installer expects this username
Password	Choose a strong password and record it — required for SSH and CUPS admin
Enable SSH	Yes — required for remote access from your laptop during setup
Wi-Fi	Set your home or lab Wi-Fi during initial OS setup. EMCOMM-NET comes later.
Locale / Timezone	US/Central for McHenry County operations

1B Build the RAID 1 Array (Pironman MAX 5 — Dual NVMe)

The Pironman MAX 5 enclosure has two M.2 NVMe slots. Configuring them as a RAID 1 mirror means both drives always contain identical data. If one SSD fails, the Pi keeps running on the surviving drive with no data loss and no operator action required. Skip this section entirely if you are using a single NVMe drive.

Complete the RAID build BEFORE running the FieldComms installer. The installer must be run on the final storage configuration. If your OS is already running from a single drive, back it up before proceeding.

Physical Installation

SLOT	DRIVE	LINUX DEVICE NAME
M.2 Slot 1 (primary)	1 TB NVMe SSD (e.g. WD Blue SN580)	/dev/nvme0n1
M.2 Slot 2 (mirror)	1 TB NVMe SSD — identical model recommended	/dev/nvme1n1

Boot from a microSD card with Raspberry Pi OS Lite to perform the initial RAID setup. After the array is built and the OS copied to it, the SD card is removed.

Build the Array

```
# Install mdadm (RAID management tool)
sudo apt-get update && sudo apt-get install -y mdadm

# Create the RAID 1 array (--run skips the "all zeroes" check for speed)
sudo mdadm --create --verbose /dev/md0 \
--level=1 --raid-devices=2 \
/dev/nvme0n1 /dev/nvme1n1

# Check build progress (shows resync percentage – takes ~15 min for 1 TB)
cat /proc/mdstat

# Create a filesystem on the array
sudo mkfs.ext4 -L fieldcomms-raid /dev/md0

# Mount and copy the running OS to the RAID array
sudo mkdir -p /mnt/raid
sudo mount /dev/md0 /mnt/raid
sudo apt-get install -y rsync
sudo rsync -axv --progress / /mnt/raid/

# Save the RAID config so it survives reboots
sudo mdadm --detail --scan | sudo tee -a /mnt/raid/etc/mdadm/mdadm.conf
sudo update-initramfs -u -k all

# Update /boot/cmdline.txt to boot from the RAID array instead of the SD
sudo nano /boot/cmdline.txt
# Change: root=PARTUUID=xxxx → root=/dev/md0
# Then reboot – Pi boots from RAID. Verify with:
cat /proc/mdstat
# Expected: md0 : active raid1 nvme0n1[0] nvme1n1[1] [UU]
```

RAID STATUS	MEANING	ACTION REQUIRED
[UU] (both drives active)	Normal — both drives healthy and in sync	None
[U_] or [_U] (one drive failed)	One drive has failed. Pi is still running on the other.	Power down. Replace failed drive. Run: <code>sudo mdadm /dev/md0 --add /dev/nvme1n1</code> . Array rebuilds automatically.
Resync in progress	Array is rebuilding — normal after first setup or drive replacement	Leave running. Takes 15 – 30 minutes. Pi is usable during rebuild.

 RAID 1 protects against drive failure — it is NOT a backup. Both drives contain identical data, so accidental deletion affects both drives simultaneously. Continue to use the FIELDCOMMS USB auto-backup for regular data backups.

3. Before You Begin — Prerequisites

Complete these prerequisites before running the installer. The installer requires an internet connection for package downloads, the FCC database, and Kiwix ZIM files. After installation, the server operates fully offline.

3.1 Flash the Operating System

OS EDITION	PROS	CONS
Raspberry Pi OS Lite (64-bit) — Recommended for production	Minimal overhead, faster boot, all RAM available to FieldComms services, smaller attack surface	No local browser or GUI — all interaction via SSH or EMCOMM-NET browser
Raspberry Pi OS Desktop (64-bit) — Good for setup and troubleshooting	GUI for initial setup, Raspberry Pi Configuration tool, local browser for testing	More RAM used by desktop environment; install takes longer
Ubuntu Server 24.04 LTS — Also supported	LTS kernel, familiar to Linux admins, good for organizations standardized on Ubuntu	Slightly larger memory footprint; some package names differ

3.2 First Boot — Initial Setup

STEP	ACTION
1	On first boot, complete the initial setup wizard: set username to fieldcomms , set a strong password, configure locale and keyboard, expand filesystem.
2	If using Desktop edition: complete the initial desktop setup wizard.
3	Enable SSH (Lite only): run <code>sudo raspi-config</code> → Interface Options → SSH → Enable

Run a full system update before installing FieldComms (works the same on both editions — Terminal or SSH):

```
# Update all packages to latest versions
sudo apt-get update && sudo apt-get full-upgrade -y
# Reboot to apply kernel updates
sudo reboot
```

3.3 Verify Disk Space

```
# Check available space – should show 20GB+ free for Tier 2 install
df -h /
# Verify RAM
free -h
```

3.4 Internet Connection

Connect the Pi to the internet via Ethernet before running the installer. Wi-Fi can be used during initial setup but Ethernet is strongly preferred for downloading large files — the FCC database is ~600 MB and Kiwix ZIMs range from 500 MB to 25 GB.

3.5 Operator Workstation — Browser Options

FieldComms runs entirely in a web browser. Any modern browser on any device connected to EMCOMM-NET works. For the Raspberry Pi 500 / 500+ used as an operator workstation, three browsers are available:

BROWSER	HOW TO INSTALL	NOTES FOR FIELDCOMMS
Chromium (default)	Pre-installed on Raspberry Pi OS. No action needed.	Best performance for FieldComms. Discovers CUPS printers automatically via Bonjour. Set http://192.168.50.1 as the startup page under Settings → On startup.
Firefox ESR	<code>sudo apt install firefox-esr</code>	Excellent compatibility with all FieldComms pages. Good fallback if Chromium behaves unexpectedly. Also discovers network printers. Slightly lower memory footprint on the Pi 500.
GNOME Web (Epiphany)	<code>sudo apt install epiphany-browser</code>	Very lightweight WebKit browser. Good for Pi 500 with many tabs open. Best for dedicated check-in stations where memory is tight.



For dedicated FieldComms operator stations running Pi 500: set Chromium to open <http://192.168.50.1> on startup. In Chromium: Settings → On startup → Open a specific page → enter <http://192.168.50.1>. The dashboard loads automatically every time the Pi 500 boots.



Wi-Fi is provided by the ASUS RT-BE58 Go router — the Pi does NOT run hostapd. During installation, connect the Pi to the internet via Ethernet through the UniFi switch and ASUS router. After installation, the Pi is always reachable at 192.168.50.1 via wired Ethernet.

2

Network Hardware Setup — ASUS Router + UniFi Switch

Step 2: Network Hardware Setup — ASUS Router + UniFi Switch

Complete this step before running the FieldComms installer. The ASUS router must be configured with the correct LAN subnet (192.168.50.x) before FieldComms is reachable at <http://192.168.50.1>.

1.1 Physical Wiring

The UniFi Switch Lite 16 PoE is the central wiring hub for the entire EMCOMM-NET deployment. Connect everything to the switch, and the switch connects up to the ASUS router. Use short CAT 6 patch cables (1 ft to 3 ft) to keep the rack or case tidy.

SWITCH PORT	DEVICE	STATIC IP / NOTES
Port 1 (uplink)	ASUS RT-BE58 Go — LAN 2.5G port	Uplink from router to switch. Router is DHCP server for 192.168.50.0/24.
Port 2	FieldComms Pi 5 (Pironman MAX 5)	192.168.50.1 — FieldComms application server. All browser tools live here.
Port 3	44Net Gateway Pi 5 (Argon NEO 5)	192.168.50.2 — AMPRNet WireGuard gateway. Routes 44.0.0.0/8 for all EMCOMM-NET devices.
Port 4	Windows Laptop (Winlink Express + JS8Call)	192.168.50.3 (recommended static reservation) — or connect via EMCOMM-NET Wi-Fi.
Port 5	Color MFP Network Printer	192.168.50.10 (recommended static reservation) — auto-discovered by all devices via Bonjour.
Ports 6 – 9	Pi 500 Operator Workstations (up to 4)	192.168.50.20 – 192.168.50.23 (static DHCP reservations)
Port 10	Starlink Router (if deployed)	Optional second WAN path — connect Starlink Ethernet output to switch, use as WAN source on ASUS router.
Ports 11 – 16	Spare	Available for additional devices, IP radios, second TNC, future expansion.

DEVICE	POWER SOURCE
ASUS RT-BE58 Go router	USB-C 18W PD adapter — or USB-C power bank for field use
UniFi Switch Lite 16 PoE	Included 45W AC power supply
FieldComms Pi 5 (Pironman MAX 5)	Official Raspberry Pi 27W USB-C PD supply via Pironman MAX 5 power inlet
44Net Gateway Pi 5 (Argon NEO 5)	Official Raspberry Pi 27W USB-C PD supply directly to Pi USB-C port

DEVICE	POWER SOURCE
ASUS RT-BE58 Go router	USB-C 18W PD adapter — or USB-C power bank for field use
UniFi Switch Flex 2.5G-5	Included USB-C 5V / 1A adapter — or PoE from ASUS router uplink port
Raspberry Pi 5 (in Pironman MAX 5)	Official 27W USB-C PD supply connected to Pironman MAX 5 power inlet

1.2 Configure the ASUS RT-BE58 Go

STEP	ACTION
------	--------

1	Power on the router. Connect a device to it via Wi-Fi (default SSID on label) or Ethernet. Open http://192.168.50.1 (or the default router IP on the label).
2	Complete the router setup wizard. When it asks for WAN, choose Automatic IP (DHCP) or skip if no internet is connected.
3	Go to LAN → LAN IP . Set the LAN IP to 192.168.50.1 , subnet 255.255.255.0 . Apply.
4	Go to LAN → DHCP Server . Set IP pool: 192.168.50.100 – 192.168.50.200 . Apply.
5	Change the ASUS router admin password to something strong. Record it on a piece of paper stored on the FIELDCOMMS USB drive.
6	Set Manually Assigned IP for the Pi: go to LAN → DHCP Server → Manually Assigned IP . Enter the Pi's MAC address → assign IP 192.168.50.1 . (Or set the Pi's static IP manually in Step 4.)
7	Set the Wi-Fi SSID: go to Wireless → General . Set both the 2.4 GHz and 5 GHz SSIDs to EMCOMM-NET . Set a strong WPA3/WPA2 password. Apply.

WAN SOURCE	SETUP	BEST FOR
None (fully offline)	Leave WAN port unplugged. FieldComms runs entirely from the Pi.	Default field posture — all tools work without internet
Ethernet uplink (site network)	Plug site Ethernet into WAN port. Set WAN → Automatic IP (DHCP).	EOC with site LAN — enables NWS alerts, HF propagation data, APRS-IS
USB smartphone tether (cellular)	Enable hotspot/tethering on the phone. Plug phone USB into ASUS router USB port. Set WAN → USB.	Field site with cellular coverage — provides internet without site LAN
Starlink satellite	Connect Starlink router Ethernet output to ASUS WAN port. Set WAN → Automatic IP. Note: Starlink uses CGNAT so inbound connections are not possible.	Remote sites with no cellular — provides internet when nothing else is available
WISP (connect to site Wi-Fi)	ASUS Web UI → Administration → Operation Mode → WISP. Select the site Wi-Fi and enter its password.	Hospital, shelter, or venue with existing guest Wi-Fi

1.3 AiMesh Coverage Extension (Optional)

STEP	ACTION
1	Factory reset the node router. Hold reset button for 5–10 seconds until power LED flashes.
2	Power on the node within 30 ft of the primary router for initial pairing.
3	On primary router (http://192.168.50.1): go to AiMesh → Add AiMesh Node .
4	Select the new node. Click Connect. The primary pushes EMMCOMM-NET config to the node (1–3 minutes).
5	Move the node to its final position. Test coverage with a phone on EMMCOMM-NET.

3 Download & Run the FieldComms Installer

Step 3: Download & Run the FieldComms Installer

Method A — Direct download to the Pi (requires internet on Pi)

Lite: SSH into the Pi and run these commands. **Desktop:** open a Terminal window (taskbar → Terminal) and run the same commands.

```
# Create working directory
mkdir -p ~/fieldcomms-install && cd ~/fieldcomms-install
# Download the FieldComms package from GitHub or your storage location
wget -O fieldcomms-v1.zip
https://github.com/KE4CON/CrossPlatformAPRS/releases/latest/download/fieldcomms-v1.zip
# Unzip the package
unzip fieldcomms-v1.zip
cd fieldcomms
```

Method B — Copy from your computer using SCP (Lite/headless)

```
# Run this on YOUR COMPUTER, not the Pi
scp fieldcomms-v1.zip fieldcomms@[pi-ip-address]:~/
# Then SSH into the Pi and unzip
ssh fieldcomms@[pi-ip-address]
mkdir -p ~/fieldcomms-install
mv fieldcomms-v1.zip ~/fieldcomms-install/
cd ~/fieldcomms-install && unzip fieldcomms-v1.zip
cd fieldcomms
```

Method B2 — Download directly on the Pi Desktop (Desktop edition)

OPTION	HOW
Browser download	Open Chromium on the Pi. Go to the GitHub releases page or download URL. Download fieldcomms-v1.zip — it saves to ~/Downloads/ automatically.
USB drive	Copy fieldcomms-v1.zip to a USB drive. Insert the USB into the Pi. Open File Manager, drag the zip to your home folder.

```
# If downloaded to ~/Downloads/:
mkdir -p ~/fieldcomms-install
cp ~/Downloads/fieldcomms-v1.zip ~/fieldcomms-install/
# Unzip (same for all methods):
cd ~/fieldcomms-install && unzip fieldcomms-v1.zip
cd fieldcomms
```

Method C — USB drive transfer (fully offline)

Lite: commands below via SSH. **Desktop:** use File Manager to copy the zip from USB to your home folder, then open a Terminal for the unzip step.

```
# Copy fieldcomms-v1.zip to a USB drive on your computer
# Insert USB drive into the Pi, then:
sudo mount /dev/sda1 /mnt # or check lsblk for your device
cp /mnt/fieldcomms-v1.zip ~/fieldcomms-install/
cd ~/fieldcomms-install && unzip fieldcomms-v1.zip
cd fieldcomms
```

Launch the Installer

Lite: run via SSH. **Desktop:** open a Terminal window from the taskbar or Accessories → Terminal. The installer runs identically on both.

```
cd ~/fieldcomms-install/fieldcomms
sudo bash scripts/install.sh
```


4 Installer Configuration Options

Step 4: Installer Configuration Options

PROMPT	DEFAULT	DESCRIPTION
Station callsign	W8ABC	Your amateur callsign. Patched into all HTML pages.
Station latitude	42.3153	Decimal degrees. Used for APRS station marker, NWS alerts, propagation, distance calc.
Station longitude	-88.4473	Decimal degrees (negative = West). Default: Woodstock IL (McHenry County seat).
Wi-Fi AP SSID	EMCOMM-NET	The Wi-Fi network name that field devices connect to.
Wi-Fi AP password	fieldcomms2026	WPA2 password for EMMCOMM-NET. Change this for operational security.
Server IP address	192.168.50.1	The Pi's static IP on EMMCOMM-NET. Devices browse to http://192.168.50.1/
Download FCC database	N	~600 MB download of the FCC amateur license database. Recommended: Y
Kiwix tier	1	Tier 1: WikiMed + Wikipedia Mini + Wikivoyage (~2.5 GB). Tier 2 adds iFixit (~5 GB more).

What the Installer Does Automatically

- Installs system packages: Python 3, nginx, kiwix-tools, rsync, gpsd, ufw, mdadm, java
- Creates the **fieldcomms** system user and directory structure at /opt/fieldcomms/
- Creates a Python virtual environment and installs Flask, flask-cors, requests, gspd-py3
- Deploys all 30 HTML pages to /opt/fieldcomms/html/ and patches your callsign and coordinates into each file
- Installs all 14 systemd service and timer units and enables them at boot
- Configures nginx with the correct web root (/opt/fieldcomms/html/) and proxy rules for all API ports
- **Does NOT configure a Wi-Fi access point** — Wi-Fi is handled by the ASUS RT-BE58 Go router. The Pi connects as a wired client only.
- Configures the Pi static IP (192.168.50.1/24) on the Ethernet interface (eth0) via NetworkManager
- Configures the firewall (ufw) — opens all required ports
- Downloads and installs YAAC (Java APRS client) and Graywolf to /opt/yaac/ and /opt/graywolf/
- Installs the USB backup udev rule (plug in a USB drive labeled FIELDCOMMS to trigger auto-backup)
- Downloads and installs Pat Winlink (browser-based Winlink backup client, port 8090)
- Runs the Kiwix ZIM downloader for the selected content tier
- Downloads the FEMA ICS forms PDFs to /opt/fieldcomms/data/ics_forms/ (22 forms)
- Optionally downloads and builds the FCC amateur license database (~600 MB)
- Starts all services and verifies they are running

■ The ASUS RT-BE58 Go router must be configured before running the installer — see Step 1. The Pi does NOT run hostapd or dnsmasq. All Wi-Fi, DHCP, and SSID management is handled by the ASUS router.

5 Raspberry Pi 5 — Static IP Configuration

Step 5: Raspberry Pi 5 — Static IP Configuration

The Pi must always be reachable at 192.168.50.1. If the installer already set this via a DHCP reservation in the ASUS router, verify with `ip addr show eth0` and skip to Step 5 if 192.168.50.1/24 is shown.

Path A — Raspberry Pi OS Lite (SSH)

```
# SSH into the Pi (use the IP shown in your router DHCP table)
ssh fieldcomms@[current-pi-ip]
# Find the Ethernet connection name
nmcli con show
# Usually: "Wired connection 1" or "Preconfigured Connection 1"
# Set static IP
sudo nmcli con mod "Wired connection 1" ipv4.addresses 192.168.50.1/24 ipv4.method manual
ipv4.method manual
# Apply the change
sudo nmcli con up "Wired connection 1"
# Verify — should show inet 192.168.50.1/24
ip addr show eth0
```

Path B — Raspberry Pi OS Desktop (GUI)

STEP	ACTION
1	Click the network icon in the taskbar (top-right corner).
2	Click Advanced Options → Edit Connections .
3	Select your Wired connection and click the gear/edit icon.
4	Click the IPv4 Settings tab.
5	Change Method from "Automatic (DHCP)" to Manual .
6	Click Add and enter: Address: 192.168.50.1 · Netmask: 255.255.255.0 · Gateway: (leave blank)
7	Click Save , then close the Network Connections window.
8	Disconnect and reconnect the Ethernet cable, or reboot the Pi.
9	Open the Terminal and verify: <code>ip addr show eth0</code> — should show inet 192.168.50.1/24 .
10	Open Chromium on the Pi and go to http://192.168.50.1 to confirm FieldComms loads locally.



Alternatively, open a Terminal on the desktop and use the same nmcli commands shown in Path A. The terminal method works identically on the Desktop edition.

Path C — raspi-config (if available)

```
# Open raspi-config:
sudo raspi-config
# Navigate to: System Options → Network → (set static IP if option is present)
# NOTE: Static IP configuration via raspi-config was removed in Raspberry Pi OS Bookworm.
# If the option is not visible, use Path A (nmcli) or Path B (GUI Network Connections).
```

4
b

RAID 1 NVMe Setup — Pironman MAX 5

7b. RAID 1 NVMe Setup — Pironman MAX 5

The Pironman MAX 5 enclosure has two M.2 NVMe slots. Configure them as a RAID 1 mirror so both drives contain identical data. If one drive fails, the system continues running on the surviving drive with no data loss and no operator action required.

Complete this step before running the FieldComms installer. The RAID array must be assembled and the OS installed on it before FieldComms is deployed. If your Pi OS is already on a single drive, back it up first.

Physical Installation

STEP	ACTION
1	Install both 1 TB NVMe SSDs into the Pironman MAX 5 M.2 slots. Slot 1 (primary) → /dev/nvme0n1 · Slot 2 (mirror) → /dev/nvme1n1
2	Boot from a Raspberry Pi OS microSD card for the initial RAID setup. After RAID is built and OS is installed, the SD card is removed.

Build the RAID 1 Array

```
# Install mdadm (RAID management tool)
sudo apt-get install -y mdadm
# Create RAID 1 array from the two NVMe drives
sudo mdadm --create --verbose /dev/md0 --level=1 --raid-devices=2 \
/dev/nvme0n1 /dev/nvme1n1
# Confirm array is building (will show [=>.....] resync progress)
cat /proc/mdstat
# Create a filesystem on the RAID array
sudo mkfs.ext4 -L fieldcomms-raid /dev/md0
# Mount it
sudo mkdir -p /mnt/raid
sudo mount /dev/md0 /mnt/raid
# Copy running OS to RAID array
sudo apt-get install -y rsync
sudo rsync -axv --progress / /mnt/raid/
# Save RAID configuration so it persists across reboots
sudo mdadm --detail --scan | sudo tee -a /mnt/raid/etc/mdadm/mdadm.conf
```

RAID Health Reference

SITUATION	WHAT TO DO
Both drives show [UU]	Normal healthy state. No action needed.
One drive fails — [_U] or [U_]	1. Power down. 2. Remove failed drive. 3. Insert new 1 TB NVMe. 4. Power on. 5. Run: <code>sudo mdadm /dev/md0 --add /dev/nvme1n1</code> . 6. Array rebuilds automatically (~30 min).
Check RAID health anytime	<code>cat /proc/mdstat</code> or <code>sudo mdadm --detail /dev/md0</code>



RAID 1 protects against drive failure — it is NOT a backup. Both drives contain identical data, so accidental deletion or corruption affects both drives simultaneously. Continue to use the USB auto-backup (insert FIELDCOMMS USB drive) for regular data backups.

5 Kiwix Offline Library Setup

8. Step 5: Kiwix Offline Library Setup

Kiwix provides an offline web library served on port 8081. All devices on EMCOMM-NET can browse it at <http://192.168.50.1:8081>. Content is packaged as ZIM files.

TIER	NAME	SIZE	DESCRIPTION
1 — Essential	WikiMed — Medical Encyclopedia	~471 MB	Offline medical encyclopedia: symptoms, treatments, drugs, procedures. Critical for mass-casualty events.
1 — Essential	Wikipedia (Mini)	~1.2 GB	Compact English Wikipedia — essential facts, geography, science.
1 — Essential	Wikivoyage	~820 MB	Emergency shelters, evacuation routes, local resources and travel logistics.
2 — Extended	Wikibooks — How-To & Field Manuals	~4.2 GB	First aid, survival, ham radio, electronics, cooking, field skills.
2 — Extended	iFixit — Equipment Repair Manuals	~3.1 GB	Step-by-step repair guides for electronics, tools, vehicles.
2 — Extended	Wikipedia (Full English)	~22 GB	Complete English Wikipedia. Large download — requires 30 GB+ free.

```
# Check what is installed and service status
sudo bash /opt/fieldcomms/scripts/kiwix_setup.sh --status

# Add Tier 2 content (resumes interrupted downloads automatically)
sudo bash /opt/fieldcomms/scripts/kiwix_setup.sh --tier 2

# Service management
sudo systemctl status kiwix
sudo systemctl restart kiwix # required after adding new ZIM files
```

ZIM downloads are resumable. If a download is interrupted by power loss or network drop, simply re-run `kiwix_setup.sh` with the same `--tier` flag. `curl` resumes from where it stopped — no need to start over.

Additional Kiwix Content — Install Any ZIM File

Kiwix.org (kiwix.org/en/content/) publishes hundreds of ZIM archives beyond the two built-in tiers. Any ZIM file can be added to FieldComms. The following table lists the most useful additions for emergency communications and public safety operations:

CONTENT	APPROX SIZE	BEST FOR
OpenStreetMap (Wikimedia Maps)	~500 MB	Offline detailed maps for any region. Download your county or state for SAR and shelter mapping.
Stack Overflow (programming Q&A;)	~3.5 GB	Technical troubleshooting reference. Useful for net managers debugging FieldComms.
Project Gutenberg (public domain books)	~65 GB (full) / ~1 GB (best-of)	Field reference library. Includes FCC regulations, ARRL handbook excerpts, first aid guides.

CONTENT	APPROX SIZE	BEST FOR
Khan Academy (education)	~30 GB	Training resource for shelter and EOC staff during extended activations.
Red Cross First Aid (WikiMed companion)	~200 MB	Practical first aid procedures in plain language — supplements WikiMed for non-medical staff.
Wiktionary (dictionary)	~520 MB	Reference for unfamiliar ICS terminology and acronyms.
Amateur Radio Wiki (if available)	Variable	Band plans, antenna theory, Winlink and APRS procedures.

How to Install Any ZIM File

```
# Step 1 – Find and download the ZIM from a device with internet
# Browse to: https://library.kiwix.org
# Filter by language (English) and category.
# Download the .zim file to your laptop or phone.

# Step 2 – Transfer the ZIM to the Pi
# Option A: USB drive (copy to USB, insert in Pi)
sudo mount /dev/sda1 /mnt
cp /mnt/my_content.zim /opt/kiwix/zim/

# Option B: SCP from your laptop over EMCOMM-NET
scp my_content.zim fieldcomms@192.168.50.1:/opt/kiwix/zim/

# Step 3 – Register the new ZIM with the Kiwix library index
sudo kiwix-manage /opt/kiwix/library.xml add /opt/kiwix/zim/my_content.zim

# Step 4 – Restart Kiwix to load the new content
sudo systemctl restart kiwix

# Step 5 – Verify it appears at http://192.168.50.1:8081
# The new content appears in the Kiwix home page search bar.

# To list all installed ZIM files:
ls -lh /opt/kiwix/zim/

# To remove a ZIM file:
sudo rm /opt/kiwix/zim/my_content.zim
sudo systemctl restart kiwix
```

ZIM files can be large. Check available disk space before downloading: `df -h /opt/kiwix/` The RAID array provides 2× 1 TB = ~900 GB usable after OS and FieldComms. Tier 1 uses ~2.5 GB. Tier 2 uses ~10 GB. There is ample space for additional content.

6

FCC Amateur Database

9. Step 6: FCC Amateur Database

The FCC database gives FieldComms instant offline access to the entire US amateur radio license database — approximately 800,000 active licensees. When a net control operator types a callsign into the check-in field, FieldComms looks up the licensee name, license class, and address automatically in under a millisecond, with no internet connection required. This is one of the most-used features during ARES/RACES net operations.

The installer offers to download and build the database during Step 4 (answer Y). If you skipped it during installation, or if the database needs to be rebuilt, run the commands below. Building takes approximately 5 to 10 minutes on a Pi 5 and requires an active internet connection.

```
# If you selected "y" during install, it already ran.
# To build or rebuild manually:
sudo -u fieldcomms \
/opt/fieldcomms/venv/bin/python \
/opt/fieldcomms/python/build_fcc_db.py
# Automatic weekly refresh timer:
sudo systemctl status fcc-refresh.timer
# Force immediate refresh:
sudo systemctl start fcc-refresh.service
```

7 APRS Setup — Graywolf + YAAC

10. Step 7: APRS Setup (Graywolf + YAAC)

FieldComms integrates two APRS client applications: Graywolf TNC (accessible on port 8080) and YAAC — Yet Another APRS Client (port 8082). Both run as background services and feed live station data to the Tactical APRS Map on the dashboard. The map merges data from both sources, deduplicates by callsign, and maintains a live WebSocket feed to all connected browsers simultaneously.

APRS is entirely optional. FieldComms runs fully without it — you simply will not see live APRS stations on the tactical map. If you are not planning to use a TNC or radio interface, skip this step entirely and proceed to Step 8 (Printer Setup).

The FieldComms installer attempts to download and install both YAAC and Graywolf automatically. If internet was available during installation, they should already be present. Skip to Section 9.3 (YAAC port configuration) if the installer succeeded.

9.1 Verify Automatic Installation

```
# Check if Java is installed
java -version
# Check if YAAC was installed
ls -lh /opt/yaac/YAAC.jar
# Check if Graywolf was installed
ls -lh /opt/graywolf/graywolf.jar
# Check service status
sudo systemctl status yaac
sudo systemctl status graywolf
```

9.2 Manual Install — If Automatic Install Failed

```
# Step 1 – Install Java runtime (required by both clients)
sudo apt install -y default-jre
# Step 2 – Install YAAC
sudo mkdir -p /opt/yaac
cd /tmp && wget http://www.ka2ddo.org/ka2ddo/YAAC.zip
sudo unzip YAAC.zip "*.jar" -d /opt/yaac/
sudo mv /opt/yaac/YAAC*.jar /opt/yaac/YAAC.jar 2>/dev/null || true
sudo chown -R fieldcomms:fieldcomms /opt/yaac
# Step 3 – Install Graywolf
sudo mkdir -p /opt/graywolf
sudo wget -O /opt/graywolf/graywolf.jar \
https://github.com/vk2tds/graywolf/releases/latest/download/graywolf.jar
sudo chown -R fieldcomms:fieldcomms /opt/graywolf
# Step 4 – Enable services
sudo systemctl enable --now yaac
sudo systemctl enable --now graywolf
```

9.3 YAAC Port Configuration (Required — First Run)

STEP	ACTION
1	Run YAAC once on a desktop/monitor: <code>java -jar /opt/yaac/YAAC.jar</code>
2	Go to File → Configure → Web Server tab.
3	Set Port: 8082 · Check Enable REST API · Check Enable WebSocket · Click Save.

- 4 Close YAAC. The yaac.service will use these settings when running headlessly.

9.4 Connect a TNC or Radio Interface

INTERFACE TYPE	PORT TYPE IN YAAC	SETTINGS
USB TNC (Digirig, SignaLink, etc.)	Serial TNC	/dev/tnc0, baud rate 9600 or 1200
KISS TNC over TCP (Direwolf)	KISS TNC (TCP)	Host: localhost, Port: 8001
AGW packet engine (Direwolf)	AGW	Host: localhost, Port: 8000
APRS-IS internet (if WAN connected)	APRS-IS	Server: noam.aprs2.net:14580, Filter: r/42.31/-88.44/50

9.5 Verify APRS is Working

```
# Test YAAC REST API (should return JSON list of heard stations)
curl http://localhost:8082/api/stations
# Test Graywolf REST API
curl http://localhost:8080/api/stations
# Check service logs if no stations appear
journalctl -u yaac -n 30
journalctl -u graywolf -n 30
```

8 Printer Setup — Three Connection Options

11. Step 8: Printer Setup

FieldComms has print buttons on 17 pages. All printing uses the browser standard window.print() function, which sends the job to whatever printer the operator's browser can reach. Three printer connection methods are supported:

Option A — Client Device Prints to Its Own Printer (Simplest)

Each operator's laptop or tablet prints to its own locally connected printer. No Pi configuration needed. Zero setup required — works immediately.



This is the simplest option and requires zero configuration on the Pi. The only requirement is that the operator's device has a printer configured.

Option B — USB Printer Shared via Pi (CUPS)

A USB printer is connected directly to the Pi. CUPS shares it across EMCOMM-NET. Installed automatically by the FieldComms installer. CUPS admin UI at <http://192.168.50.1:631>.

B.2 Add the USB Printer via CUPS Web Admin

STEP	ACTION
1	Plug the USB printer into one of the Pi's USB ports (or powered USB hub).
2	On any device on EMCOMM-NET, open a browser and go to: http://192.168.50.1:631
3	Click Administration → Add Printer .
4	If prompted for credentials, enter the Pi username and password (e.g. fieldcomms / your password).
5	Your USB printer appears in the Local Printers list. Select it and click Continue .
6	Enter a Name (e.g. FieldComms-Printer), Description, and Location. Check Share This Printer . Click Continue.
7	Select the correct printer driver. Click Add Printer .
8	Set default options (paper size: Letter) and click Set Default Options .
9	Click Print Test Page to confirm the printer is working.

B.3 Add the Shared Printer on Operator Devices

DEVICE TYPE	HOW TO ADD THE SHARED PRINTER
Windows laptop (Winlink / JS8Call station)	Settings → Bluetooth & devices → Printers & scanners → Add a printer or scanner. Windows discovers the CUPS shared printer automatically on EMCOMM-NET via Bonjour. Select FieldComms-Printer when it appears and click Add device.
Mac / macOS	System Settings → Printers & Scanners → click + (Add Printer). Click the Default tab — the shared printer appears via Bonjour discovery. Select it and click Add.
iPad / iPhone (AirPrint)	No setup required. CUPS + Avahi advertises the printer as AirPrint-compatible. Open any FieldComms page → tap the Share icon → tap Print → select the printer. Works on any iOS device on EMCOMM-NET.
Android tablet / phone	Install the free CUPS Print app from Google Play. Open the app → Add Printer → enter IP 192.168.50.1, Port 631, Protocol IPP. The printer appears in the Android print dialog for all apps.

DEVICE TYPE	HOW TO ADD THE SHARED PRINTER
Chromebook	Settings → Advanced → Printing → Printers → Add Printer. Enter: Name = FieldComms-Printer, Address = 192.168.50.1, Protocol = IPP, Queue = /printers/FieldComms-Printer. Click Add.
Raspberry Pi 500 / 500+ (operator workstation)	Chromium browser (pre-installed): the CUPS printer appears automatically in the print dialog. No additional setup needed — Chromium on Pi OS discovers CUPS printers via Bonjour. For Firefox ESR on the Pi 500: install via <code>sudo apt install firefox-esr</code> then open Print → More Settings → select the printer from the destination list. Alternatively, run: <code>sudo usermod -aG lpadmin fieldcomms</code> to give the Pi 500 user full access to the CUPS admin at http://192.168.50.1:631 .

B.4 Recommended Printers for Field Use

Monochrome Laser (recommended for most EOC deployments)

PRINTER	CONNECTION	WHY IT WORKS WELL
Brother HL-L2350DW	USB or Wi-Fi	Excellent Linux driver support out of the box. Fast, compact, duplex, durable. Best all-round choice for field EOC use. Under \$130.
HP LaserJet Pro M15w / P1102w	USB or Wi-Fi	Full Linux support via HP HPLIP driver (installed automatically with CUPS). Fast, reliable, very low cost per page. Under \$150.

Color Multifunction Laser (ICS maps, colored forms, and chart printing)

PRINTER	CONNECTION	WHY IT WORKS WELL
Brother MFC-L3770CDW	USB, Wi-Fi, or Ethernet	Color laser all-in-one with duplex, scan, copy, fax. Full Linux support via Brother driver. Prints color ICS maps and resource boards clearly. Under \$400.
HP Color LaserJet Pro MFP M479fdw	USB, Wi-Fi, or Ethernet	Color laser multifunction — print, scan, copy, fax. HPLIP driver works with CUPS out of the box. Excellent for IAP packages with color-coded sections. Under \$500.
Canon imageCLASS MF743Cdw	USB, Wi-Fi, or Ethernet	Color laser multifunction with excellent Linux CUPS driver (CAPT driver). Handles letter and legal paper. Good choice for permanent EOC installations. Under \$450.

Portable / Battery-Powered (mobile and field deployments without shore power)

PRINTER	CONNECTION	WHY IT WORKS WELL
Canon PIXMA TR150	USB or Wi-Fi (battery built-in)	Compact inkjet with rechargeable battery. Prints ~200 pages per charge. Letter size. Wi-Fi connects directly to EMCOMM-NET. Under \$200.
HP OfficeJet 200	USB or Wi-Fi (battery optional)	Portable inkjet with larger paper tray than TR150. Optional battery accessory. Good for shelter check-in stations and mobile command posts. Under \$180.

Option C — Network Printer on EMCOMM-NET (Simplest Shared Setup)

A Wi-Fi or Ethernet printer is connected directly to the ASUS router or UniFi switch — no Pi involvement required at all. All devices on EMCOMM-NET can discover and print to it automatically via Bonjour / mDNS. This works with any network-capable printer including color multifunction laser printers that have built-in Wi-Fi or Ethernet. This is the simplest option for permanent EOC installations where a color MFP is already on site.

Option C works with any network-capable printer — including all three color multifunction laser printers listed in the BOM. These are the best choice for a permanent EOC installation because they connect directly to EMCOMM-NET with no Pi configuration, provide color printing for ICS maps and IAP packages, and are discoverable by every device on scene automatically.

CONNECTION METHOD	COMPATIBLE PRINTERS	HOW TO SET UP
Wi-Fi (wireless)	Brother MFC-L3770CDW / HP Color LaserJet M479fdw / Canon MF743Cdw / Canon PIXMA TR150 / HP OfficeJet 200	Use the printer control panel to join EMCOMM-NET. Enter the Wi-Fi password when prompted. The printer receives a 192.168.50.x address from the ASUS router automatically. All EMCOMM-NET devices discover it via Bonjour — no driver installation needed.
Ethernet (wired)	Brother MFC-L3770CDW / HP Color LaserJet M479fdw / Canon MF743Cdw	Run a CAT 6 cable from the printer Ethernet port to any spare UniFi Switch port (Ports 3 through 5). The printer receives an IP automatically. Set a static DHCP reservation in the ASUS router so the IP never changes between activations.

Reserve a Static IP for the Printer (Recommended)

```
# On the ASUS router web UI (http://192.168.50.1):
# LAN → DHCP Server → Manually Assigned IP
# Enter the printer MAC address → assign a fixed IP, e.g.: 192.168.50.10
# Reboot the printer to pick up the reservation
# Confirm: ping 192.168.50.10
```

Printer Option Comparison

	Option A — Client Printer	Option B — USB via Pi / CUPS	Option C — Network Printer
Pi configuration needed	None	CUPS (auto-installed)	None
One printer for all operators	Each device needs own printer	Shared across EMCOMM-NET	Shared across EMCOMM-NET
Works without internet	Yes	Yes	Yes
iOS / AirPrint support	Requires AirPrint printer	Yes via CUPS + Avahi	Yes if AirPrint printer
Battery printer support	Yes	Yes (USB connected)	Yes (Wi-Fi connected)
Best for	Single operator or tablet with own printer	Any USB printer, shared to all devices	Wi-Fi/Ethernet printer already on site

For most K9ESV field activations, Option B (USB printer via CUPS) is recommended. A Brother HL-L2350DW or HP LaserJet plugged into the Pi USB hub covers all ICS forms, net logs, and cheat sheets needed for a typical activation.

9

Pat Winlink — Verify & Configure

12. Step 9: Pat Winlink — Verify & Configure

Pat is an open-source Winlink client that runs directly on the Pi and is accessible from any browser on EMCOMM-NET at <http://192.168.50.1:8090>. The FieldComms installer downloads and configures Pat automatically, so this step is primarily about verifying it is running and adding your Winlink account password.

Pat serves as the backup Winlink path when the Windows laptop is unavailable, or for VHF Packet operations when a TNC is connected directly to the Pi. MCEMV/MCEMA primary Winlink operations use Winlink Express on the Windows laptop (Step 10). Pat is the fallback.

```
# Check pat.service status
sudo systemctl status pat
# If not running:
sudo systemctl start pat && sudo systemctl enable pat
# Confirm port 8090 is listening
ss -tlnp | grep 8090
# Add your Winlink password:
sudo nano /opt/fieldcomms/.config/pat/config.json
# Verify / update these fields:
# "mycall": "K9ESV" ← set by installer
# "secure_login_password": "xxxxx" ← add your Winlink password
# "http_addr": "0.0.0.0:8090" ← must be 0.0.0.0 for EMCOMM-NET access
```

10

Windows Laptop — Winlink Express + JS8Call

12. Step 10: Windows Laptop Setup

The Windows laptop is the primary HF digital station. It runs Winlink Express and JS8Call with the IC-7300 connected via a single USB cable. Connect the laptop to EMCOMM-NET (Wi-Fi) or the UniFi switch Port 3 (wired Ethernet).

9.1 IC-7300 One-Time Radio Setup

IC-7300 MENU PATH	SETTING
SET → Connectors → CI-V Baud Rate	115200
SET → Connectors → CI-V Transceive	ON
SET → Connectors → USB Send/Keying → USB Send	RTS
SET → Connectors → MOD Input → USB MOD Level	40–50%
COMP button (speech compression)	OFF
Mode for digital operation	USB-D

9.2 Install Winlink Express + VARA HF

STEP	ACTION
1	Download Winlink Express from: winlink.org/client-software . Run installer, accept defaults.
2	On first launch: enter your callsign, Winlink password, and grid square EN52 (McHenry County, IL).
3	Settings → Radio Setup: Radio=IC-7300, Control Port=(check Device Manager), Baud Rate=115200, PTT via CAT=checked.
4	Settings → Sound Card: Input=USB Audio CODEC (IC-7300), Output=USB Audio CODEC (IC-7300).
5	Download and install VARA HF from: winlink.org → VARA → VARA HF Modem. Set same audio devices in VARA HF Settings.
6	Test: Open a VARA HF session in Winlink Express → connect to any Winlink RMS gateway on 40m to confirm audio and CAT control work.

9.3 Install JS8Call

STEP	ACTION
1	Download JS8Call from: js8call.com → Windows installer. Run installer, accept defaults.
2	Launch JS8Call. Open File → Settings (F2). General tab: My Call=K9ESV, My Grid=EN52.
3	Audio tab: Input=USB Audio CODEC (IC-7300), Output=USB Audio CODEC (IC-7300).
4	Radio tab: Rig=IC-7300, PTT Method=CAT, Serial Port=(same COM port as Winlink), Baud Rate=115200.
5	Reporting tab (CRITICAL): TCP Server Hostname= 0.0.0.0 (MUST change from 127.0.0.1). Enable TCP Server API=checked. TCP Server Port= 2442 . Accept TCP Requests=checked.

6	Click OK. Restart JS8Call for API settings to take effect.
7	Set VFO to 7.078 MHz (JS8 40m calling frequency). Mode → Normal.

9.4 Windows Firewall — Allow JS8Call Port 2442

1. Search "Windows Defender Firewall" → Advanced Settings
2. Inbound Rules → New Rule → Port → TCP → Specific port: 2442 → Allow → All profiles
3. Name the rule: JS8Call API

9.5 Find the Windows Laptop IP on EMCOMM-NET

```
# Run in Windows Command Prompt:
ipconfig

# Note the IPv4 Address for the EMCOMM-NET adapter (e.g. 192.168.50.105)
# Set a DHCP reservation (recommended – gives laptop a fixed IP):
# ASUS Web UI → LAN → DHCP Server → Manually Assigned IP
# Enter laptop MAC address → assign 192.168.50.2

# Configure the FieldComms dashboard JS8Call card:
# 1. Connect to EMCOMM-NET, open http://192.168.50.1
# 2. Find the JS8Call card (purple) in Amateur Radio section
# 3. Tap/click the card
# 4. Enter the Windows laptop IP (e.g. 192.168.50.105)
# 5. Card saves IP and opens http://192.168.50.105:2442
```

SWITCHING TO...	PROCEDURE
Winlink Express (from JS8Call)	Click Disconnect in JS8Call or close it. Open VARA HF — it automatically reclaims the USB audio device. Open Winlink Express and connect normally.
JS8Call (from Winlink)	Finish any active Winlink transmission. Close VARA HF. Minimize Winlink Express. Open JS8Call and click Connect — it reclaims the COM port and audio.
Both simultaneously (two radios)	Connect a second HF radio via a separate USB audio and CAT interface. Configure JS8Call to use that radio's COM port and audio device. Both run at the same time without conflicts.

1
0
b

SCS PACTOR Modem Setup (Optional — High-Performance HF)

Step 10b: SCS PACTOR Modem Setup

PACTOR is a high-performance HF digital mode used extensively in Winlink operations. It provides significantly better throughput than VARA HF on marginal or noisy HF paths, and is the only mode that supports PACTOR 4 compression on Winlink. SCS (Special Communications Systems) manufactures the only PACTOR-licensed TNCs available. A PACTOR TNC connects between the IC-7300 and the Windows laptop. This step is optional — Winlink via VARA HF works well for most activations.

Supported SCS PACTOR Modems

MODEL	PACTOR LEVEL	INTERFACE	NOTES
SCS Tracker DSP TNC	PACTOR 1 / 2 / 3	USB (COM port)	Entry-level PACTOR TNC. Good for most Winlink operations. Also supports PACKET and ROBUST PR. ~\$250.
SCS PTC-IIIusb	PACTOR 1 / 2 / 3	USB (COM port)	Full-featured controller with front-panel display. Supports PACTOR, PACKET, AMTOR, RTTY. ~\$650.
SCS P4dragon DR-7400	PACTOR 1 / 2 / 3 / 4	USB (COM port)	Top-of-line PACTOR 4 TNC. Maximum throughput on HF. Required for PACTOR 4 sessions. ~\$1,100. Recommended for permanent EOC and EMCOMM stations.

Physical Connection

FROM	TO	CABLE / NOTE
SCS TNC — AFSK audio output	IC-7300 — ACC jack audio input or 3.5mm mic input	SCS-supplied audio cable (included with TNC)
SCS TNC — AFSK audio input	IC-7300 — ACC jack audio output or 3.5mm speaker output	SCS-supplied audio cable (included with TNC)
SCS TNC — PTT output	IC-7300 — remote jack (ACC or SEND)	SCS-supplied PTT cable (check your TNC model)
SCS TNC — USB port	Windows laptop — any USB-A port	USB-A to USB-B or USB-A to micro-USB (included with TNC)

If you are also using VARA HF via the IC-7300 USB audio: configure the PACTOR TNC to use the IC-7300 ACC jack for audio, not the USB sound card. This allows VARA (USB audio path) and PACTOR (ACC audio path) to coexist on the same radio. Never transmit both modes simultaneously.

Configure Winlink Express for PACTOR

STEP	ACTION
1	In Winlink Express, go to Settings → Radio Setup .
2	Click Add to create a new radio entry.

3	Set Template to: SCS PTC-Ilx (works for all SCS PACTOR TNCs including the Tracker and P4dragon).
4	Set Control Port to the COM port assigned to your SCS TNC. Check Windows Device Manager → Ports (COM & LPT) to find the correct number. The TNC appears as "USB Serial Port (COM X)".
5	Set Baud Rate to 115200 .
6	Leave PTT via CAT unchecked — the TNC handles PTT directly via the ACC cable.
7	Click OK to save the radio profile.

Open a PACTOR Winlink Session

STEP	ACTION
1	In Winlink Express, click the session type dropdown and select Open Session → PACTOR Winlink .
2	The session window opens. The TNC initializes and you will see the SCS banner text in the session log.
3	Set your frequency on the IC-7300 to a known Winlink RMS gateway frequency for your region. Common 40m PACTOR frequencies: 7.038 MHz, 7.040 MHz, 7.103 MHz.
4	Click Start . Winlink Express scans for and connects to the nearest RMS gateway.
5	The PACTOR handshake completes automatically — the session connects at the highest common level (PACTOR 1 through 4) that both stations support.
6	Send and receive messages as normal. PACTOR 4 typically completes a full ICS-213 exchange in under 2 minutes on a good path.

Verify the TNC is Responding

```
# Method: use PuTTY or Windows Terminal to open a direct serial session
# Open PuTTY → Connection type: Serial → COM port: (your TNC port)
# Speed: 115200 → click Open

# Type the following TNC command:
cmd
# The TNC responds with its command prompt: cmd:

# Useful TNC verification commands:
ver # shows firmware version and TNC model
status # shows current operating status
mycall K9ESV # sets your callsign in the TNC (replace K9ESV with yours)

# If the TNC does not respond:
# 1. Confirm the correct COM port in Device Manager
# 2. Confirm no other application has the COM port open
# 3. Try baud rate 9600 (some TNC models default lower)
```

PACTOR levels 3 and 4 require a separate Winlink license fee beyond the standard Winlink account. PACTOR 1 and 2 are available to all licensed amateur radio operators at no additional cost. The SCS TNC also supports AX.25 Packet, which Pat Winlink on the Pi can use via a KISS TCP connection (typically for VHF packet via a separate TNC or via the Digirig). This provides a VHF backup to the HF PACTOR path.

1
1

AMPRNet / 44Net Gateway Setup

Step 11: AMPRNet / 44Net Gateway Setup

The following files are part of FieldComms and work together to provide integrated 44Net gateway support across both Pis:

FILE	RUNS ON	PURPOSE
scripts/setup_44net.sh	Gateway Pi (192.168.50.2)	Installer for the gateway Pi. Sets up WireGuard, static IP, IP forwarding, status service, and Desktop autostart. Run once on the gateway Pi.
python/amprgate_status.py	Gateway Pi (192.168.50.2)	Flask status service on port 9000. Serves the gateway dashboard UI and /api/status JSON endpoint. Installed by setup_44net.sh.
systemd/amprgate-status.service	Gateway Pi (192.168.50.2)	Systemd unit that keeps amprgate_status.py running. Installed by setup_44net.sh. Starts after wg-quick@ampr0.
python/amprgate_poll.py	FieldComms Pi (192.168.50.1)	Polls the gateway Pi every 30 seconds and writes status to /opt/fieldcomms/data/amprgate_status.json for the dashboard.
systemd/amprgate-poll.service	FieldComms Pi (192.168.50.1)	Systemd unit for the poll service. Installed automatically by the FieldComms install.sh.
html/amprgate.html	FieldComms Pi (192.168.50.1)	Dashboard page at http://192.168.50.1/amprgate.html. Shows tunnel state, AMPRNet address, traffic stats, and tunnel controls.

AMPRNet (Amateur Packet Radio Network) is the global amateur radio IP network using the reserved 44.0.0.0/8 address block assigned by IANA to ARRL. It provides licensed amateur radio operators with globally routable IP addresses reachable over RF links or via encrypted internet tunnels to the AMPRNet gateway. Adding a dedicated 44Net gateway Pi to FieldComms gives every device on EMCOMM-NET full access to the AMPRNet — Winlink gateways, APRS-IS servers, Mesh networking nodes, and other amateur stations worldwide that are reachable on 44.x.x.x addresses.

The 44Net Gateway Pi is completely separate from the FieldComms server Pi. It runs WireGuard, ip routing, and a status page only. If the gateway goes down or needs reconfiguring, FieldComms continues operating normally. This isolation was an intentional design choice — keep routing infrastructure separate from the communications server.

Part A — Get Your AMPRNet Allocation (Do This First — Allow 2-4 Weeks)

Before configuring any software, you need an AMPRNet IP address block assigned to K9ESV. This is a one-time registration process managed by the AMPRNet administrators at [ampr.org](https://portal.ampr.org). The block you receive will be something like 44.x.x.x/29 (6 usable addresses) or 44.x.x.x/28 (14 usable addresses) depending on what is available in your region.

STEP	ACTION
1	Create an account at portal.ampr.org — go to https://portal.ampr.org and click Register. You must use your callsign K9ESV as your username. Verify your license via the FCC ULS lookup that the portal performs automatically.

2	Request a subnet allocation — after logging in, click Subnets → Request Subnet. Select your region (Illinois — typically 44.24.x.x or 44.172.x.x range). Request a /29 block for a small deployment or a /28 if you anticipate growth. In the justification field, explain the MCEM/MCEMA EMCOMM-NET deployment and intended use.
3	Coordinate with your regional AMPRNet administrator — Illinois AMPRNet administration is coordinated through ARRL. You may be contacted by the regional admin for verification. Response times vary from days to several weeks. Be patient.
4	Receive your allocation — you will get an email with your assigned 44.x.x.x/29 block. The portal will also show your allocation under Subnets → My Subnets. Record this allocation — you will need it in Part B.
5	Note your WireGuard endpoint credentials — the portal provides a WireGuard configuration for your specific subnet. Download or copy this — it contains your private key, allowed IPs, and the amprgw.ampr.org endpoint address.

ARRL membership is not required for an AMPRNet allocation, but a valid FCC amateur radio license (any class) is required. The K9ESV club callsign is valid for this purpose. The allocation is tied to the callsign and is permanent as long as the license remains active.

Part B — Set Up the 44Net Gateway Pi

Once you have your AMPRNet allocation, the following steps configure the dedicated gateway Pi running in the Argon NEO 5 case. This Pi should be freshly flashed with Raspberry Pi OS Lite (64-bit). It does not need the FieldComms installer — it runs WireGuard and routing only.

B.1 Initial OS Setup

Flash Raspberry Pi OS Desktop (64-bit) to the M.2 SATA SSD using Raspberry Pi Imager. Desktop is used on the gateway Pi so any team member can check tunnel status from the local keyboard and monitor without SSH. Chromium opens the status page automatically on login. During Imager advanced options set:

OPTION	VALUE
Hostname	amprgate.local — discoverable as amprgate.local on EMCOMM-NET
Username	amprgate — used by the gateway setup script
Password	Choose a strong password and record it with the FieldComms credentials
Enable SSH	Yes — useful for remote diagnostics if the monitor is not available
Wi-Fi	Your home or lab Wi-Fi for initial package downloads — switched to wired EMCOMM-NET after setup
Locale	US/Central — matches the FieldComms Pi for consistent log timestamps

B.2 Assign Static IP and Install WireGuard

```
# SSH into the gateway Pi
ssh amprgate@[current-pi-ip]

# Update packages
sudo apt-get update && sudo apt-get full-upgrade -y

# Install WireGuard
sudo apt-get install -y wireguard wireguard-tools

# Set static IP on eth0
sudo nmcli con mod "Wired connection 1", ipv4.addresses 192.168.50.2/24, ipv4.gateway 192.168.50.254,
ipv4.dns "8.8.8.8 8.8.4.4", ipv4.method manual
sudo nmcli con up "Wired connection 1"

# Verify
ip addr show eth0
# Expected: inet 192.168.50.2/24
```

B.3 Configure the WireGuard Tunnel

The AMPRNet portal provides a WireGuard configuration specific to your subnet. The following is the general structure — replace the placeholder values with the actual values from your portal allocation.

```
# Create the WireGuard config directory
sudo mkdir -p /etc/wireguard
sudo chmod 700 /etc/wireguard

# Create the tunnel config file
sudo nano /etc/wireguard/ampr0.conf

# Paste the following – replace ALL values in [brackets] with your portal values:
[Interface]
PrivateKey = [your-private-key-from-portal]
Address = [your-44.x.x.x/29-address]
ListenPort = 51820
PostUp = ip route add 44.0.0.0/8 dev ampr0
PostUp = iptables -A FORWARD -i ampr0 -j ACCEPT
PostUp = iptables -A FORWARD -o ampr0 -j ACCEPT
PostUp = iptables -t nat -A POSTROUTING -o eth0 -j MASQUERADE
PostDown = ip route del 44.0.0.0/8 dev ampr0
PostDown = iptables -D FORWARD -i ampr0 -j ACCEPT
PostDown = iptables -D FORWARD -o ampr0 -j ACCEPT
PostDown = iptables -t nat -D POSTROUTING -o eth0 -j MASQUERADE

[Peer]
PublicKey = [amprnet-gateway-public-key-from-portal]
Endpoint = amprgw.ampr.org:51820
AllowedIPs = 44.0.0.0/8
PersistentKeepalive = 25
```

B.4 Enable IP Forwarding and Start the Tunnel

```
# Enable IP forwarding (required for routing between EMCOMM-NET and AMPRNet)
echo "net.ipv4.ip_forward = 1" | sudo tee -a /etc/sysctl.conf
sudo sysctl -p

# Start the WireGuard tunnel
sudo wg-quick up ampr0

# Enable at boot
sudo systemctl enable wg-quick@ampr0

# Check tunnel status
sudo wg show ampr0
# Expected: shows latest handshake, transfer stats, allowed IPs

# Test reachability into AMPRNet
ping 44.0.0.1 -c 4
# Expected: replies from 44.0.0.1 (AMPRNet gateway)
```

B.5 Advertise the 44Net Route to EMCOMM-NET Devices

For other devices on EMCOMM-NET to use the 44Net gateway automatically, the ASUS router needs to push a static route to all DHCP clients. This tells every device: "to reach anything in 44.0.0.0/8, use 192.168.50.2".

STEP	ACTION
1	Open the ASUS router admin at http://192.168.50.254 .
2	Go to LAN → Route .
3	Click Add and enter: Network/Host IP = 44.0.0.0 , Netmask = 255.0.0.0 , Gateway = 192.168.50.2 , Interface = LAN .
4	Click Apply .
5	On any EMCOMM-NET device, verify the route was received:
	<pre># On any EMCOMM-NET device (Pi 500, Windows laptop, etc.) ip route show grep 44 # Expected: 44.0.0.0/8 via 192.168.50.2 dev eth0 # Windows equivalent (Command Prompt) route print find "44." # Expected: 44.0.0.0 0.0.0.0 192.168.50.2 ... # Test from the FieldComms Pi ping 44.0.0.1 -c 4 # If reachable, FieldComms can now connect to AMPRNet resources</pre>

B.6 Gateway Status Page

Install a lightweight status page on the 44Net Pi so operators can verify the tunnel state from any EMCOMM-NET browser without SSH access. This is a small Flask application that displays tunnel status, connected peers, and recent handshake times.

```

# Install Python and Flask on the 44Net Pi
sudo apt-get install -y python3 python3-pip python3-venv
python3 -m venv /opt/amprgate/venv
/opt/amprgate/venv/bin/pip install flask

# Create the status app
sudo mkdir -p /opt/amprgate
sudo nano /opt/amprgate/status.py

# Paste the following into status.py:
# ---
from flask import Flask, jsonify
import subprocess, json
app = Flask(__name__)

@app.route("/")
def index():
    return open("/opt/amprgate/status.html").read()

@app.route("/api/status")
def status():
    wg = subprocess.run(["sudo", "wg", "show", "ampr0", "dump"],
        capture_output=True, text=True).stdout
    lines = [l.split(" ") for l in wg.strip().split("\n") if l]
    return jsonify({"tunnel": "up" if lines else "down", "peers": len(lines)-1})

if __name__ == "__main__":
    app.run(host="0.0.0.0", port=9000)
# ---

# Create systemd service
sudo nano /etc/systemd/system/amprgate-status.service
# Paste:
[Unit]
Description=AMPRNet Gateway Status Page
After=network.target wg-quick@ampr0.service

[Service]
User=amprgate
ExecStart=/opt/amprgate/venv/bin/python /opt/amprgate/status.py
Restart=always

[Install]
WantedBy=multi-user.target

sudo systemctl enable --now amprgate-status
# Status page now at: http://192.168.50.2:9000

```

Part C — What You Can Do on AMPRNet

Once the gateway is operational and the route is advertised to EMCOMM-NET, every device on EMCOMM-NET has full access to the AMPRNet. Here are the most useful applications for MCESV/MCEMA operations:

APPLICATION	HOW IT USES 44NET	ACCESS FROM EMCOMM-NET
Winlink via AMPRNet	Some Winlink RMS gateways have 44.x.x.x addresses. Pat Winlink on the FieldComms Pi can connect to them directly over the AMPRNet tunnel rather than the commercial internet — useful when only amateur radio paths are available.	Pat Winlink at http://192.168.50.1:8090 Add AMPRNet RMS in Pat settings
APRS-IS via AMPRNet	The APRS-IS network has servers reachable on 44.x.x.x. Graywolf and YAAC can connect to APRS-IS via the AMPRNet path, keeping APRS traffic within the amateur radio network.	Configure APRS-IS server address in Graywolf or YAAC settings
Inter-node FieldComms	If another MCEVS station runs a second FieldComms system with its own 44Net gateway, the two systems can share net data and resource boards over AMPRNet without routing traffic through the commercial internet.	Future capability — requires second FieldComms deployment
HamSphere / Echolink via AMPRNet	Some VoIP amateur radio nodes are reachable on 44.x.x.x addresses, providing RF-to-AMPRNet linking without commercial internet dependency.	Direct connection to 44.x.x.x node addresses
Direct amateur station communication	Any amateur station worldwide with a 44.x.x.x address (whether via RF packet or WireGuard tunnel) is directly reachable from any EMCOMM-NET device for data exchange, file transfer, or status checking.	Direct TCP/IP connections to 44.x.x.x addresses

■ AMPRNet does not carry voice traffic and is not a replacement for your radio links. It is a data network for IP-based amateur radio applications. All traffic on AMPRNet is subject to Part 97 rules — no encryption of content, no commercial traffic, licensed operator identification required. WireGuard encryption of the tunnel itself is permitted as it is the transport, not the content.

Part D — Verification Checklist

CHECK	COMMAND / METHOD	EXPECTED RESULT
AMPRNet portal shows allocation	Login to portal.ampr.org → Subnets → My Subnets	Your 44.x.x.x/29 block shows Status: Active
WireGuard tunnel is up on gateway Pi	SSH to 192.168.50.2 then: <code>sudo wg show ampr0</code>	Shows latest handshake within last 2 minutes
AMPRNet gateway reachable from gateway Pi	<code>ping 44.0.0.1 -c 4</code>	Replies received — round trip time typically 10-50 ms
EMCOMM-NET devices have 44 route	<code>ip route show grep 44</code> (on any EMCOMM-NET device)	44.0.0.0/8 via 192.168.50.2

CHECK	COMMAND / METHOD	EXPECTED RESULT
AMPRNet reachable from FieldComms Pi	ping 44.0.0.1 -c 4 (on FieldComms Pi)	Replies received
Status page accessible	Open http://192.168.50.2:9000 in any browser on EMCOMM-NET	Shows tunnel status: UP, peer count, last handshake time
AMPRNet reachable from Pi 500 workstation	Open http://192.168.50.2:9000 in Chromium on Pi 500	Status page loads and shows tunnel UP

1 2

First Boot Verification — Full System

Step 12: First Boot Verification

After the installer completes and the Pi reboots, run through this verification checklist before handing off the system. Every service should show "active" and the dashboard should load cleanly from another device on EMCOMM-NET. If anything is not running, the troubleshooting section at the end of this guide covers the most common issues and their fixes.

```
# Check all FieldComms services
for svc in fcc-lookup health-monitor deadmans ics-platform kiwix nginx pat; do
echo "$svc: $(systemctl is-active $svc)"
done

# Test the dashboard from the Pi itself
curl -s http://localhost/ | head -5

# Test API endpoints
curl http://localhost:5050/health # FCC API health check
curl http://localhost:5051/health # System health monitor

# Verify Pi has the correct static IP
ip addr show eth0

# Should show: inet 192.168.50.1/24
```

14. Network Architecture Reference

Full Network Topology

The EMCOMM-NET deployment uses the ASUS RT-BE58 Go as the Wi-Fi access point and DHCP server. The UniFi Switch Lite 16 PoE distributes wired connections to both Pi servers, all operator workstations, the network printer, and any additional field devices. The 44Net Gateway Pi provides AMPRNet connectivity to every device on EMCOMM-NET by routing the 44.0.0.0/8 address block through a WireGuard tunnel to amprgw.ampr.org.

DEVICE	IP ADDRESS	ROLE	CONNECTION
ASUS RT-BE58 Go	192.168.50.254 (LAN gateway)	Wi-Fi 7 AP + DHCP server + WAN gateway	WAN: site Ethernet, Starlink, or USB tether (optional). EMCOMM-NET SSID on 2.4 GHz and 5 GHz.
UniFi Switch Lite 16 PoE	N/A (Layer 2 switch)	Wired distribution hub — 16 ports	Port 1 uplink to ASUS router. Ports 2-16 to all wired devices.
FieldComms Pi 5 (Pironman MAX 5)	192.168.50.1 (static)	FieldComms application server All EmComm tools and services	Wired GbE via UniFi Switch Port 2. Does not run Wi-Fi.
44Net Gateway Pi 5 (Argon NEO 5)	192.168.50.2 (static)	AMPRNet / 44Net WireGuard gateway Routes 44.0.0.0/8 for EMCOMM-NET	Wired GbE via UniFi Switch Port 3. WireGuard tunnel to amprgw.ampr.org.
Windows Laptop	192.168.50.3 (DHCP reservation)	Winlink Express + JS8Call IC-7300 HF station	Wired via Port 4 or Wi-Fi (EMCOMM-NET).
Color MFP Printer	192.168.50.10 (DHCP reservation)	Network printer shared to all devices	Wired via Port 5 or Wi-Fi (EMCOMM-NET).
Pi 500 Workstations x4	192.168.50.20-2 3 (DHCP reservations)	Operator browser stations	Wired via Ports 6-9 or Wi-Fi (EMCOMM-NET).
Field Devices (phones, tablets, laptops)	192.168.50.100- 200 (DHCP)	Additional operator browsers	Wi-Fi — EMCOMM-NET — 2.4 GHz or 5 GHz.



Recommended: set the ASUS router LAN IP to 192.168.50.254 and the Pi static IP to 192.168.50.1. This keeps the FieldComms URL clean and the router admin clearly separate at <http://192.168.50.254>.

13. Web Dashboard Reference

PAGE	URL	DESCRIPTION
Dashboard	/	Main hub — UTC clock, NWS weather alerts, APRS table, tool cards, DMS status
Amateur Net Control	/netcontrol.html	Multi-net logger, FCC autofill, precedence, ICS-309 export, server sync
Starcom Net Logger	/starcom.html	Public safety net log with Radio IDs, sc- prefix nets, ICS-309 export
Net Observer	/observer.html?net=NETNAME	Read-only net viewer — 15-second auto-refresh, no login
Member Roster	/roster.html	Directory with 11 certs, 13 equipment fields, 4 roles, CSV import/export
Resource Board	/resources.html	Equipment, vehicle, personnel tracking with status cycling
Tactical APRS Map	/tactical.html	Leaflet map — Graywolf + YAAC merged, live WebSocket, APRS symbols
Starcom Resource Map	/resmap.html	Unit positioning map with zone and polygon drawing tools
Callsign Lookup	/callsign.html	FCC local database — ~800K licensees, instant offline search
ICS Platform	/ics/	Command, Operations, Planning, Logistics, Finance sections
ICS-213	/ics213.html	General Message form with print output and form log
ICS-214	/ics214.html	Activity Log with personnel and timestamped activity rows
ICS-309	/ics309.html	Communications Log with incident archiving
NTS Radiogram	/nts.html	ARRL-format radiogram generator and traffic log
Winlink Form Import	/winlink-import.html	Import Winlink Express XML forms to incident archive
Pre-Flight	/preflight.html	GO/CAUTION/NO-GO deployment readiness assessment
Health Monitor	:5051/health	Live CPU/memory/disk/temp, all service status, GPS, internet
Pat Winlink	:8090	Browser-based backup Winlink client
Kiwix Library	:8081/	Offline reference library — WikiMed, Wikipedia, iFixit
Print Center	/printcenter.html	All printable documents in one place + incident cover sheet generator

14. Service & Port Reference

PORT	SERVICE	SYSTEMD UNIT	DESCRIPTION
80	nginx	nginx.service	Web frontend — serves all HTML pages
5050	FCC Lookup Server	fcc-lookup.service	Main API: callsign lookup, net logs, roster, resources, DMS, ICS forms
5051	Health Monitor	health-monitor.service	System health: CPU temp, memory, disk, GPS, all service status
5055	ICS Platform	ics-platform.service	ICS incident management: incidents, objectives, resources, T-cards
5056	References API	fieldcomms-refs.service	Reference library API
8080	Graywolf APRS	(graywolf.service)	APRS TNC client — REST API + WebSocket live stream
8081	Kiwix Library	kiwix.service	Offline web library — WikiMed, Wikipedia, iFixit, etc.
8082	YAAC APRS	yaac.service	YAAC Java APRS client — REST API + WebSocket
8083	Tile Server	fieldcomms-tiles.service	Offline map tile server (MBTiles)
8090	Pat Winlink	pat.service	Winlink email-over-radio — Packet, VARA HF, VARA FM
631	CUPS Printer	cups.service	Print server — USB printer shared to EMCOMM-NET
2442	JS8Call	(JS8Call app on laptop)	HF digital keyboard messaging — TCP API on Windows laptop

15. Maintenance & Updates

```
# Interactive maintenance menu:
sudo bash /opt/fieldcomms/scripts/update.sh

# Menu options:
# 1) Restart all services
# 2) Stop all services
# 3) Check service status
# 4) View live logs
# 5) Refresh FCC database
# 6) Fetch repeater data
# 7) Update web files from current directory
# 8) Backup data to /tmp
# 9) Show disk usage
```

USB Auto-Backup

Insert a USB drive formatted with the label **FIELDCOMMS** to trigger an automatic backup of all runtime data. The backup copies `/opt/fieldcomms/data/` to a timestamped folder on the USB drive.

```
# Format a USB drive with label FIELDCOMMS (Linux):
sudo mkfs.vfat -n FIELDCOMMS /dev/sda1

# Or on Windows: format as FAT32, set volume label to FIELDCOMMS

# Backup destination on USB:
# /media/fieldcomms/backup/YYYYMMDD_HHMMSS
```

16. Troubleshooting

SYMPTOM	LIKELY CAUSE / FIX
http://192.168.50.1 not reachable	Pi not running, or ASUS router not configured with 192.168.50.x subnet. Check Pi power LED. Verify router LAN IP is 192.168.50.1.
Dashboard loads but cards give errors	Not connected to EMCOMM-NET — device is on a different network. Check Wi-Fi — must show EMCOMM-NET.
FCC lookup returns no results	FCC database not yet built. Run: <code>sudo systemctl start fcc-refresh.service</code> (needs internet)
APRS map shows no stations	Graywolf or YAAC not running, or no RF received yet. Check Health Monitor for service status. Confirm antenna connected.
Winlink form import fails	Wrong file type — must be the XML attachment, not the message body. In Winlink Express, right-click .xml attachment → Save As → then import.
Service dot is red on Health Monitor	Background service has stopped. SSH to Pi: <code>sudo systemctl restart</code>
Pat Winlink not accessible at port 8090	pat.service not running. Run: <code>sudo systemctl start pat && sudo systemctl enable pat</code>
JS8Call card does not open	TCP Server API not enabled in JS8Call, or wrong IP entered. Verify: File → Settings → Reporting → Enable TCP Server API, port 2442, hostname 0.0.0.0.
Printer not visible on EMCOMM-NET	avahi-daemon not running, or CUPS printer not shared. Check: <code>sudo systemctl status avahi-daemon cups</code> . Verify Share This Printer is checked in CUPS UI.
Issue: Services crash on startup	Low disk space or permission error. Check: <code>df -h /</code> and <code>ls -la /opt/fieldcomms/</code> . Verify fieldcomms user owns /opt/fieldcomms/.

For any issue not covered here — open the Health Monitor at <http://192.168.50.1:5051/health> or check the system log with: `journalctl -u fcc-lookup -n 50`

17. Quick Reference Card

ITEM	VALUE
FieldComms dashboard	http://192.168.50.1
Wi-Fi network (SSID)	EMCOMM-NET
FieldComms Pi static IP	192.168.50.1
44Net Gateway Pi IP	192.168.50.2
44Net gateway status	http://192.168.50.2:9000
AMPRNet tunnel check	ping 44.0.0.1 (from any EMMCOMM-NET device)
ASUS router admin	http://192.168.50.254
CUPS printer admin	http://192.168.50.1:631
Pat Winlink (backup)	http://192.168.50.1:8090
Kiwix offline library	http://192.168.50.1:8081
Health monitor (raw)	http://192.168.50.1:5051/health
JS8Call TCP API (laptop)	http://[laptop-ip]:2442
Callsign K9ESV	McHenry County Emergency Services Volunteers and EMA
McHenry County grid	EN52
Default coordinates	42.3153 N / 88.4473 W (Woodstock, IL)
Install log	<code>/var/log/fieldcomms-install.log</code>
Application data	<code>/opt/fieldcomms/data/</code>
HTML pages	<code>/opt/fieldcomms/html/</code>
Update script	<code>sudo bash /opt/fieldcomms/scripts/update.sh</code>

Operator Workstation Options — Raspberry Pi 500 / 500+ + Raspberry Pi Monitor

FieldComms is a browser-based system — any device with a modern browser and Wi-Fi can connect to EMCOMM-NET and access every tool. The Raspberry Pi 500 paired with the official Raspberry Pi Monitor provides a purpose-built, low-cost, low-power operator workstation that is fully Pi ecosystem compatible and ideal for fixed EOC positions, shelter check-in stations, and net control operator desks. Funding through ARPA-E grants, FEMA BRIC, or 501(c)(3) equipment donations may cover these workstations.

Pi 500 vs Pi 500+ vs Pi 400 — Comparison

SPEC	Pi 400 (2020)	Pi 500 (Dec 2024) ★ Recommended	Pi 500+ (Sept 2025)
Processor	Cortex-A72 @ 1.8 GHz (Pi 4 generation)	Cortex-A76 @ 2.4 GHz (Pi 5 generation)	Cortex-A76 @ 2.4 GHz (Pi 5 generation)
RAM	4 GB DDR4	8 GB LPDDR4X	16 GB LPDDR4X
Storage	microSD only	microSD only (32 GB A2 included)	256 GB NVMe built-in + microSD slot
Keyboard	Membrane	Membrane	Mechanical (Gateron Blue KS-33)
Wi-Fi	802.11ac dual-band	802.11ac dual-band	802.11ac dual-band
Ethernet	Gigabit	Gigabit	Gigabit
USB ports	2× USB 3.0, 1× USB 2.0	2× USB 3.0, 1× USB 2.0	2× USB 3.0, 1× USB 2.0
Display output	2× micro-HDMI	2× micro-HDMI	2× micro-HDMI
Production until	Jan 2028	TBD (current model)	TBD (current model)
Best for FieldComms?	Acceptable — older chip, only 4 GB RAM	✓ YES — Pi 5 chip, 8 GB RAM, current generation	Overkill for browser use Justified only if also running heavy Linux apps locally

Raspberry Pi Monitor — 15.6"

SPEC	DETAIL
Panel	15.6" IPS LCD, 1920×1080 Full HD @ 60 Hz
Video input	Standard HDMI 1.4 (full-size) — requires micro-HDMI to HDMI cable with Pi 500
Audio	2× front-facing stereo speakers, 3.5mm headphone jack
Power	USB-C, 5V/1.5A — can power from Pi 500 USB port at 60% brightness/volume, or from separate USB-C supply for 100% brightness/volume
Mounting	Integrated angle-adjustable kickstand, VESA mount, wall hanger
Dimensions	Slim 15.6" form — similar footprint to a laptop
Colors	Red/White (matching Pi 500 keyboard) or Black
Where to buy	raspberrypi.com · Adafruit · PiShop.us · GigaParts · Amazon

The Pi 500 has micro-HDMI ports; the Raspberry Pi Monitor has a standard full-size HDMI input. You need a micro-HDMI to standard HDMI cable (or adapter). The Pi 500 desktop kit (\$120) includes one. When ordering separately, confirm the cable is included or purchase one — they are available from the same retailers listed above.

Operator Workstation — Bill of Materials (Per Station)

ITEM	MODEL / SPEC	WHERE TO BUY
— Standard Workstation (Pi 500) —		
Raspberry Pi 500 keyboard computer	Pi 500 standalone — Pi 5 chip, 8 GB RAM, 32 GB A2 microSD, keyboard	raspberrypi.com Adafruit · Amazon
Raspberry Pi Monitor	15.6" Full HD IPS, built-in speakers, kickstand, VESA mount	raspberrypi.com GigaParts · Amazon
micro-HDMI to HDMI cable	1m micro-HDMI to standard HDMI (Pi 500 → Monitor) Included in Pi 500 Kit (\$120) — verify before ordering separately	raspberrypi.com Amazon
USB mouse	Any USB or Bluetooth mouse — included in Pi 500 Kit	Amazon
USB-C power supply for Pi 500	Official Raspberry Pi 27W USB-C PD power supply (or equivalent)	raspberrypi.com Amazon
USB-C power supply for monitor (optional, for full brightness)	5V/1.5A USB-C supply — skip if powering monitor from Pi USB port (Pi USB port gives 60% brightness which may be dim outdoors)	Amazon
— Premium Workstation (Pi 500+) —		
Raspberry Pi 500+ keyboard computer	Pi 500+ — Pi 5 chip, 16 GB RAM, 256 GB NVMe SSD, mechanical keyboard (Gateron Blue), RGB	raspberrypi.com Adafruit · Amazon
Raspberry Pi Monitor + cables + mouse	Same as Standard Workstation above	Same as above

501(c)(3) Grant Funding Note: MCEMV/MCEMA is a 501(c)(3) nonprofit. Operator workstation equipment may be eligible for funding through: FEMA BRIC (Building Resilient Infrastructure & Communities), ARPA-E Emergency Communications grants, ARRL Foundation grants, local Community Foundation equipment grants, or AUXCOMM/ARES regional funding. Document each workstation as "emergency communications operator terminal for the McHenry County Emergency Services Volunteers (K9ESV), a 501(c)(3) nonprofit supporting McHenry County Emergency Management Agency (MCEMA) RACES/ARES/Starcom communications."

Recommended Deployment by Position

POSITION	RECOMMENDED DEVICE	REASON
Net Control Operator (fixed EOC desk)	Pi 500 + Pi Monitor	Dedicated keyboard, good display, Chromium runs every FieldComms page smoothly
ICS Section Chief (Planning, Ops, Logistics)	Pi 500 + Pi Monitor or Windows/Mac laptop	Needs reliable keyboard for ICS form entry; Pi 500 is sufficient for all ICS platform pages
Served Agency Staff (EOC or shelter)	Any tablet, Chromebook, or Pi 500	Observer Mode and ICS forms work on any browser — no special hardware needed
Winlink / JS8Call Operator	Windows laptop (required)	Winlink Express and JS8Call are Windows applications — Pi 500 cannot run them natively

Mobile / Field Operator	Phone or tablet	FieldComms works on any smartphone browser on EMCOMM-NET — no dedicated hardware needed
-------------------------	-----------------	---

■ The Pi 500 cannot run Windows applications natively. Winlink Express and JS8Call must run on the Windows laptop connected to the IC-7300. The Pi 500 is ideal for all browser-based FieldComms tools — net control logging, ICS forms, tactical maps, resource tracking, and the full ICS platform.