Offline Incident Management + Emergency Communications — Raspberry Pi 5

Communications and Incident Command System (ICS) incident management are inseparable, so FieldCommand marries them in one tool — and it keeps **amateur radio** ready as the communications that survive when public-service radio and cellular are overwhelmed or destroyed, as recent hurricanes across Florida, Louisiana, and the Carolinas — and massive tornado outbreaks — have shown. A deliberate goal is to promote and advance the use of amateur radio in emergency management. It is a self-contained server on a Raspberry Pi 5 (16 GB, Pironman MAX 5, dual 1 TB NVMe in RAID 1) paired with an ASUS RT-BE58 Go router that broadcasts its own **EMCOMM-NET** Wi-Fi (the Pi does not broadcast Wi-Fi itself). It serves a full suite of amateur radio, ICS, and SAR tools to any browser on scene — no internet, no app, no configuration. Everything is at **http://192.168.50.1**.

29 Web pages	**3** Dashboard modes	**10** Background services	**RAID 1** 2× 1TB NVMe

■ Amateur Radio Mode

· Net Control Logger — multi-net, FCC auto-fill, ICS-309 export
· Observer Mode — read-only live net view for served agencies
· Repeater Database — RepeaterBook data, band/ARES/mode filters
· NTS Radiogram — formatted ARRL traffic with log
· Callsign Lookup — full FCC database (~800K licensees) offline
· HF Propagation — band conditions, MUF/LUF, solar indices
· Dead Man's Switch — inactivity alert per armed net
· APRS Tactical Map — live Direwolf / APRS Command stations on Leaflet

■ Starcom / Public Safety Mode

· Starcom Net Logger — Radio ID / unit-based public safety nets
· SAR Net — quick-launch Search & Rescue net with unit tracking
· Resource Board — 5-state status cycle (Available → Demobilized)
· Facilities Directory — EOC, shelters, hospitals with frequencies
· Weather Net — quick-launch storm spotter check-in net
· Resource Tracking Map — unit placement, status, zone drawing
· Member Roster — Radio IDs, certifications, activation check-in
· ICS Platform access — full incident command from Starcom mode

■ ICS Incident Command — including SAR Activations

· Incident types: Natural Disaster, HazMat, **Search & Rescue**, MCI
· Operations Section — T-card board, resource assignments (ICS-204)
· Logistics Section — comms plan, supply tracking (ICS-205/206/211)
· ICS-213 / ICS-214 / ICS-309 forms — fill, print, archive by incident
· Command Section — objectives, safety, weather, staff (ICS-201–203)
· Planning Section — ICS-209, IAP tracker, resource status table
· Finance/Admin — cost accounting, time tracking, procurement
· Winlink Form Import — parse ICS XML from Winlink Express

■ SAR & Personnel Operations

· SAR incident type — full ICS platform for search and rescue ops
· SAR unit tracking — resource map with ■ Search & Rescue unit type
· Member certifications — ICS-100 through ICS-800, EmComm I/II, CERT
· Search & Rescue Net — Starcom logger net type for SAR radio ops
· Activation tracking — check-ins, walk-ins, deployment log per incident
· Operator access cards — Avery 5371 printable laminated cards

■ Winlink & Digital Comms — Windows Laptop + Pi

· Winlink Express (Windows) — primary Winlink with IC-7300 + VARA HF
· JS8Call (Windows) — HF keyboard-to-keyboard weak-signal digital mode
· Single USB cable from IC-7300 — no interface box required
· Pat Winlink (Pi) — browser-based backup email-over-radio, port 8090
· JS8Call API — open from any EMCOMM-NET device via dashboard card
· Winlink Form Import — ICS-213/214/309 XML archived to incident

■ Reference & Administration

· Reference Library — upload, search, tag, and serve field documents
· Kiwix Offline Library — WikiMed, Wikipedia, iFixit, Wikivoyage
· Pre-Flight Checklist — GO / CAUTION / NO-GO deployment readiness
· Radio Cheat Sheets — phonetic, Q-codes, prowords, band plan, CTCSS
· Print Center — all forms, reference cards, incident cover sheet
· System Health Monitor — CPU, memory, disk, services, GPS, internet

HOW TO ACCESS	Connect to Wi-Fi **EMCOMM-NET**, open any browser to **http://192.168.50.1** — no app, no login, no internet.
HARDWARE	Raspberry Pi 5 (16 GB) · Pironman MAX 5 · 2× 1 TB NVMe RAID 1 · ASUS RT-BE58 Go Wi-Fi 7 · UniFi Switch Flex 2.5G-5 · Windows laptop (Winlink Express + JS8Call).