

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV

RADIO (IC-7300 Menu)

MODEUSB-D (USB Digital)

MOD LevelUSB MOD = 40%

DATA MODUSB

DATA OFFMIC, ACC

Cl-V Addr94h (leave default)

Cl-V Baud115200

TransceiveON

COMP OFF

RF Power100% • MIC Gain 30%

PTT StartON (auto-tune)

COMPUTER (Express/VARA)

USB DriverSilicon Labs CP210x

Audio InMic (USB Audio CODEC) ~28

Audio OutSpkr (USB Audio CODEC) ~80

Radio ModelIcom 7300

Cl-V Addr94

ModeUSB Digital

COM PortYour COM# @ 115200 baud

RTS / DTRBoth UNCHECKED

PTTCl-V (via USB cable)

VARA Port8300 (TNC default)

USB cable only — no interface box needed · Mode USB-D · COMP OFF

IC-7300 + VARA Quick Reference

Winlink Express · K9ESV · McHenry Co. ESV