```
#include <string.h>
#include <stdio.h>

int main() {
    char msg[50];
    int w, i, j, n;

    printf("window size: ");
    scanf("%d", &w);

    printf("Text message");
    scanf("%s", msg);
    n = strlen(msg);

    for (i = 0; i < n; i += w) {
        printf("\nSender Buffer:\n");

        for (j = i; j < i + w && j < n; j++)
            printf("Frame %d: %c\n", j + 1, msg[j]);

        printf("Receiver: ");

        for (j = i; j < i + w && j < n; j++)
            printf("ACK %d ", j + 1);

        printf("\n");
    }

    printf("\n message transmitted successfully");
    return 0;
}
```

OUTPUT:

```c
#include <string.h>
#include <stdio.h>

int main() {
    char msg[50];
    int w, i, j, n;

    printf("window size: ");
    scanf("%d", &w);

    printf("Text message");
    scanf("%s", msg);
    n = strlen(msg);

    for (i = 0; i < n; i += w) {
        printf("\nSender Buffer:\n");

        for (j = i; j < i + w && j < n; j++)
            printf("Frame %d: %c\n", j + 1, msg[j]);

        printf("Receiver: ");

        for (j = i; j < i + w && j < n; j++)
            printf("ACK %d ", j + 1);

        printf("\n");
    }

    printf("\n message transmitted successfully");
    return 0;
}
```

input

```
window size: 5
Text messageKevin

Sender Buffer:
Frame 1: K
Frame 2: e
Frame 3: v
Frame 4: i
Frame 5: n
Receiver: ACK 1 ACK 2 ACK 3 ACK 4 ACK 5

 message transmitted successfully

...Program finished with exit code 0
Press ENTER to exit console.
```