





Param server: shell cmds

- A Parameter Server is a shared dictionary
- ROS uses to store global parameters/constants.
- Can be accessed by nodes
- The terminal cmds to play with them:
 - > `rosparam set param value` → set parameter
 - > `rosparam get param` → get parameter
 - > `rosparam load file` → load parameters from file
 - > `rosparam dump file` → dump parameters to file
 - > `rosparam delete param` → delete parameter
 - > `rosparam list` list parameter names

5

Checking param list

```
~/catkin_ws$ rosparam list
/rostdistro
/roslaunch/uris/host_rosvirtualserver_virtual_machine__32787
/roslaunch/uris/host_rosvirtualserver_virtual_machine__33307
/roslaunch/uris/host_rosvirtualserver_virtual_machine__38671
/roslaunch/uris/host_rosvirtualserver_virtual_machine__41027
/roslaunch/uris/host_rosvirtualserver_virtual_machine__41479
/roslaunch/uris/host_rosvirtualserver_virtual_machine__45735
/roslaunch/uris/host_rosvirtualserver_virtual_machine__45761
/rosversion
/run_id
rosvirtualserver@rosvirtualserver-virtual-
machine:~/catkin_ws$ rosparam get /rosversion
'1.12.7'
```

6

Param server: parameter types

- 32-bit integers
- booleans
- strings
- doubles
- iso8601 dates
- lists
- base64-encoded binary data



7

Param server: getting from python

```
global_name = rospy.get_param("/global_name")
relative_name = rospy.get_param("relative_name")
private_param = rospy.get_param('~private_name')
default_param = rospy.get_param('default_param', 'default_value')

# fetch a group (dictionary) of parameters
gains = rospy.get_param('gains')
p, i, d = gains['P'], gains['I'], gains['D']
```

25/06/2018

8

Param server: setting from python

```
# Using yaml strings
rospy.set_param('a_string', 'baz')
rospy.set_param('~private_int', '2')
rospy.set_param('list_of_floats', "[1., 2., 3., 4.]")
rospy.set_param('bool_True', "true")rospy.set_param('gains', "{p: 1, 'i': 2, 'd': 3}")
# Using raw python objects
rospy.set_param_raw('a_string', 'baz')
rospy.set_param_raw('~private_int', 2)
rospy.set_param_raw('list_of_floats', [1., 2., 3., 4.])
rospy.set_param_raw('bool_True', True)
rospy.set_param_raw('gains', {'p': 1, 'i': 2, 'd': 3})
rospy.get_param('gains/P') #should return 1
```



9

Param server: exercise

- try to set and get parameters using the Python code from previous slides
- try the terminal commands as well

```
> rosparam set param value → set parameter
> rosparam get      param → get parameter
> rosparam load file → load parameters from file
> rosparam dump file → dump parameters to file
> rosparam delete param → delete parameter
> rosparam list      list parameter names
```



10

Param server: definition in a YAML file

- YAML is a lightweight markup language that supports all parameter types

- Config.yaml

```
camera:
  left:
    name: left_camera
    exposure: 1
  right:
    name: right_camera
    exposure: 1.1
```

- package.launch

```
<launch>
  <node name="name" pkg="package" type="node_type">
    <rosparam command="load"
      file="$(find package)/config/config.yaml" />
  </node>
</launch>
```



11

Param server: yaml file → yaml format

- YAML uses "tags" to override types, where the YAML syntax may be ambiguous
- Common tags

```
!!str, !!int, !!float, !!seq, !!map
```



12