

Knowledge Graphs

Lecture 5: Knowledge Graph Applications

Karlsruher Institut für Technologie

FIZ Karlsruhe
Leibniz Institute for Information Infrastructure

- 5.1 Ontologies in Action Books
- 5.2 Knowledge Graphs
- 5.3 RDF and OWL Knowledge Graphs
- 5.4 Knowledge Graph Programming
- 5.5 Knowledge Graph Visualization
- 5.6 Knowledge Graph Analytics



Knowledge Mining and Knowledge Discovery



Knowledge Discovery [in Databases] (KDD) is the nontrivial process of identifying **valid**, **novel**, **potentially useful**, and **ultimately understandable patterns** in (massive) data sources. (Fayyad et al, 1996)

- valid: to a certain degree the discovered patterns should also hold for new, previously unseen problem instances.
- novel: at least to the system and preferable to the user.
- potentially useful: they should lead to some benefit to the user or task.
- ultimately understandable: the end user should be able to interpret the patterns either immediately or after some post-processing.

Knowledge Mining and Knowledge Discovery



Knowledge Discovery [in Databases] (KDD) is the nontrivial process of identifying **valid**, **novel**, **potentially useful**, and **ultimately understandable patterns** in (massive) data sources. (Fayyad et al, 1996)

Goals:


- Descriptive Modelling: explains the characteristic and the behaviour of the observed data
- Predictive Modelling: predicts the behaviour of new data based on some model

• Important:

The extracted model/pattern does not have to apply in 100% of the cases

The Knowledge Discovery Process





Selection:
Select a relevant dataset or focus on a subset of a dataset

Preprocessing/
Cleaning:
Data integration from different sources, Data
Cleaning

Transformation:
Select useful
features, feature
transformation,
dimensionality
reduction

Data Mining: Search for patterns of interest Evaluation:
Evaluate
patterns based
on
interestingness
measures,
model validation

Hands-On Example - Knowledge Graph Analytics



- Let's discover "interesting knowledge" about Physicists
- General knowledge graphs, as e.g. DBpedia or Wikidata contain data about thousands of physicists

Data Acquisition

 First, let's look at an random example to see what kind of data we have to expect



Joseph Fourier, physicist


5. Knowledge Graph Applications / 5.6 Knowledge Gra

1. Data Acquisition


 First, let's look at an random example to see what kind of data we have to expect



Statements







of Contambanda Gregorian

country of citizenship

Kingdom of France
start time


21 March 1768 Gregorian

Knowledge Graphs 2020 , Prof. Dr. Harald Sack & Dr. Mehwish Alam, FIZ I

1. Data Acquisition

5. Knowledge Graph Applications / 5.6 Knowledge (

First, let's look at an random example to see what kind of data we have to expect statement





https://www.wikidata.org/wiki/Q8772

Knowledge Graphs 2020 , Prof. Dr. Harald Sack & Dr. Mehwish Alam, F

WikiData Recap

object subject/context for statement

21 March 1768 Gregorian start time 21 September 1792 Gregorian end time ▼ 0 references French First Republic

country of citizenship

Access via different namespaces for properties:

wdt: connects an item to a value wd:Q8772 wdt:P27 ?country.

First French Empire start time end time - 0 references

Bourbon Restoration

start time

end time

▼ 0 references

First French Empire

start time

start time

end time

▼ 0 references

Kingdom of France

6 April 1814 Gregorian 20 March 1815 Gregorian

21 September 1792 Gregorian

18 May 1804 Gregorian

18 May 1804 Gregorian

6 April 1814 Gregorian


Knowledge Graphs 2020, Prof. Dr. Harald Sack & Dr. Mehwish Alam, FIZ Karlsruhe - Leibniz Institute

20 March 1815 Gregorian 9

WikiData Recap

Access via different namespaces for properties:


- wdt: connects an <u>item</u> to a <u>value</u>
 wd:Q8772 wdt:P27 ?country .
- p: connects a <u>subject</u> to a <u>statement</u> wd:Q8772 p:P27 ?country_statement .



WikiData Recap

Access via different namespaces for properties:

- wdt: connects an <u>item</u> to a <u>value</u>
 wd:Q8772 wdt:P27 ?country .
- p: connects a <u>subject</u> to a <u>statement</u>wd:Q8772 p:P27 ?country statement .
- pq: connects <u>statement</u> to <u>qualifier value</u>?country_statement pq:P582 ?statement_value



Knowledge Graph Analytics with SPARQL



- Convenient and very powerful way to analyze Knowledge Graph data
- E.g. WIKIDATA SPARQL endpoint provides visualization toolkit with
 - Bar plots and Histograms
 - Scatter plots
 - Timelines
 - Graph visualizations
 - o etc.

Knowledge Graph Analytics with SPARQL



what other occupations do Physicists have?


```
Wikidata Query Service
                                Help -
                                                           More tools -
      1 #defaultView:BarChart
0
      2 SELECT ?occupationLabel (COUNT(DISTINCT(?scientist)) AS ?numsci) WHERE {
                                                                                                                           SPARQL query
          ?scientist wdt:P106 wd:0169470 .
X
          ?scientist wdt:P106 ?occupation FILTER (?occupation != wd:Q169470)
          SERVICE wikibase: label { bd:serviceParam wikibase: language "en, fr, es" }
1.
      6 } GROUP BY ?occupationLabel
7 ORDER BY DESC(?numsci)
      8 Limit 100
13
```

Knowledge Graph Analytics with SPARQL

Karlsruher Institut für Technologie

FIZ Karlsruhe
Leibniz Institute for Information Infrastructure

what other occupations do Physicists have?



SPARQL query

2. Get Data



There is so much more to know about physicists

Compose a SPARQL query to collect physicist data available in Wikidata

```
SELECT ?physicist (SAMPLE(YEAR(?birthdate)) AS ?bdate)
  (COUNT(DISTINCT(?country)) AS ?countries)
  (COUNT(DISTINCT(?occupation)) AS ?occupations)
  (COUNT(DISTINCT(?employer)) AS ?employers)
  (COUNT(DISTINCT(?award)) AS ?awards)
  (COUNT(DISTINCT(?member)) AS ?members)
  (COUNT(DISTINCT(?field)) AS ?fields)
  (SAMPLE(?sex) AS ?gender)
WHERE {
  ?physicist wdt:P106 wd:Q169470 .
  ?physicist wdt:P27 ?country .
  ?physicist wdt:P569 ?birthdate .
  ?physicist wdt:P106 ?occupation .
  ?physicist wdt:P108 ?employer .
  ?physicist wdt:P166 ?award .
  ?physicist wdt:P463 ?member .
  ?physicist wdt:P21 ?sex .
  ?physicist wdt:P101 ?field .
} GROUP BY ?physicist
```



Joseph Fourier, physicist


2. Get Data

Karlsruher Institut für Technologie

FIZ Karlsruhe
Leibniz Institute for Information Infrastructure

There is so much more to know about physicists

Compose a SPARQL query to collect physicist data available in Wikidata



SPARQL query



5. Knowledge Graph Applications / 5.6 Knowledge Graph A		■	5.6 - Physicists Data Selle File Edit View Insert Format	Data Tools	Add-ons Help	All changes	saved in Drive				
2.	Get Data	□ □ □ 100% ▼ \$ % .0 00 123 ▼ Default (Ari ▼ 10 ▼ B I 号 A ◆ 田 記 ▼ 三 ▼ 土 ▼ ☆ ▼ ▼ □ ▼ ▼ ▼ □ ▼ ▼ ▼ ▼ □ ▼ ▼ ▼ □ ▼ ▼ ▼ ▼									
_ `			A	В	С	D	E	F	G	Н	
		1	scientist	bdate	countries	occupations	employers	awards	members		
		2	http://www.wikidata.org/entity/Q80	1955-06-08	1	7	6	40)	5	
		3	http://www.wikidata.org/entity/Q164384	1881-05-11	6		3 4	37		29	
		4	http://www.wikidata.org/entity/Q183279	1930-03-15	2	. 4	2	33	3	12	
		5	http://www.wikidata.org/entity/Q28189	1926-01-29	2		5	32	2	11	
		6	http://www.wikidata.org/entity/Q71013	1941-10-30	2	! 3	5	31		10	
		7	http://www.wikidata.org/entity/Q106624	1946-02-26	2	: 5	i 1	30)	14	
		8	http://www.wikidata.org/entity/Q997	1921-05-21	2		1	28	3	6	
		9	http://www.wikidata.org/entity/Q83552	1916-07-11	2	: 3	6	28	3	6	
		10	http://www.wikidata.org/entity/Q335213	1942-06-23	1		5 4	28	3	12	
		-11	http://www.wikidata.org/entity/Q201513	1951-08-26	1	4	1	28	3	8	
		12	http://www.wikidata.org/entity/Q184566	1915-07-28	1	4	3	27	,	12	
		13	http://www.wikidata.org/entity/Q487983	1903-02-13	3		3	26	3	4	
<u>Da</u>	ata in Google Doc Spreadsheet	14	http://www.wikidata.org/entity/Q2587259	1946-01-23	2		1	26	3	4	
		15	http://www.wikidata.org/entity/Q29573	1930-11-11	1	3	1	25	5	4	
		16	http://www.wikidata.org/entity/Q80917	1962-09-04	1	7	3	25	5	5	
		17	http://www.wikidata.org/entity/Q48983	1901-02-28	1	8	5	23	3	11	
		18	http://www.wikidata.org/entity/Q91410	1962-12-23	2	. 4	2	23	3	5	

http://www.wikidata.org/entity/Q190697

http://www.wikidata.org/entity/Q193803

http://www.wikidata.org/entity/Q16389 http://www.wikidata.org/entity/Q1030228

http://www.wikidata.org/entity/Q148109

http://www.wikidata.org/entity/Q1975294

http://www.wikidata.org/entity/Q1248892

http://www.wikidata.org/entity/Q164396

http://www.wikidata.org/entity/Q574605

http://www.wikidata.org/entity/Q155794

http://www.wikidata.org/entity/Q172844

http://www.wikidata.org/entity/Q187224

http://www.wikidata.org/entity/Q60066

http://www.wikidata.org/entity/Q336397

http://www.wikidata.org/entity/Q237825

http://www.wikidata.org/entity/Q323320

http://www.wikidata.org/entity/Q62857

http://www.wikidata.org/entity/Q154855

http://www.wikidata.org/entity/Q172466

http://www.wikidata.org/entity/Q4106859

	8	
	9	
	10	
	-11	
	12	
	13	
<u>Data in Google Doc Spreadsheet</u>	14	
Data in Google Doc Spreadsneet	15	
	16	
	17	
	18	
	19	
	20	
	21	
	22	
	23	
	24	
	25	
	26	
	27	
	28	
	29	
	30	
	31	
	32	
	33	
	34	
	35	
	36	ĺ
Manufada Caraba 2020 Barf Da Harald Carb C Da Mahad L Al 517 K L	37	
Knowledge Graphs 2020 , Prof. Dr. Harald Sack & Dr. Mehwish Alam, FIZ Karlsru	38	



1932-10-24

1936-10-10

1936-01-08

1929-01-23

1940-06-01

1913-06-26

1942-07-14


1948-02-28

3. Clean Up Data



1977-12-23






<u>CleanedUp Data in Google Doc Spreadsheet</u>

Knowledge Graphs 2020, Prof. Dr. Harald Sack & Dr. Mehwish Alam, 1.25 Antstrume vikidata.org/entity/Q19502586 11071-12-18 2020, Prof. Dr. Harald Sack & Dr. Mehwish Alam, 1.25 Antstrume vikidata.org/entity/Q19502586 11071-12-18

http://www.wikidata.org/entity/Q21259815







The first quartile (Q_1) is defined as the middle number between the smallest number and the median of the data set.

The **third quartile** (Q_3) is the middle value between the median and the highest value of the data set.

-86.00

3.00

17.00 38.85

51.00

:1329.00

X0

Min.


Mean

Max.

1st Qu.:

Median:

3rd Qu.:



Knowledge Graphs 2020 , Prof. Dr. Harald Sack & Dr. Mehwish Alam, FIZ Karlsruhe - Leibniz Insti



Whiskers are indicating variability outside the upper and lower quartiles.

Any data not included between the whiskers should be considered as an **outlier**.

Whiskers: $IQR \times 1.5 = (Q_3 - Q_1) \times 1.5$

X0

Min. : -86.00


1st Qu.: 3.00

Median : 17.00

Mean : 38.85

3rd Qu.: 51.00

Max. :1329.00



Knowledge Graphs 2020 , Prof. Dr. Harald Sack & Dr. Mehwish Alam, FIZ Karlsruhe - Leibniz Insti




4. **Analyse the Data** E.g. via python

[29] physicists.boxplot('awards')

<matplotlib.axes. subplots.AxesSubplot at 0x7f3c00578f28> 40 35 30 25 20 15 10 5 0

awards

Data in Google Collab Notebook



Knowledge Graphs

5. Knowledge Graph Applications / 5.6 Knowledge Graph Analytics



Picture References:

- [1] Louis Leopold Bouilly, Engraved portrait of French mathematician Jean Baptiste Joseph Fourier (1768 1830), early 19th century.
 [Public Domain]
 https://commons.wikimedia.org/wiki/File:Fourier2.jpg
- [2] David Teniers the Younger, Archduke Leopold Wilhelm in his Gallery in Brussels (1651). [Public Domain]
 https://commons.wikimedia.org/wiki/File:David Teniers the Younger Archduke Leopold William in his Gallery at Brussels Google Art Project.jpg