



XSLT <xsl:value-of> Element

[< Previous](#)[Next >](#)

The <xsl:value-of> element is used to extract the value of a selected node.

The <xsl:value-of> Element

The <xsl:value-of> element can be used to extract the value of an XML element and add it to the output stream of the transformation:

Example

```
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform">

<xsl:template match="/">
  <html>
  <body>
    <h2>My CD Collection</h2>
    <table border="1">
      <tr bgcolor="#9acd32">
        <th>Title</th>
        <th>Artist</th>
      </tr>
      <tr>
        <td><xsl:value-of select="catalog/cd/title"/></td>
        <td><xsl:value-of select="catalog/cd/artist"/></td>
      </tr>
    </table>
  </body>
</html>
</xsl:template>

</xsl:stylesheet>
```

[Try it Yourself »](#)

Example Explained


Note: The **select** attribute, in the example above, contains an XPath expression. An XPath expression works like navigating a file system; a forward slash (/) selects subdirectories.

The result from the example above was a little disappointing; only one line of data was copied from the XML document to the output. In the next chapter you will learn how to use the `<xsl:for-each>` element to loop through the XML elements, and display all of the records.


[< Previous](#)

[Log in to track progress](#)

[Next >](#)



COLOR PICKER



[Spaces](#)[Upgrade](#)[Newsletter](#)[Get Certified](#)[Report Error](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)
- [XML Examples](#)
- [jQuery Examples](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

Get Certified

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [Front End Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [PHP Certificate](#)
- [jQuery Certificate](#)
- [Java Certificate](#)
- [C++ Certificate](#)
- [C# Certificate](#)
- [XML Certificate](#)

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

