



# XSLT - On the Client

[< Previous](#)[Next >](#)

XSLT can be used to transform the document to XHTML in your browser.

## A JavaScript Solution

In the previous chapters we have explained how XSLT can be used to transform a document from XML to XHTML. We did this by adding an XSL style sheet to the XML file and let the browser do the transformation.

Even if this works fine, it is not always desirable to include a style sheet reference in an XML file (e.g. it will not work in a non XSLT aware browser.)

A more versatile solution would be to use a JavaScript to do the transformation.

By using a JavaScript, we can:

- do browser-specific testing
- use different style sheets according to browser and user needs

That is the beauty of XSLT! One of the design goals for XSLT was to make it possible to transform data from one format to another, supporting different browsers and different user needs.

## The XML File and the XSL File

Look at the XML document that you have seen in the previous chapters:

```
<?xml version="1.0" encoding="UTF-8"?>
<catalog>
  <cd>
    <title>Empire Burlesque</title>
    <artist>Bob Dylan</artist>
    <country>USA</country>
    <company>Columbia</company>
    <price>10.90</price>
    <year>1985</year>
  </cd>
  .
  .
</catalog>
```

[View the XML file.](#)

And the accompanying XSL style sheet:

```

<?xml version="1.0" encoding="UTF-8"?>

<xsl:stylesheet version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform">

<xsl:template match="/">
  <h2>My CD Collection</h2>
  <table border="1">
    <tr bgcolor="#9acd32">
      <th style="text-align:left">Title</th>
      <th style="text-align:left">Artist</th>
    </tr>
    <xsl:for-each select="catalog/cd">
      <tr>
        <td><xsl:value-of select="title" /></td>
        <td><xsl:value-of select="artist" /></td>
      </tr>
    </xsl:for-each>
  </table>
</xsl:template>

</xsl:stylesheet>

```

[View the XSL file.](#)

**Notice that the XML file does not have a reference to the XSL file.**

**IMPORTANT:** The above sentence indicates that an XML file could be transformed using many different XSL style sheets.

## Transforming XML to XHTML in the Browser

Here is the source code needed to transform the XML file to XHTML on the client:

### Example

```

<!DOCTYPE html>
<html>
<head>
<script>
function loadXMLDoc(filename)
{
  if (window.ActiveXObject)
  {
    xhttp = new ActiveXObject("Msxml2.XMLHTTP");
  }
  else
  {
    xhttp = new XMLHttpRequest();
  }
  xhttp.open("GET", filename, false);
  try {xhttp.responseType = "msxml-document"} catch(err) {} // Helping IE11
  xhttp.send("");
  return xhttp.responseXML;
}

function displayResult()
{
  xml = loadXMLDoc("cdcatalog.xml");
  xsl = loadXMLDoc("cdcatalog.xsl");

```

```
// code for IE
if (window.ActiveXObject || xhttp.responseType == "msxml-document")
{
    ex = xml.transformNode(xsl);
    document.getElementById("example").innerHTML = ex;
}
// code for Chrome, Firefox, Opera, etc.
else if (document.implementation && document.implementation.createDocument)
{
    xsltProcessor = new XSLTProcessor();
    xsltProcessor.importStylesheet(xsl);
    resultDocument = xsltProcessor.transformToFragment(xml, document);
    document.getElementById("example").appendChild(resultDocument);
}
}
</script>
</head>
<body onload="displayResult()">
<div id="example" />
</body>
</html>
```

Try it Yourself »

**Tip:** If you don't know how to write JavaScript, please study our [JavaScript tutorial](#).

## Example Explained:

**The loadXMLDoc() function does the following:**

- Create an XMLHttpRequest object
- Use the open() and send() methods of the XMLHttpRequest object to send a request to a server
- Get the response data as XML data


**The displayResult() function is used to display the XML file styled by the XSL file:**

- Load XML and XSL files
- Test what kind of browser the user has
- If Internet Explorer:
  - Use the transformNode() method to apply the XSL style sheet to the xml document
  - Set the body of the current document (id="example") to contain the styled xml document
- If other browsers:
  - Create a new XSLTProcessor object and import the XSL file to it
  - Use the transformToFragment() method to apply the XSL style sheet to the xml document
  - Set the body of the current document (id="example") to contain the styled xml document

[< Previous](#)

[Log in to track progress](#)

[Next >](#)




Save 770\$

**Lifelong  
Access To  
All Current  
And Future  
Courses**


Get Full Access

COLOR PICKER





**Learn AWS**  
..and Boost  
your cloud  
skills!



This skill  
offers many job  
opportunities.

Read more

---

Spaces

Upgrade

Newsletter

Get Certified

Report Error

---

## Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

## Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)
- [XML Examples](#)
- [jQuery Examples](#)

## Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

## Get Certified

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [Front End Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [PHP Certificate](#)
- [jQuery Certificate](#)
- [Java Certificate](#)
- [C++ Certificate](#)
- [C# Certificate](#)
- [XML Certificate](#)

---

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie](#) and [privacy policy](#).

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.

