Explainable Supply Chain Optimization: Reinforcement Learning Against Tuned Classical Policies, with a Number-Checked Language-Model Explainer

1st Koushik
Department of Artificial Intelligence
Amrita Vishwa Vidyapeetham
Coimbatore, Tamil Nadu, India
Roll No.: CB.SC.U4AIE23312
cb.sc.u4aie23312@cb.students.amrita.edu

2nd Santosh
Department of Artificial Intelligence
Amrita Vishwa Vidyapeetham
Coimbatore, Tamil Nadu, India
Roll No.: CB.SC.U4AIE23310
cb.sc.u4aie23310@cb.students.amrita.edu

3rd Srinith
Department of Artificial Intelligence
Amrita Vishwa Vidyapeetham
Coimbatore, Tamil Nadu, India
Roll No.: CB.SC.U4AIE23357
cb.sc.u4aie23357@cb.students.amrita.edu

4th Dharani Pratap
Department of Artificial Intelligence
Amrita Vishwa Vidyapeetham
Coimbatore, Tamil Nadu, India
Roll No.: CB.SC.U4AIE23330
cb.sc.u4aie23330@cb.students.amrita.edu

Abstract

Every day a retailer has to decide how much of each product to order and which supplier to use. We built a decision-support system for this problem and tested a reinforcement learning agent against four classical inventory policies that we tuned ourselves. The system has a simulator calibrated on 1,067,371 real sales records, a MaskablePPO agent that picks quantity and supplier together, the four classical policies, and a language model that explains each decision and also writes crisis scenarios for testing. Every method was scored on the same 30 held-out simulation runs.

The tuned agent earns Rs. 79.7 lakh per 180-day run. That is 90.8% of the best classical policy (Rs. 87.8 lakh), and it beats two of the four classical policies. The gap to the best one is modest but real (paired $t = -6.45$, $n = 30$, 95% CI 5.5 to 10.6 lakh). Most of it comes from ordering fees: the agent splits its orders across suppliers and pays about twice as much in fees, and nothing in its inputs tells it what it ordered earlier. Action masking made the agent about three times better, and tuning closed 38% of the gap that was left. Training on LLM-written crises did not make the agent more robust ($t = +1.69$, not significant), while plain tuning did. For the explainer, 5 of 30 raw LLM outputs contained a number the simulator never produced. A number check caught all five, which lifts the accuracy of what the user sees from 83% to 100%.

1 Introduction

A shop that orders badly loses money in two different ways. If it orders too much, cash sits in the warehouse, storage costs add up, and seasonal items end up unsold. If it orders too little, customers go elsewhere and the sale is gone. Choosing a supplier makes this harder. One supplier is cheap but slow, one is quick but expensive, and a third looks fine on paper but ships only 80% of what was asked for and goes offline more often than the others. Since today's order turns into next week's stock, each decision changes the situation for the next one.

The usual tools here are rules like (s, S), EOQ with a reorder point, the newsvendor model, and forecasting with safety stock. They look at one product at a time and assume demand behaves reasonably. In our data it does not: the variance of daily demand is about 216 times its mean, much more than a Poisson model would give. Reinforcement learning (RL) can in principle learn a combined ordering and sourcing policy that no simple formula captures, and earlier work has tried deep RL on inventory problems with mixed results against tuned rules [3, 5]. There is also a practical problem. A buyer is unlikely to follow a recommendation that nobody can explain.

We wanted to check two things: whether an RL agent can match or beat tuned classical policies, and whether an LLM can make the agent's decisions understandable without inventing facts. We kept the baselines strong, kept the test runs separate from everything used for tuning, and decided in advance to report the result whichever way it came out. This paper makes the following contributions.

1. A complete system with a calibrated simulator, a Mask-

ablePPO agent that chooses quantity and supplier jointly, four tuned classical baselines, an LLM explainer, an LLM crisis generator, and a recommend-only dashboard (Sections 3–5).
2. A fair comparison on 30 held-out runs with paired tests. The tuned agent reaches 90.8% of the best classical policy, and the remaining Rs. 8.1 lakh gap can be traced to one specific cause (Sections 6.1 and 7).
3. Two controlled ablations. Action masking is worth about $3\times$ and tuning closes 38% of what is left, but training on LLM-generated crises does not improve robustness (Sections 6.2 and 6.3).
4. A measurement of the explainer showing that its number check matters: 83% of raw outputs were correct, against 100% of delivered ones (Section 6.4).

2 Related Work

Deep RL for inventory. Oroojlooyjadid et al. [5] trained a deep Q-network on the beer game and found it matched or beat base-stock policies when the players cooperate. That game has one product in a serial chain and no choice of supplier. Gijsbrechts et al. [3] used an actor-critic method on lost-sales and dual-sourcing problems. It came out about as good as well-tuned heuristics, not clearly better, and it needed a lot of tuning. Boute et al. [4] review the field and list fair benchmarking and interpretability among the open problems. Our setting adds the joint choice of quantity and supplier under one shared warehouse, and we treat fair benchmarking as a requirement of the study.

Policy optimization and action masking. Proximal Policy Optimization [1] limits how far each update can move the policy and is a common stable default. Huang and Ontañón [2] showed that masking invalid actions is a valid policy-gradient method and works with large action spaces. This is what makes our daily action space of $21^{10} \approx 1.7 \times 10^{13}$ combinations manageable. We build on the Stable-Baselines3 library [7].

Retail demand data. Chen et al. [6] applied data mining to online-retail transactions of the same kind as the UCI Online Retail II set [8] that we use.

Explanation. A trained policy outputs a number and no reason, which is one reason such policies rarely reach a decision-maker. We do not try to open the network. The LLM only restates facts that the simulator computed, and a check rejects any number it makes up (Section 4.4). As far as we know, an RL inventory agent, a number-checked LLM explainer, and an LLM that writes the test scenarios have not been evaluated together before. We claim this only for our own setting.

Supplier	Price	Lead	Ships	Fee
EconoSource	base	5–8 d	90%	Rs. 2,100
RapidTrade	+35%	1–3 d	98%	Rs. 4,725
MidWay	+15%	3–5 d	80%	Rs. 3,150

Table 1: The three suppliers. Minimum orders are 100, 20 and 50 units. MidWay goes offline most often and RapidTrade almost never.

3 Problem Setup

Data. The UCI Online Retail II dataset [8] has 1,067,371 sales records from a UK online gift shop. We removed cancelled orders, returns, negative quantities and rows with no product code, and summed the sales into one row per product per day. Saturdays are left out because the shop never traded on them, and filling them with zeros would create a weekly dip that is not real. We picked ten products on purpose so that they cover three kinds of demand: four steady ones (coefficient of variation 1.02 to 1.20), three moderate ones (1.29 to 1.65) and three bursty ones (2.09 to 2.34). The agent never sees the raw records. We measure five things from them (mean demand, variability, weekday pattern, month pattern and how often a day has no sales), and the simulator recreates demand from those with a Gamma–Poisson (negative binomial) model.

Environment. The environment is a Gymnasium simulator with 10 products, 3 suppliers and 180 days per run. The first 14 days are a warm-up and are not scored. All products share one warehouse of 20,000 units, and any delivery that does not fit is refused and written off. A day runs in this order: deliveries arrive, demand is drawn (adjusted for weekday and month), sales are made, orders are placed, and profit is counted. Unmet demand becomes a lost sale with a penalty and is carried over as backlog. Orders come after demand because a real buyer places them once the day is known. Stock left at the end is valued at 60% of its cost, and storage costs 0.15% of item cost per day. The suppliers (Table 1) are our own invention, because no public dataset records supplier terms. None of them is better than the others on every count.

Decision and objective. Each day, for each product, the system picks one of $7 \times 3 = 21$ options: a quantity level and a supplier. Across 10 products that is $21^{10} \approx 1.7 \times 10^{13}$ combinations per day. The aim is to maximise profit,

$$\begin{aligned} \text{profit} = \text{sales} - \text{purchases} - \text{storage} \\ - \text{fees} - \text{stockout} - \text{overflow}. \end{aligned} \tag{1}$$

Seed groups. We use three separate groups of random seeds. Seeds 100 to 111 tune the classical policies, seeds 900 to 905 pick the best checkpoint during training, and seeds 500 to 529 are used only for the final numbers. On each of those final seeds every method sees the same customers and the same delivery delays, so comparisons are paired.

Metrics. Profit optimisation has no ground-truth label, so classification accuracy does not apply. We report mean profit per 180-day run, relative profit (the agent's profit divided by the best classical profit), fill rate (the share of demand served), and the ordering, stockout and overflow costs. For the explainer we report *raw accuracy* (every number real and all key details present) and *delivered accuracy* (after the number check).

4 Method

4.1 System Overview

The system has five parts: the simulator, a MaskablePPO agent, four tuned classical policies, an LLM explainer and an LLM crisis generator. A Streamlit dashboard ties them together in what we call shadow mode. The best classical policy is the *engine*. The agent runs next to it as a *challenger* that is scored but never acts. Any decision can be explained on request. The dashboard only recommends and never places an order.

4.2 Agent and Objective

The agent sees 88 numbers. For each product these are stock on hand, stock on order, days of cover, the 7-day mean and variability of demand, the demand trend and the backlog. On top of that come the weekday, the time of year, and each supplier's availability, lead time and recent reliability. The action is a vector of ten entries, one per product, each over the 21 joint options. Quantity and supplier are chosen together rather than separately. This trained $2.8\times$ faster, and it matches how the decision works, since a large order only makes sense from a supplier that can deliver it. The reward is the day's profit, scaled and clipped, and it is zero during the warm-up.

We use MaskablePPO. PPO maximises the clipped surrogate objective

$$L^{\text{CLIP}}(\theta) = \hat{\mathbb{E}}_t\Big[\min\big(\rho_t \hat{A}_t,\ \text{clip}(\rho_t, 1-\epsilon, 1+\epsilon)\hat{A}_t\big)\Big], \tag{2}$$

where $\rho_t = \pi_\theta(a_t|s_t)/\pi_{\theta_{\text{old}}}(a_t|s_t)$. Masking adds a vector m to the logits z before the softmax,

$$\pi_\theta(a \mid s) = \text{softmax}(z+m)_a, \quad m_a = \begin{cases} 0 & \text{legal} \\ -\infty & \text{illegal,} \end{cases} \tag{3}$$

so an offline supplier or an order too large for the warehouse can never be sampled. The network is small (two layers of 128 or 256 units) and trains on a CPU.

4.3 Classical Baselines

We implemented four textbook policies that choose from the same 21 options per product as the agent, so none of them has finer control than the others: (s, S), EOQ with a reorder point, the newsvendor model, and forecasting with safety stock. Each was tuned with a grid search on the 12 tuning seeds. This step matters. Widening the search lifted the best policy from Rs. 69.7 lakh to Rs. 89.2 lakh on the tuning seeds, and an untuned baseline would have made the agent look better than it is.

4.4 LLM Explainer and the Number Check

We never ask the LLM why a decision was made. The agent's real reason sits inside a neural network, so any "because" from the LLM would be a plausible story and not the cause. Instead the LLM is given a set of facts F that the simulator computed (stock, orders in transit, days of cover, recent demand, what was ordered and from whom, and that supplier's lead time and reliability) and writes two or three sentences from them. Let $N(x)$ be the set of numbers in a text x. We accept the output y only if $N(y) \subseteq N(F)$ and the key details are present. Otherwise a fixed template is shown. Three free models are tried in turn (`gemma-4-31b-it`, `glm-5.2`, `nemotron-3-ultra-550b-a55b`) through OpenRouter, with retries, because the free endpoints often hit rate limits.

4.5 Crisis Generator and Training on Crises

We ask the LLM for realistic supply-chain crises. It returns scenarios such as a demand spike on four products, a supplier outage, a delivery delay and a cost increase, and these overlap in time. We do not trust the output. The scenario type has to be one we know, supplier and product numbers have to exist (invalid product numbers are dropped, not wrapped around), values are clamped to safe ranges, and the time window is moved inside the 180 days. We tested this with six deliberately broken inputs, and each was either corrected or rejected.

For training on crises we saved 16 crisis sets built from 19 scenarios and split them 10 for training and 6 for testing. At the start of each run the agent trains on a random set from the training part, and it is tested only on the 6 it has never seen. Its seed, settings and number of steps match the untuned agent, so crisis exposure is the only difference.

5 Experimental Setup

Training. All agents use MaskablePPO. The untuned agent trains for 1M steps with default settings. For the hyperparameter search we ran eight configurations for 250,000 steps each, then trained the best two to 2M steps on Kaggle. Each long run took about 1.5 hours, and the whole search about 4.8 hours. Table 2 lists the winning configuration. Checkpoints are chosen on seeds 900 to 905 and results come from seeds 500 to 529.

The search picked the lowest learning rate and the larger network. That fits what we suspected: the earlier runs were

Setting	Value
Learning rate	5×10^{-5} (lowest offered)
Entropy coefficient	0.005
Discount γ	0.995
Rollout length	1024
Network	$[256, 256]$
Training steps	2M

Table 2: Winning hyperparameters from the 8-configuration search.

unstable because they learned too fast, and the network size was not the problem.

Training logs. Figure 1 shows the console output of a short 30,000-step training run, which we made only to show what the training console reports. The models reported in this paper were trained for 1M and 2M steps. Under it, Figure 2 shows the checkpoint evaluations printed for the tuned 2M-step run, and Figure 3 shows the summary of the hyperparameter search.

Statistics. We compare methods with paired t-tests on the per-seed differences ($n = 30$) and report the 95% interval of the mean difference.

6 Results

6.1 Main Comparison

Table 3 and Figure 4 compare all methods on the 30 held-out seeds. The best classical policy, forecasting with safety stock, earns Rs. 87.8 lakh. The tuned agent earns Rs. 79.7 lakh, or **90.8%** of that. The difference of Rs. 8.1 lakh is statistically clear (paired $t = -6.45$, $n = 30$, $p < 0.001$, 95% CI 5.5 to 10.6 lakh), and the classical policy comes out ahead on 26 of the 30 seeds. The agent does beat two of the four classical policies, EOQ and (s, S). A shop with no system would simply order the same amount every day. Compared with that, the engine raises profit from Rs. 53.3 lakh to Rs. 87.8 lakh (+65%) and wins on all 30 seeds. The agent beats the fixed order on 29 of 30.

6.2 Ablation: What Each Step Added

Table 4 separates the two improvements. Action masking made by far the biggest difference, about $3\times$. Without it the agent spends most of its training finding out that some choices are pointless. Tuning and longer training then closed 38% of the remaining gap, taking it from Rs. 13.0 lakh down to Rs. 8.1 lakh. The learning curves are in Figure 5.

6.3 Robustness to LLM-Generated Crises

Table 5 scores each method on 10 normal seeds and on 6 held-out crisis sets that the agents never trained on. Every method loses more than a third of its profit. The tuned agent never saw a crisis during training, yet it has the highest crisis profit and the smallest drop among the agents.

Training on crises did not help. The crisis-trained agent earns Rs. 38.9 lakh in a crisis, against Rs. 38.8 lakh for the control, and it gave up Rs. 7.7 lakh of normal profit to get there. Its smaller percentage drop is misleading, because it starts lower and so has less to lose. The difference is not significant ($t = +1.69$, $n = 30$). This is why we show the drop next to the actual profit.

6.4 Explainer Accuracy

We scored 30 real decisions (6 days $\times$ 10 products), shown in Table 6. The LLM answered every call once retries were allowed. In five of the 30 raw outputs there was a number the simulator never produced. They read fluently, and a buyer would probably not have noticed. The check caught all five and showed the template instead, so every explanation the user saw was correct and complete. Without the check, about one explanation in six would have carried a made-up figure.

Our first version of this metric only scored outputs that had already passed the check. It reported 100% for a model that invented numbers in 17% of cases, which told us nothing about the model, so we now report both figures.

7 Error Analysis

Where does the Rs. 8.1 lakh gap come from? Figure 6 shows one traced run, and the averages in Table 3 agree with it.

- **Ordering fees.** The agent pays Rs. 5.8 lakh against Rs. 2.9 lakh for the best classical policy. It spreads its orders over all three suppliers. In the traced run it placed 719 orders and the classical policy placed 323, almost all with the cheap supplier.
- **Fill rate.** It is 95.1% against 97.9%. The agent runs out of stock more often, which costs about Rs. 3 lakh extra in penalties.
- **Overflow.** Only the RL agents have zero overflow loss. They learned the shared-warehouse limit, while every classical policy wastes some goods.

We think the reason for the fee gap is that the agent cannot observe its own history. None of the 88 inputs says how long ago it last ordered, how much it has paid in fees, or which supplier it used last. So it pays double and has no way to notice. This is about what the agent can see, so more tuning would not fix it. Adding a few history features per product looks like the most promising change, but we have not tried it yet.

8 Efficiency and Deployment

Everything was trained on ordinary hardware. A 1M-step run takes about 48 minutes on a laptop CPU, and each 2M-step run took about 1.5 hours on Kaggle. Training on crises




Figure 1: Terminal output of a short training run (30,000 steps) with the project's training script. The reported models were trained for 1M and 2M steps.




Figure 2: Checkpoint evaluations of the tuned 2M-step agent, read from its saved training history (profit per 180-day run on the checkpoint seeds).

costs roughly twice as much per step as normal training (we measured 156 steps per second). We did not measure inference speed or memory use.

Our results point to shadow mode, which is how the dashboard works. The tuned classical policy is the engine a buyer would run. The agent runs beside it, and its decisions are logged and scored but not carried out. The explainer covers whichever decision is on screen. If the challenger beats the engine steadily on live data, it could then be promoted. Several things are still missing before real use: handling of new products with no history, limits on order value, an audit trail, a live data feed, and a signal that tells a human to take over when the system is unsure.

9 Limitations

The first two matter most.

Invented suppliers. Lead times, reliability and fees were set by hand to cover the usual trade-off. No public dataset records them, so the rupee values should be read as relative comparisons and not as forecasts.

Unequal difficulty in crisis training. The crisis-trained agent had a harder task with the same number of steps, so part of its weaker result may come from under-training and not from the method.

Explainer sample. We tested 30 decisions with one model setup and one seed. The explainer restates computed facts. It does not describe how the network reasons, and we do not claim that it does.

One shop, ten products. Other product categories, larger ranges and other cost structures were not tested.

Free LLM endpoints. Free models are rate-limited, so an explanation can take up to a minute and sometimes falls back to the template.

10 Broader Impact

We would not deploy the agent today, because it earns less than a simpler method and is no more robust. We would use it only as a scored challenger. There is one more risk to name. An explanation that reads smoothly can make a wrong decision look right. That is why the numbers are checked, and why we call the explanation a restatement of facts and




Figure 3: Summary of the 8-configuration hyperparameter search, read from the saved sweep results.

Method	Profit (Rs. lakh)	Std	Fill rate	Fees (Rs. lakh)	Stockout (Rs. lakh)
Forecast + safety stock	**87.8**	4.6	97.9%	2.9	6.1
Newsvendor	86.2	4.4	98.0%	3.4	7.4
RL agent, tuned, 2M steps	**79.7**	5.5	95.1%	5.8	9.2
RL agent, 2nd config, 2M steps	77.0	5.4	93.6%	7.1	10.5
EOQ + reorder point	75.9	7.4	96.8%	2.8	10.5
RL agent, untuned, 1M steps	74.8	5.8	94.3%	7.4	11.0
(s, S) policy	73.9	7.1	94.9%	3.1	16.5
Constant order (no system)	53.3	13.4	92.3%	3.5	29.0
RL agent, no masking, 1M steps	23.7	9.0	94.8%	14.7	11.3

Table 3: Mean profit per 180-day run over 30 held-out seeds (500–529). Std is the spread across seeds. All methods face the same customers and delays on each seed. Rupee amounts use 1 GBP = Rs. 105.




Figure 4: Profit of every method on the 30 held-out seeds. Green bars are classical policies and red bars are RL agents. Error bars show the standard deviation across seeds.

not a reason. Because the suppliers are invented, the rupee figures are best read as comparisons inside one simulator.

Step	Train	Test	Gap
PPO, no masking	24.9	23.7	−64.1
+ action masking	76.4	74.8	−13.0
+ tuning, 2M steps	86.2	79.7	**−8.1**

Table 4: Profit in Rs. lakh. Train: checkpoint seeds (900–905). Test: held-out seeds (500–529). Gap: test profit minus the best classical policy.




Figure 5: Learning progress on the checkpoint seeds. This shows how training went. The reported scores come from the held-out seeds.

11 Conclusion

A MaskablePPO agent reaches 90.8% of the profit of the best tuned classical policy on 30 held-out seeds. It beats two of the four classical policies and beats a fixed daily order on 29 of 30 seeds, but the best classical policy still wins by Rs. 8.1 lakh per run ($t = -6.45$). So the idea that RL would adapt better than a tuned formula did not hold up, either on normal days or in a crisis. What we can say with confidence comes from how we tested it. The baselines were tuned, the test seeds were kept separate, the crisis-trained agent was tested on crises it had never seen, and the percentage drop was shown next to the actual profit. Action masking and tuning each helped by a measurable amount, and training on crises did not. The explainer is accurate only because its output is checked: 83% before the check and 100% after.

The error analysis suggests the next step. The gap comes from fees caused by splitting orders across suppliers, and the agent cannot see its own ordering history. Giving it that history and repeating the same evaluation is the experiment most likely to change the main result.




Figure 6: One run in the simulator: stock against demand for one product, warehouse fill, cumulative profit, and the supplier mix (panel D).

Method	Normal	Crisis	Drop
Forecast + safety stock	87.4	53.7	−38.6%
RL, tuned	80.4	**50.7**	**−37.0%**
RL, untuned (control)	73.8	38.8	−47.5%
RL, crisis-trained	66.0	38.9	−41.1%

Table 5: Profit in Rs. lakh on normal seeds and on 6 unseen LLM-generated crises.

Measure	Result
LLM answered (after retries)	100%
Only real numbers (raw output)	83% (25/30)
Complete	100%
Raw model accuracy	**83%**
Delivered accuracy	**100%**
Length	2.9 sentences, 58 words

Table 6: Explainer results on 30 decisions. Raw accuracy means all numbers were real and the key details present, before the check. Delivered accuracy is what the user saw.

References

[1] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. arXiv:1707.06347, 2017.

[2] S. Huang and S. Ontañón. A closer look at invalid action masking in policy gradient algorithms. In *FLAIRS-35*, 2022.

[3] J. Gijsbrechts, R. N. Boute, J. A. Van Mieghem, and D. Zhang. Can deep reinforcement learning improve inventory management? *Manufacturing & Service Operations Management*, 2022.

[4] R. N. Boute, J. Gijsbrechts, W. van Jaarsveld, and N. Vanvuchelen. Deep reinforcement learning for inventory control: A roadmap. *European Journal of Operational Research*, 2022.

[5] A. Oroojlooyjadid, M. Nazari, L. V. Snyder, and M. Takáč. A deep Q-network for the beer game. *Manufacturing & Service Operations Management*, 2022.

[6] D. Chen, S. L. Sain, and K. Guo. Data mining for the online retail industry. *Journal of Database Marketing & Customer Strategy Management*, 2012.

[7] A. Raffin et al. Stable-Baselines3: Reliable reinforcement learning implementations. *JMLR*, 22(268), 2021.

[8] UCI Machine Learning Repository. Online Retail II. `https://archive.ics.uci.edu/dataset/502`.