

Date: 07-05-2024

UCS2611 - Internet Programming Lab Mini Project

A. Karthikeyan	3122 21 5001 041
M Irayanbu	3122 21 5001 036
Anand	3122 21 5001 009

Mini project Description

Develop a full stack web application for conducting *On-line quiz using MVC architecture*. The application should facilitate the normal and admin users to access it. To the normal user, instructions, questions with options and the score needs to be provided as the following snapshots. Admin user can view the registered users and their scores.

Operations:

- Authenticate the user and provide necessary messages
- Keep a timer for the Quiz
- Sending appropriate GET http requests from front end, to the endpoint in the node server.
- Perform necessary operations in the Mongo Collection at the endpoints
- Create a suitable interface in ReactJS to display the results

Tech-Stack:

- ReactJS
- NodeJS
- Express Server
- MongoDB

GitHub Link:


<https://github.com/KKBUGHUNTER/Internet-Programming-Lab/tree/main/Project/examination-app/>

Run the Project: DIR: home

```
npm install  
npm start
```

```
node server.js
```

Project Structure:



Front-end Code:

index.js

```
import React from 'react';
import ReactDOM from 'react-dom';
import { BrowserRouter } from 'react-router-dom';
import App from './App';
import reportWebVitals from './reportWebVitals';

ReactDOM.createRoot(document.getElementById('root')).render(
  <React.StrictMode>
    <BrowserRouter>
      <App />
    </BrowserRouter>
  </React.StrictMode>
);

reportWebVitals();
```

App.js

```
// App.js
import React, { useEffect, useState } from 'react';
import { Routes, Route, Navigate, useLocation } from 'react-router-dom';

import Login from "./views/Login";
import Signup from "./views/Signup";
import Dashboard from "./views/appview/Dashboard";
import Profile from "./views/appview/Profile";
import MainTestPage from "./views/appview/testpage/MainTestPage.js";
import Cookies from 'js-cookie';

function App() {
  const [redirected, setRedirected] = useState(false);
  const storedToken = Cookies.get('token');
  const location = useLocation();

  useEffect(() => {
    if (!redirected) {
      if (location.pathname === '/' || location.pathname === '/signup') {
        if (storedToken) {
          setRedirected(true);
          window.location.href = '/dashboard';
        }
      } else if (location.pathname === '/dashboard') {
        if (!storedToken) {
          setRedirected(true);
          window.location.href = '/';
        }
      }
    }
  });
}
```

```

    }
  }
}, [storedToken, redirected, location]));

return (
  <Routes>
    { /* Stage 1 */ }
    <Route path="/" element={ <Login /> } />
    <Route path="signup" element={ <Signup /> } />

    { /* Stage 2 */ }
    <Route path="/dashboard" element={ <Dashboard /> } />
    <Route path="/profile" element={ <Profile /> } />

    { /* Stage 3 */ }
    <Route path="/test" element={ <MainTestPage /> } />

    <Route path="*" element={ <Navigate to="/" /> } />
  </Routes>
);
}

```

export default App;

utils/CookieHelper.js

import Cookies from 'js-cookie';

```

class CookieHelper {
  static getFullCookie() {
    return Cookies.get('token');
  }

  static getUserId() {
    const token = CookieHelper.getFullCookie();
    return token.substring(0, 13);
  }

  static removeTokenCookie() {
    Cookies.remove('token');
  }
}

```

export default CookieHelper;

Views/appviews/AppBar.js

import Cookies from 'js-cookie';

```

function AppBar({ parse }) {

```

```

const Logout = () =>{
  Cookies.remove('token');
  window.location.href = '/';
}

const style = {
  appBar: {
    display: "flex",
    justifyContent: "space-between",
    alignItems: "center",
    height: "40px",
    width: "100%",
    backgroundColor: "#1F85DE",
    color: "white",
    padding: "5px",
  },
  profileImage: {
    marginRight: "10px",
  },
  btn:{
    position:"absolute",
    right:"70px",
    padding:"4px",
    backgroundColor:"red",
    border:"0",
    color:"white",
    fontWeight:"bold",
    borderRadius:"5px"
  }
};

return (
  <div style={style.appBar}>
    <b>Hello <i>{parse.userId} </i>,</b>
    <button type="submit" onClick={Logout}
style={style.btn}>LogOut</button>
    <a href="http://localhost:3000/profile">
      
      </a>
    </div>
  );
}

export default AppBar;

```

CourseBox.js

```
import React from 'react';

function CourseBox({ data, onTakeTest }) {
  const style = {
    master: {
      margin: "10px",
      padding: "10px",
      border: "0",
      width: "400px",
      border: '3px solid #DE1F85',
      borderRadius: "10px",
    },
    btn: {
      padding: "5px",
      width: "100px",
      border: "0",
      borderRadius: '5px',
      backgroundColor: "#85DE1F",
      float: 'right'
    }
  };

  const handleTakeTest = () => {
    onTakeTest(data.testName);
  };

  return (
    <div style={style.master}>
      <h2 style={{color:"darkgreen"}}>{data.testName}</h2>
      <small>{data.testDescription}</small> <br/> <br/>
      <span><b>Score: <i>{data.score}</i></b></span> <br />
      <button onClick={handleTakeTest} style={style.btn}> <big><b>
>Take Test</b></big></button>
      <br />
      <br />
    </div>
  );
}

export default CourseBox;
```

Dashboard.js

```
import React, { useEffect, useState } from 'react';
import AppBar from './AppBar';
import CourseBox from './CourseBox';
import CookieHelper from '../utils/CookieHelper';
```

```

function Dashboard() {
  const [userDetails, setUserDetails] = useState();
  const [testData, setTestData] = useState();

  useEffect(() => {
    const userId = CookieHelper.getUserId();
    if (userId) {
      LoadUserData(userId);
      LoadTestData();
    }
    else{
      window.location.href = '/';
    }
  }, []);

  function LoadTestData(){
    fetch(`http://localhost:7020/test`)
      .then(res => res.json())
      .then(data => {
        setTestData(data);
      })
      .catch(error => console.log(error))
  }

  function LoadUserData(regNo){
    fetch(`http://localhost:7020/userDetails?userId=${regNo}`)
      .then(res => res.json())
      .then(data => {
        setUserDetails(data.username);
      })
      .catch(error => console.log(error))
  }

  const style = {
    master: {
      margin: "0",
      padding: "0",
      border: "0",
      display: "flex",
      flexWrap: "wrap",
    },
  };

  const handleTakeTest = (courseName) => {
    console.log(`Clicked on ${courseName}`);
    window.location.href = `/test?Subject=${courseName}`;
  };

```

```

return (
  <div>
    <AppBar parse={{userId:userDetails}} />
    <h1>Take Your New Test  </h1>
    <br/>
    <div style={style.master}>
      {testData && testData.map((test, index) => (
        <CourseBox
          key={index}
          data={{
            testName: test.testName,
            testDescription: test.testDesc,
            score: test.totalNoOfQues
          }}
          onTakeTest={handleTakeTest}
        />
      ))}
    </div>
    {/* {questionSet && <MainTestPage questionSet={questionSet} />}
  */}
  </div>
);
}

```

export default Dashboard;

Profile.js

// /src/views/appviews/Profile.js

```

import React from 'react';
import {useState, useEffect} from 'react';
import CookieHelper from '../utils/CookieHelper';

```

```

function Profile() {
  const [name, setName] = useState();
  const [regNo, setRegNo] = useState();
  const [score, setScore] = useState();
  const [coursesCompleted, setCoursesCompleted] = useState();
  const [courseNames, setCourseNames] = useState([]);

  useEffect(() => {
    const userId = CookieHelper.getUserId();
    setRegNo(userId);
    // console.log("data in useEffect: ", userId);
  }, []);

  useEffect(() => {

```



```

    if (regNo) {
      // console.log("load data", regNo);
      LoadData();
    }
  }, [regNo]);

```

```

const LoadData = () => {
  console.log("load data", regNo);
  fetch(`http://localhost:7020/userDetails?userId=${regNo}`)
    .then(res => res.json())
    .then(data => {
      setName(data.username);
      setScore(data.score);
      setCoursesCompleted(data.courseCount);
      setCourseNames(data.courseList);
    })
    .catch(error => console.log(error))
}

```

```

const DeleteAccount = () => {
  fetch(`http://localhost:7020/deleteUser?userId=${regNo}`, {
    method: 'DELETE'
  })
    .then(res => res.json())
    .then(data => {
      if (data.message === "DeleteSuccess") {
        // Redirect to the homepage if the deletion was successful
        CookieHelper.removeTokenCookie();
        window.location.href = '/signup';
      }
    })
    .catch(error => console.log(error));
}

```

```

const style = {
  container: {
    margin: "auto",
    padding: "30px",
    maxWidth: "600px",
    boxShadow: "0px 0px 20px rgba(0, 0, 0, 0.1)",
    borderRadius: "10px",
    backgroundColor: "#f9f9f9",
  },
  header: {
    textAlign: "center",
    marginBottom: "20px",
    fontSize: "24px",
    fontWeight: "bold",
  },
}

```

```

        color: "#333",
        textTransform: "uppercase",
    },
    detailItem: {
        marginBottom: "10px",
        fontSize: "16px",
        color: "#666",
    },
    courseList: {
        listStyleType: "none",
        padding: 0,
        marginTop: "10px",
    },
    courseItem: {
        marginBottom: "5px",
        paddingLeft: "20px",
        position: "relative",
        fontSize: "14px",
        color: "#444",
    },
    courseBullet: {
        position: "absolute",
        left: "0",
        top: "50%",
        transform: "translateY(-50%)",
        width: "10px",
        height: "10px",
        borderRadius: "50%",
        backgroundColor: "#007bff",
    },
    delBtn: {
        backgroundColor: "red",
        border: "0",
        borderRadius: "8px",
        padding: "8px",
        fontWeight: "bold",
        fontSize: "14px",
        color: "white",
        marginLeft: "40%"
    }
};

return (
    <div style={style.container}>
        {/* <AppBar parse={{userId:regNo}}/> */}
        <div>
            <h2 style={style.header}>Profile</h2>

```

```

        
        <br/>
        <br/>
        <div style={style.detaillItem}>
            <strong>Name:</strong> {name}
        </div>
        <div style={style.detaillItem}>
            <strong>Registration Number:</strong> {regNo}
        </div>
        <div style={style.detaillItem}>
            <strong>Score:</strong> {score}
        </div>
        <div style={style.detaillItem}>
            <strong>Courses Completed:</strong> {coursesCompleted}
        </div>
        {courseNames && (
            <div style={style.detaillItem}>
                <strong>Course Lists:</strong>
                <ul style={style.courseList}>
                    {courseNames.map((course, index) => (
                        <li key={index} style={style.courseItem}>
                            <span style={style.courseBullet}></span>
                            {course}
                        </li>
                    ))}
                </ul>
            </div>
        )}
    </div>
    <button type="submit" onClick={DeleteAccount}
style={style.delBtn}>Delete Account</button>
</div>
);
}

```

export default Profile;

src/views/appview/testpage/MainTestPage.js

```

import React, { useState, useEffect } from 'react';
import CookieHelper from '../../utils/CookieHelper';

const MainTestPage = () => {
    const [userDetails, setUserDetails] = useState();
    const [regno, setRegNo] = useState();
    const [questionSet, setQuestionSet] = useState({});
    const [selectedOptions, setSelectedOptions] = useState({});
    const [score, setScore] = useState(null);

```

```

const [prevScore, setPrevScore] = useState();
const Subject = new
URLSearchParams(window.location.search).get('Subject');
const [timer, setTimer] = useState(10 * 60); // 10 minutes timer

useEffect(() => {
  const userId = CookieHelper.getUserId();
  setRegNo(userId);
  if (userId) {
    LoadUserData(userId);
    fetch(`http://localhost:7020/taketest?testName=${Subject}`)
      .then(res => res.json())
      .then(data => {
        console.log(data);
        setQuestionSet(data.questionSet || {});
        const initialSelectedOptions = {};
        data.questionSet?.Question?.forEach((question, index) => {
          initialSelectedOptions[index] = "";
        });
        setSelectedOptions(initialSelectedOptions);
      })
      .catch(error => console.log(error));

    const countdown = setInterval(() => {
      setTimer(prevTimer => prevTimer - 1);
      if (timer <= 0) {
        clearInterval(countdown);
        handleSubmit();
      }
    }, 1000);

    return () => clearInterval(countdown);
  } else {
    window.location.href = '/';
  }
}, [Subject]);

const LoadUserData = (regNo) => {
  fetch(`http://localhost:7020/userDetails?userId=${regNo}`)
    .then(res => res.json())
    .then(data => {
      setUserDetails(data.username);
      setPrevScore(data.score);
    })
    .catch(error => console.log(error));
};

const handleOptionSelect = (index, option) => {
  setSelectedOptions(prevState => ({

```

```

        ...prevState,
        [index]: option,
      }));
    });

const handleSubmit = () => {
  let correctAnswers = 0;
  const submittedOptions = {};

  questionSet?.Question?.forEach((question, index) => {
    const selectedOption = selectedOptions[index];
    submittedOptions[index] = selectedOption ? selectedOption : "";
    if (selectedOption === question.ans) {
      correctAnswers++;
    }
  });

  setScore(correctAnswers);
  updateUserScoreData(regno, correctAnswers, Subject);
};

const updateUserScoreData = (regno, score, Subject) => {
  fetch(`http://localhost:7020/updateUserData?userId=${
    {regno}&score=${score}&testName=${Subject}&prevScore=${
    {prevScore}}`)
    .then(res => res.json())
    .then(data => {
      setTimeout(() => {
        window.location.href = '/profile';
      }, 5000);
    })
    .catch(error => console.log(error));
};

return (
  <div style={{ margin: '20px auto', maxWidth: '800px', fontFamily:
'Arial, sans-serif', color: '#333', background: '#2E8B57', padding: '20px',
borderRadius: '10px' }}>
    <h1 style={{ fontSize: '24px', textAlign: 'center', marginBottom:
'20px', color: '#fff' }}>Time Remaining: {Math.floor(timer / 60)}:{timer %
60 < 10 ? '0' : ''}{timer % 60}</h1>
    <h2 style={{ fontSize: '20px', textAlign: 'center', marginBottom:
'20px', color: '#fff' }}>{Subject}</h2>
    {questionSet && questionSet.Question && (
      <div>
        <h3 style={{ fontSize: '18px', marginBottom: '10px', color:
'#fff' }}>{questionSet.testName}</h3>
        <p style={{ fontSize: '16px', marginBottom: '20px', color:
'#fff' }}>{questionSet.testDescription}</p>

```

```

        {questionSet.Question.map((question, index) => (
            <div key={index} style={{ marginBottom: '20px',
borderBottom: '1px solid #ccc', paddingBottom: '20px' }}>
                <h3 style={{ fontSize: '16px', marginBottom: '10px',
color: '#fff' }}>{question.Q}</h3>
                <ul style={{ listStyleType: 'none', padding: 0 }}>
                    {['opt1', 'opt2', 'opt3', 'opt4'].map((optionKey,
optionIndex) => (
                        <li key={optionIndex} style={{ marginBottom:
'10px' }}>
                            <label style={{ display: 'flex', alignItems:
'center', fontSize: '14px', color: '#fff' }}>
                                <input
                                    type="radio"
                                    name={`question-${index}`}
                                    value={question[optionKey]}
                                    checked={selectedOptions[index] ===
question[optionKey]}
                                    onChange={() =>
handleOptionSelect(index, question[optionKey])}
                                    style={{ marginRight: '10px', cursor:
'pointer' }}
                                />
                                {question[optionKey]}
                            </label>
                        </li>
                    ))}
                </ul>
            </div>
        ))}
        <button onClick={handleSubmit}
style={{ backgroundColor: '#4CAF50', color: 'white', padding: '10px
20px', borderRadius: '5px', border: 'none', cursor: 'pointer', fontSize:
'16px' }}>Submit</button>
    </div>
)}
{score !== null && (
    <div style={{ position: 'fixed', top: '0', left: '0', width: '100%',
height: '100%', backgroundColor: 'rgba(0, 0, 0, 0.5)', zIndex: '9999',
display: 'flex', justifyContent: 'center', alignItems: 'center' }}>
        <div style={{ background: '#fff', padding: '20px',
borderRadius: '10px', textAlign: 'center' }}>
            <h2 style={{ color: '#333', marginBottom:
'20px' }}>Your Score</h2>
            <h1 style={{ color: '#007bff', fontSize: '48px',
marginBottom: '20px' }}>{score}/{questionSet.Question.length}</h1>
        </div>
    </div>
)}

```

```

    </div>
  );
}

```

```
export default MainTestPage;
```

Server side Code:

server.js

```

const express = require('express');
const bodyParser = require('body-parser');
const cors = require('cors');
const mainRoute = require('./src/routes/MainRoute');
const path = require('path');
const cookieParser = require('cookie-parser');

const app = express();
const PORT = 7020;

app.use(bodyParser.json());
app.use(cors());
app.use(cookieParser());

// Serve static files from the React build directory
// app.use(express.static(path.join(__dirname, 'build')));

// API routes
app.use('/', mainRoute);

// Serve index.html for all other routes
// app.get('*', (req, res) => {
//   res.sendFile(path.join(__dirname, 'build', 'index.html'));
// });

app.listen(PORT, () => {
  console.log(`SERVER Listening http://localhost:${PORT}`);
});

```

/src/routes/MainRoute.js

```

const express = require('express');
const router = express.Router();
const LoginRegisterController =
  require('../controllers/LoginRegisterController.js');
const dashboardController =
  require("../controllers/DashboardController.js");
const profileController = require("../controllers/ProfileController.js");
const testController = require("../controllers/TestContorller.js");

```

```

// stage 1
router.post('/login', LoginRegisterController.login);
router.post('/register', LoginRegisterController.register);

// stage 2
router.get('/userDetails', profileController.getUserDetails);
router.delete('/deleteUser', profileController.deleteAccount);
router.get('/test', dashboardController.getTestList);

// stage 3
router.get("/taketest", testController.testData);
router.get('/updateUserData', profileController.updateUserScore);

module.exports = router;

// /src/modules/RegisterModel.js

const MainModel = require('./MainModel.js');

async function RegisterUser(username, registerNumber, password){
  const mainModule = new MainModel();
  await mainModule.connect();
  const userCollection = await mainModule.getUserCollection();

  try {
    // Insert the user with the given
    const user = {
      _id: registerNumber,
      username: username ,
      password: password,
      solved: [],
      score: 0
    };

    // Insert the user into the user collection
    await userCollection.insertOne(user);

    return user;

  } catch (error) {
    console.error('Error finding user:', error);
    return "ERROR";
  }
  finally {
    await mainModule.close();
  }
}

```



```

module.exports = { RegisterUser };

// /src/modules/MainModule.js

const { MongoClient } = require('mongodb');

class MainModel {

  constructor() {
    this.client = new MongoClient('mongodb://localhost:27017'); //
    Database Client
    this.dbName = 'ExaminationApp'; // Database name
    this.userCollection = 'User'; // User Collection
    this.appDataCollection = 'AppData'; // AppData Collection
  }

  async connect() {
    try {
      await this.client.connect();
      // console.log("Connected successfully to server");
    } catch(error) {
      console.error("Connection Error: ", error);
    }
  }

  async getCollection(collectionName) {
    try {
      const database = this.client.db(this.dbName);
      const collection = database.collection(collectionName);
      return collection;
    } catch(error) {
      console.error("Error getting collection: ", error);
    }
  }

  async getUserCollection() {
    return this.getCollection(this.userCollection);
  }

  async getAppDataCollection() {
    return this.getCollection(this.appDataCollection);
  }

  async close() {
    try {
      await this.client.close();
      // console.log("Connection closed");
    } catch(error) {
      console.error("Error closing connection: ", error);
    }
  }
}

```

```
    }  
  }  
}
```

```
module.exports = MainModel;
```

```
// /src/modules/LoginModule.js
```

```
const MainModel = require('./MainModel.js');
```

```
async function LoginUser(registerNumber) {  
  const mainModule = new MainModel();  
  await mainModule.connect();  
  const userCollection = await mainModule.getUserCollection();  
  
  try {  
    // Find the user with the given registerNumber  
    // console.log("Searching for user: ", registerNumber);  
    const user = await userCollection.findOne({ _id: registerNumber });  
    // console.log(user);  
    return user;  
  
  } catch (error) {  
    // console.log('Error finding user');  
    return "ERROR";  
  }  
  finally {  
    await mainModule.close();  
  }  
}
```

```
module.exports = { LoginUser };
```

```
// /src/models/ProfileModel.js
```

```
const MainModel = require('./MainModel.js');
```

```
async function getUser(userId) {  
  const mainModule = new MainModel();  
  await mainModule.connect();  
  const userCollection = await mainModule.getUserCollection();  
  
  try {  
  
    const user = await userCollection.findOne({ _id: userId });  
    // console.log("model" , user);  
    return user;  
  } catch (error) {  
    console.log("Error finding user details:", error);  
    return null;  
  }  
}
```

```

    }
  }
  async function DeleteUser(userId){
    const mainModule = new MainModel();
    await mainModule.connect();
    const userCollection = await mainModule.getUserCollection();

    try {
      // Delete the user document from the collection based on the userId
      const result = await userCollection.deleteOne({ _id: userId });

      if (result.deletedCount === 1) {
        return "DeleteSuccess";
      } else {
        return "DeleteFailed";
      }
    } catch (error) {
      console.log("Error deleting user:", error);
      return null;
    }
  }
}

async function updateUserScore(userId, newScore, testName, prevScore)
{
  const mainModule = new MainModel();
  await mainModule.connect();
  const userCollection = await mainModule.getUserCollection();
  console.log(userId, newScore, testName, prevScore);
  const updatedScore = prevScore + newScore;
  console.log("Updated Score: ", updatedScore);
  try {
    await userCollection.updateOne(
      { _id: userId },
      { $set: { score: updatedScore }, $addToSet: { solved: testName }
    } // Update score and add testName to solved array
    );
  } catch (error) {
    console.log("Error updating user score:", error);
    throw error;
  }
}

module.exports = {getUser, DeleteUser, updateUserScore};

// /src/models/appmodel/testmodel/MainDashboardModel.js
const MainModel = require('../MainModel.js');

async function generateTestList(){
  const mainModule = new MainModel();

```

```

    await mainModule.connect();

    const client = await mainModule.getAppDataCollection();

    try {
        const cursor = client.find({});

        const data = await cursor.toArray();

        return data;
    } catch (error) {
        console.log("Error finding user details:", error);
        return null;
    }
}

module.exports = { generateTestList };
// /src/models/ProfileModel.js

const MainModel = require('./MainModel.js');

async function getUser(userId) {
    const mainModule = new MainModel();
    await mainModule.connect();
    const userCollection = await mainModule.getUserCollection();

    try {
        const user = await userCollection.findOne({ _id: userId });
        // console.log("model" , user);
        return user;
    } catch (error) {
        console.log("Error finding user details:", error);
        return null;
    }
}

async function DeleteUser(userId) {
    const mainModule = new MainModel();
    await mainModule.connect();
    const userCollection = await mainModule.getUserCollection();

    try {
        // Delete the user document from the collection based on the userId
        const result = await userCollection.deleteOne({ _id: userId });

        if (result.deletedCount === 1) {
            return "DeleteSuccess";
        } else {

```

```

        return "DeleteFailed";
    }
} catch (error) {
    console.log("Error deleting user:", error);
    return null;
}
}

async function updateUserScore(userId, newScore, testName, prevScore)
{
    const mainModule = new MainModel();
    await mainModule.connect();
    const userCollection = await mainModule.getUserCollection();
    console.log(userId, newScore, testName, prevScore);
    const updatedScore = prevScore + newScore;
    console.log("Updated Score: ", updatedScore);
    try {
        await userCollection.updateOne(
            { _id: userId },
            { $set: { score: updatedScore }, $addToSet: { solved: testName } }
        );
    } catch (error) {
        console.log("Error updating user score:", error);
        throw error;
    }
}
}

```

```

module.exports = {getUser, DeleteUser, updateUserScore};

```

```

// /src/ models/appmodel/MainDashboardModel.js

```

```

const { generateTestList } =
require("../models/appmodel/MainDashboardModel");

exports.getTestList = async (req, res) => {
    try {
        const data = await generateTestList();
        const formattedData = [];

        for (let i = 0; i < data.length; i++) {
            const { testName, testDescription, totalNoOfQuestion } = data[i];
            formattedData.push({
                testName: testName,
                testDesc: testDescription,
                totalNoOfQues: totalNoOfQuestion
            });
        }
        // console.log(formattedData);
    }
}

```

```

        return res.json(formattedData);
    } catch (error) {
        console.log("Error:", error);
        return res.status(500).json({ error: "Internal Server Error" });
    }
}

// src/controllers/LoginRegisterController.js
const { LoginUser } = require('../models/LoginModel');
const { RegisterUser } = require('../models/RegisterModel');

function generateToken(userId) {
    const newToken = userId + Math.random().toString(36).substring(2, 15);
    console.log("New Token Generated - ", newToken);
    return newToken;
}

exports.register = async (req, res) => {
    let { username, registerNumber, password } = req.body;
    registerNumber = parseInt(registerNumber);
    console.log("Register END-POINT Hit:", username, registerNumber, password);

    try {
        let user = await LoginUser(registerNumber, password);
        if (user) {
            console.log("User already exists:", user.username, registerNumber);
            return res.json({ message: 'User already exists.', username: user.username, registerNumber: registerNumber });
        } else {
            user = await RegisterUser(username, registerNumber, password);
            if (user) {
                console.log("Signup Success:", username, registerNumber);
                return res.json({ message: "Signup Success", username: username, registerNumber: registerNumber });
            } else {
                console.log("Signup Fail. Try again:", username);
                return res.json({ message: "Signup Fail. Try again.", username: username, registerNumber: -1 });
            }
        }
    } catch (error) {
        console.log('...Register ERROR...');
        res.status(500).json({ message: 'Signup Fail. Try again.' });
    }
};

exports.login = async (req, res) => {
    let { registerNumber, password } = req.body;
    registerNumber = parseInt(registerNumber);

```

```

console.log("Login END-POINT Hit:", registerNumber, password);
try {
  const user = await LoginUser(registerNumber);
  if (user) {
    if (user.password === password) {
      console.log("User:", user._id, "Login Success at", new Date());
      const token = generateToken(user._id);
      res.cookie('token', token, { httpOnly: true });
      return res.json({ message: 'Login successful', username:
user.username, registerNumber: user._id, token: token });
    } else {
      console.log("User:", user._id, "Incorrect Password ", new Date());
      return res.json({ message: 'Incorrect Username or *Password'});
    }
  } else {
    console.log("User:", user._id, "User Not Found ", new Date());
    return res.json({ message: 'Incorrect *Username or Password'});
  }
} catch (error) {
  console.log("Login API-END POINT Error ", new Date());
  res.status(500).json({ message: 'Server Error.'});
}
};

// /src/controllers/ProfileController.js
const {getUser, DeleteUser, updateUserScore} =
require("../models/appmodel/ProfileModel");

exports.getUserDetails = async (req, res) => {
  let { userId } = req.query; // Use req.query to get parameters from the
URL
  userId = parseInt(userId);
  console.log("getUserDetails END-POINT Hit:", userId);

  try {
    const user = await getUser(userId); // Call getUserDetails function
with userId
    // console.log(user);
    if (!user) {
      return res.status(404).json({ message: "User not found" });
    }

    const data = {
      username: user.username,
      registerNumber: user._id,
      score: user.score,
      courseCount: user.solved.length, // Corrected to use array.length
      courseList: user.solved
    }
  }
}

```

```

    };
    // console.log(data);
    return res.json(data);
  } catch (error) {
    console.log("Error retrieving user details:", error);
    return res.status(500).json({ message: "Internal server error" });
  }
};

```

```

exports.deleteAccount = async (req, res) => {
  let { userId } = req.query; // Use req.query to get parameters from the URL
  userId = parseInt(userId);
  console.log("getUserDetails END-POINT Hit:", userId);
  // Call the function to delete the user account based on the userId
  const result = await DeleteUser(userId);

  if (result === "DeleteSuccess") {
    return res.json({ message: "DeleteSuccess" });
  } else {
    return res.status(500).json({ message: "Failed to delete user account" });
  }
};

```

```

exports.updateUserScore = async (req, res) => {
  let { userId, score, testName, prevScore } = req.query; // Extract userId, score, and testName from request query parameters
  userId = parseInt(userId);
  score = parseInt(score);
  prevScore = parseInt(prevScore);
  console.log(userId, score, testName, prevScore);
  try {
    await updateUserScore(userId, score, testName, prevScore); // Call updateUserScore function with userId, score, and testName
    return res.status(200).json({ message: "User score updated successfully" });
  } catch (error) {
    console.log("Error updating user score:", error);
    return res.status(500).json({ message: "Internal server error" });
  }
};

```

```

// /src/controllers/TestController.js
const { getQuestionSet } =
require("../models/appmodel/testmodel/TestModel");

```




```

exports.testData = async (req, res) => {
  const data = req.query;
  console.log("Test Request: ", data.testName);
  try {
    const questionSet = await getQuestionSet(data.testName);
    // console.log(questionSet);
    if (questionSet) {
      return res.json({questionSet});
    } else {
      console.log("No question set found for test name: ${testName}");
      return res.json({message: `No question set found for test name: ${testName}`});
    }
  } catch (error) {
    console.error('Error retrieving question set:', error);
  }
}

```



Sample Input and Output:




The screenshot shows a web browser window titled "Exam App — Mozilla Firefox". The address bar displays "localhost:3000". The browser's bookmark bar includes links to "IET", "G", "GH", "SSN", "Cloud", "Placement", "Project", "SM", "FC", "P&V", "Dev Tool", "Guitar", "GC", "SSN NLP Disaster Twe...", and "Other Bookmarks".


The main content area displays a login form with the following elements:

- Login** (Section Header)
- Register Number:** A text input field containing the value "3122215001041".
- Password:** A text input field with masked characters "*****".
- Login** (A green button)
- Don't have an account? [Sign up](#)






PROFILE



Name: karthikeyan A
Registration Number: 3122215001041
Score: 0
Courses Completed: 0
Course Lists:

[Delete Account](#)



Time Remaining: 9:18

NodeJS

Test your foundational knowledge of HTML with this beginner-level assessment.

What is Node.js?

- ☒ A frontend framework
- ☐ A backend framework
- ☐ A database management system
- ☐ A programming language

Which package manager is commonly used with Node.js?

- ☒ npm
- ☐ pip
- ☐ yarn
- ☐ composer



Which module is used to create a web server in Node.js?

- ☒ http
- ☐ fs
- ☐ url
- ☐ path

Which keyword is used to import modules in Node.js?

- ☒ import
- ☐ require
- ☐ use
- ☐ include

Which method is used to read user input from the command line in Node.js?



Best Practices:

- Design before coding
- Incremental coding
- Usage of proper naming convention
- Usage of Comments to the code
- Indentation of code