

题目描述 | 题解 | 提交记录

### 175. Combine Two Tables

已解答

简单 | 相关标签 | 相关企业

[SQL Schema](#) > [Pandas Schema](#) >

Table: Person

| Column Name | Type    |
|-------------|---------|
| personId    | int     |
| lastName    | varchar |
| firstName   | varchar |

personId is the primary key (column with unique values) for this table.  
This table contains information about the ID of some persons and their first and last names.

代码

MySQL | 智能模式

```
1 # Write your MySQL query statement below
2
3
4 select firstName, lastName, city, state
5 from Person a1
6 left join Address a2 on a1.personId = a2.personId
```

176. Second Highest Salary

已解答

中等 | 相关标签 | 相关企业

[SQL Schema](#) > [Pandas Schema](#) >

Table: Employee

| Column Name | Type |
|-------------|------|
| id          | int  |
| salary      | int  |

id is the primary key (column with unique values) for this table.  
Each row of this table contains information about the salary of an employee.

代码

MySQL | 智能模式

```
1 # Write your MySQL query statement below
2
3
4 SELECT
5     IFNULL(
6         (select distinct salary as SecondHighestSalary
7          from Employee
8          order by salary desc
9          limit 1 offset 1),
10    NULL) AS SecondHighestSalary
```

1757. Recyclable and Low Fat Products

已解答

简单 | 相关标签 | 相关企业

[SQL Schema](#) > [Pandas Schema](#) >

Table: Products

| Column Name | Type |
|-------------|------|
| product_id  | int  |
| low_fats    | enum |
| recyclable  | enum |

product\_id is the primary key (column with unique values) for this table.  
low\_fats is an ENUM (category) of type ('Y', 'N') where 'Y' means this product is low fat and 'N' means it is not.  
recyclable is an ENUM (category) of types ('Y', 'N') where 'Y' means this product is recyclable and 'N' means it is not.

代码

MySQL | 智能模式

```
1 # Write your MySQL query statement below
2
3
4 select product_id
5 from Products
6 where low_fats = "Y"
7 and recyclable = "Y"
8
9
```

## 181. Employees Earning More Than Their Managers 已解答

简单相关标签相关企业🔍

[SQL Schema](#) > [Pandas Schema](#) >

Table: Employee

| Column Name | Type    |
|-------------|---------|
| id          | int     |
| name        | varchar |
| salary      | int     |
| managerId   | int     |

id is the primary key (column with unique values) for this table.

Each row of this table indicates the ID of an employee, their name, salary, and the ID of their manager.

MySQL 智能模式

```
1 # Write your MySQL query statement below
2
3 select a1.name as Employee
4 from Employee a1
5 left join Employee a2 on a1.managerId = a2.id
6 where a1.salary > a2.salary
```

## 180. Consecutive Numbers 已解答

中等相关标签相关企业🔍

[SQL Schema](#) > [Pandas Schema](#) >

Table: Logs

| Column Name | Type    |
|-------------|---------|
| id          | int     |
| num         | varchar |

In SQL, id is the primary key for this table.

id is an autoincrement column starting from 1.

MySQL 智能模式

```
1 # Write your MySQL query statement below
2
3 select distinct a.num as ConsecutiveNums
4 from Logs a
5 left join Logs b on a.id = b.id-1
6 left join Logs c on b.id = c.id-1
7 where a.num = b.num
8 and b.num = c.num
9
```

Find all numbers that appear at least three times consecutively.

Return the result table in **any order**.

## 196. Delete Duplicate Emails 已解答

简单相关标签相关企业🔍

[SQL Schema](#) > [Pandas Schema](#) >

Table: Person

| Column Name | Type    |
|-------------|---------|
| id          | int     |
| email       | varchar |

id is the primary key (column with unique values) for this table.

Each row of this table contains an email. The emails will not contain uppercase letters.

MySQL 智能模式

```
1 # Write your MySQL query statement below
2
3 delete p1
4 from person p1
5 join person p2 on p1.email = p2.email
6 where p1.id > p2.id
```

已存储

测试用例

测试结果

### 183. Customers Who Never Order

简单🔗 相关标签🏢 相关企业🔖 A

[SQL Schema](#) > [Pandas Schema](#) >

Table: Customers

| Column Name | Type    |
|-------------|---------|
| id          | int     |
| name        | varchar |

id is the primary key (column with unique values) for this table.

Each row of this table indicates the ID and name of a customer.

MySQL ▾ · 智能模式

```
1 # Write your MySQL query statement below
2
3
4 select name as Customers
5 from Customers a
6 left join Orders b on a.id = b.customerId
7 where b.id is null
```

### 584. Find Customer Referee

简单🔗 相关标签🏢 相关企业💡 提示🔖 A

[SQL Schema](#) > [Pandas Schema](#) >

Table: Customer

| Column Name | Type    |
|-------------|---------|
| id          | int     |
| name        | varchar |
| referee_id  | int     |

In SQL, id is the primary key column for this table.

Each row of this table indicates the id of a customer, their name, and the id of the customer who referred them.

MySQL ▾ · 智能模式

```
1 # Write your MySQL query statement below
2
3
4 select name
5 from Customer
6 where referee_id != 2 or referee_id is null
```

### 595. Big Countries

简单🔗 相关标签🏢 相关企业🔖 A

[SQL Schema](#) > [Pandas Schema](#) >

Table: World

| Column Name | Type    |
|-------------|---------|
| name        | varchar |
| continent   | varchar |
| area        | int     |
| population  | int     |
| gdp         | bigint  |

name is the primary key (column with unique values) for this table.

Each row of this table gives information about the name of a country, the continent to which it belongs, its area, the population, and its GDP value.

MySQL ▾ · 智能模式

```
1 # Write your MySQL query statement below
2
3
4 select name, population, area
5 from World
6 where area >= 3000000
7 or population >= 25000000
```

### 184. Department Highest Salary

中等相关标签相关企业文

[SQL Schema](#) > [Pandas Schema](#) >

Table: Employee

| Column Name  | Type    |
|--------------|---------|
| id           | int     |
| name         | varchar |
| salary       | int     |
| departmentId | int     |

id is the primary key (column with unique values) for this table.

departmentId is a foreign key (reference columns) of the ID from the Department table.

Each row of this table indicates the ID, name, and salary of an employee. It also contains the ID of their department.

MySQL 智能模式

```
2
3
4
5 select c.name as Department
6      ,a.name as Employee
7      ,a.salary
8
9 from Employee a
10 join (select departmentId, max(salary) as salary
11      from Employee
12      group by departmentId) b
13 on a.departmentId = b.departmentId
14 and a.salary = b.salary
15 left join Department c on a.departmentId = c.id
16
17
18
```

已存储

### 596. Classes With at Least 5 Students

简单相关标签相关企业文

[SQL Schema](#) > [Pandas Schema](#) >

Table: Courses

| Column Name | Type    |
|-------------|---------|
| student     | varchar |
| class       | varchar |

(student, class) is the primary key (combination of columns with unique values) for this table.

Each row of this table indicates the name of a student and the class in which they are enrolled.

MySQL 智能模式

```
1 # Write your MySQL query statement below
2
3
4 select class
5 from Courses
6 group by class
7 having count(distinct student) >= 5
```