

homework4 - sql

题目描述

题解

通过

提交记录

175. Combine Two Tables

已解答

简单 相关标签 相关企业

SQL Schema Pandas Schema

Table: Person

Column Name	Type
personId	int
lastName	varchar
firstName	varchar

personId is the primary key (column with unique values) for this table.

This table contains information about the ID of some persons and their first and last names.

Table: Address

Column Name	Type
addressId	int
personId	int
city	varchar
state	varchar

</> 代码

MySQL 智能模式

```
1 # Write your MySQL query statement below
2 select firstName, lastName, city, state
3 from Person left join Address
4 on Person.personId = Address.personId
5
6
7
8
9
10
```

已存储

测试用例 测试结果

通过 执行用时: 126 ms

Case 1

输入

Person =

personId	lastName	firstName
1	Wang	Allen
2	Alice	Bob

题目描述

通过

题解

提交记录

1757. Recyclable and Low Fat Products

已解答

简单 相关标签 相关企业

SQL Schema Pandas Schema

Table: Products

Column Name	Type
product_id	int
low_fats	enum
recyclable	enum

product_id is the primary key (column with unique values) for this table.

low_fats is an ENUM (category) of type ('Y', 'N') where 'Y' means this product is low fat and 'N' means it is not.

recyclable is an ENUM (category) of types ('Y', 'N') where 'Y' means this product is recyclable and 'N' means it is not.

Write a solution to find the ids of products that are both low fat and recyclable.

239 340 9 人在线

</> 代码

MySQL 智能模式

```
1 # Write your MySQL query statement below
2 select product_id from Products
3 where low_fats = 'Y' and recyclable = 'Y'
```

已存储

测试用例 测试结果

通过 执行用时: 84 ms

Case 1

输入

Products =

product_id	low_fats	recyclable
0	Y	N
1	Y	Y
2	N	Y
3	Y	Y
4	N	N

📖 题目描述

🔄 通过 ×

🧑 题解

📝 提交记录

181. Employees Earning More Than Their Managers

已解答

简单

🏷️ 相关标签

🏢 相关企业

🗖️

SQL Schema >

Pandas Schema >

Table: Employee

Column Name	Type
id	int
name	varchar
salary	int
managerId	int

id is the primary key (column with unique values) for this table.

Each row of this table indicates the ID of an employee, their name, salary, and the ID of their manager.

Write a solution to find the employees who earn more than their managers.

Return the result table in **any order**.

The result format is in the following example.

👍 814

💬 1.5K

☆

🔗

?

3 人在线

</> 代码

MySQL ▾ • 智能模式

```
1 SELECT e.name AS Employee
2 FROM Employee AS e
3 JOIN Employee AS m
4 ON e.managerId = m.id
5 WHERE e.salary > m.salary
```

📁 已存储

✅ 测试用例

> 测试结果

通过 执行用时: 84 ms

✅ Case 1

输入

Employee =

id	name	salary	managerId
1	Joe	70000	3
2	Henry	80000	4
3	Sam	60000	null
4	Max	90000	null

📖 题目描述

🔄 通过 ×

🧑 题解

📝 提交记录

196. Delete Duplicate Emails

已解答

简单

🏷️ 相关标签

🏢 相关企业

🗖️

SQL Schema >

Pandas Schema >

Table: Person

Column Name	Type
id	int
email	varchar

id is the primary key (column with unique values) for this table.

Each row of this table contains an email. The emails will not contain uppercase letters.

Write a solution to **delete** all duplicate emails, keeping only one unique email with the smallest `id`.

For SQL users, please note that you are supposed to write a `DELETE` statement and not a `SELECT` one.

For Pandas users, please note that you are supposed to modify `Person` in place.

After running your script, the answer shown is the `Person` table. The driver

👍 918

💬 1.5K

☆

🔗

?

4 人在线

</> 代码

MySQL ▾ • 智能模式

```
1 DELETE p1
2 FROM Person AS p1
3 JOIN Person AS p2
4 ON p1.email = p2.email
5 AND p1.id > p2.id
```

📁 已存储

✅ 测试用例

> 测试结果

通过 执行用时: 96 ms

✅ Case 1

输入

Person =

id	email
1	john@example.com
2	bob@example.com
3	john@example.com

183. Customers Who Never Order

已解答

简单 相关标签 相关企业 文A

SQL Schema > Pandas Schema >

Table: Customers

Column Name	Type
id	int
name	varchar

id is the primary key (column with unique values) for this table.

Each row of this table indicates the ID and name of a customer.

Table: Orders

Column Name	Type
id	int
customerId	int

id is the primary key (column with unique values) for this table.

576 1.2K ☆ 2 人在线

代码 通过 ×

MySQL 智能模式

```
1 SELECT c.name AS Customers
2 FROM Customers AS c
3 LEFT JOIN Orders AS o
4   ON c.id = o.customerId
5 WHERE o.id IS null;
```

已存储

测试用例 测试结果

通过 执行用时: 129 ms

Case 1

输入

Customers =

id	name
1	Joe
2	Henry
3	Sam
4	Max

题目描述

通过

题解

提交记录

584. Find Customer Referee

已解答

简单 相关标签 相关企业 提示

SQL Schema Pandas Schema

Table: Customer

Column Name	Type
id	int
name	varchar
referee_id	int

In SQL, id is the primary key column for this table. Each row of this table indicates the id of a customer, their name, and the id of the customer who referred them.

Find the names of the customer that are either:

1. referred by any customer with id != 2.

2. not referred by any customer.

Return the result table in any order.

The result format is in the following example.

362

559

6 人在线

</> 代码

MySQL 智能模式

```
1 SELECT name
2 FROM Customer
3 WHERE referee_id != 2 OR referee_id IS null;
```

已存储

测试用例

测试结果

通过 执行用时: 90 ms

Case 1

输入

Customer =

id	name	referee_id
1	Will	null
2	Jane	null
3	Alex	2
4	Bill	null

题目描述

正在判题

题解

提交记录

595. Big Countries

已解答

简单 相关标签 相关企业

SQL Schema Pandas Schema

Table: World

Column Name	Type
name	varchar
continent	varchar
area	int
population	int
gdp	bigint

name is the primary key (column with unique values) for this table. Each row of this table gives information about the name of a country, the continent to which it belongs, its area, the population, and its GDP value.

A country is big if:

it has an area of at least three million (i.e., 3000000 km²), or

it has a population of at least twenty-five million (i.e., 25000000).

448

815

4 人在线

</> 代码

MySQL 智能模式

```
1 SELECT name, population, area
2 FROM World
3 WHERE area >=3000000 OR population >=25000000;
```

已存储

测试用例

测试结果

通过 执行用时: 150 ms

Case 1

输入

World =

name	continent	area	population	gdp
Afghanistan	Asia	652230	25500100	20343000000
Albania	Europe	28748	2831741	12960000000
Algeria	Africa	2381741	37100000	188681000000
Andorra	Europe	468	78115	3712000000
Angola	Africa	1246700	20609294	100990000000

596. Classes With at Least 5 Students

已解答 ✓

简单

🏷️ 相关标签

🏢 相关企业

🔖

[SQL Schema](#) >
 [Pandas Schema](#) >

Table: Courses

Column Name	Type
student	varchar
class	varchar

(student, class) is the primary key (combination of columns with unique values) for this table.
Each row of this table indicates the name of a student and the class in which they are enrolled.

Write a solution to find all the classes that have **at least five students**.

Return the result table in **any order**.

The result format is in the following example.

Example 1:

Input:

373

811

☆

📄

?

1 人在线

</> 代码

MySQL ▾ • 智能模式

```

1 SELECT class
2 FROM Courses
3 GROUP BY class
4 HAVING COUNT(*) >=5;
    
```

🔒 已存储

☒ 测试用例 |
 >_ 测试结果

通过 执行用时: 132 ms

✅ Case 1

输入

Courses =

student	class
A	Math
B	English
C	Math
D	Biology
E	Math

题目描述通过 × 题解提交记录

176. Second Highest Salary

已解答

中等

相关标签

相关企业

文

SQL Schema > Pandas Schema >

Table: Employee

Column Name	Type
id	int
salary	int

id is the primary key (column with unique values) for this table.
Each row of this table contains information about the salary of an employee.

Write a solution to find the second highest **distinct** salary from the `Employee` table. If there is no second highest salary, return `null` (return `None` in Pandas).

The result format is in the following example.

Example 1:

1.6K

2K

☆

🔗

?

6 人在线

</> 代码

MySQL 智能模式

```
1 SELECT MAX(salary) AS SecondHighestSalary
2 FROM Employee
3 WHERE salary < (
4     SELECT MAX(salary)
5     FROM Employee
6 );
```

已存储

测试用例

> 测试结果

通过 执行用时: 119 ms

Case 1

Case 2

输入

Employee =

id	salary
1	100
2	200
3	300

题目描述通过 × 题解提交记录

180. Consecutive Numbers

已解答

中等

相关标签

相关企业

文

SQL Schema > Pandas Schema >

Table: Logs

Column Name	Type
id	int
num	varchar

In SQL, id is the primary key for this table.
id is an autoincrement column starting from 1.

Find all numbers that appear at least three times consecutively.

Return the result table in **any order**.

The result format is in the following example.

Example 1:

Input:
Logs table:

1K

1.8K

☆

🔗

?

4 人在线

</> 代码

MySQL 智能模式

```
1 SELECT DISTINCT a.num AS ConsecutiveNums
2 FROM Logs AS a
3 JOIN Logs AS b
4     ON b.id = a.id + 1
5 JOIN Logs AS c
6     ON c.id = b.id + 1
7 WHERE a.num = b.num
8     AND b.num = c.num;
```

已存储

测试用例

> 测试结果

通过 执行用时: 91 ms

Case 1

输入

Logs =

id	num
1	1
2	1
3	1
4	2
5	1

184. Department Highest Salary

已解答

[中等](#)
[相关标签](#)
[相关企业](#)

[SQL Schema](#)
[Pandas Schema](#)

Table: Employee

Column Name	Type
id	int
name	varchar
salary	int
departmentId	int

id is the primary key (column with unique values) for this table.

departmentId is a foreign key (reference columns) of the ID from the Department table.

Each row of this table indicates the ID, name, and salary of an employee. It also contains the ID of their department.

Table: Department

Column Name	Type
-------------	------

774

1.7K



3 人在线

代码

MySQL • 智能模式

```

5 JOIN (
6     SELECT departmentId, MAX(salary) AS max_salary
7     FROM Employee
8     GROUP BY departmentId
9 ) AS highest
10 ON e.departmentId = highest.departmentId
11 AND e.salary = highest.max_salary
12 JOIN Department AS d
13 ON e.departmentId = d.id;
    
```

已存储

[测试用例](#)
[测试结果](#)

通过 执行用时: 136 ms

Case 1

输入

Employee =

id	name	salary	departmentId
1	Joe	70000	1
2	Jim	90000	1
3	Henry	80000	2
4	Sam	60000	2
5	Max	90000	1