

# KKluaverb Package Documentation

Kosei Kawaguchi a.k.a. KKTeX

Version 1.5.0 (2026/01/12)

目次

1     Outline ..... 3

2     Acknowledgements / Credit ..... 3

3     Usage ..... 3

     3.1     Basical Useage ..... 3

     3.2     In Verbatim Environments ..... 3

     3.3     Optional Useage ..... 3

# 1 Outline

The `KKluaverb` is a LaTeX package which provides a Lua-enhanced `\verb` command, `\KKverb`. It can be used in the table of contents, index, underline commands (e.g., `\underlineKK` provided by the `luwa-ul` package), `tblr` environment and so on.

## 2 Acknowledgements / Credit

In developing this package, I made use of an algorithm which is used in “`bxcrawstr`” (by Takayuki YATO)<sup>1)</sup>.

## 3 Usage

### 3.1 Basical Useage

As mentioned in the “Outline” seciton, this package mainly provides enhanced `\verb` command. The usage is not much different from the normal one.

Input
<code>\KKverb \def\TEST{Test Text.} </code>
Output
<code>\def\TEST{Test Text.}</code>

### 3.2 In Verbatim Environments

When this package is loaded, the Lua-sccaning which enables `\KKverb` to detokenize its argument is activated. However, when `\KKverb` used in verbatim environments such as “listings” and “`tcblisting`”, the argument cannot be decoded properly. In such cases, you should use `\KKvScanOff` which deactivates the sccaning process used internally in `KKverb.lua`. Of course, `\KKvScanOn` re-activetes the process.

### 3.3 Optional Useage

In addition to the main function of `\KKverb`, some optional funcions are provided.

---

1) package: <https://gist.github.com/zr-tex8r/c7901658a866adfdc3cd66b6dfa86997>  
article: <https://zrbabbler.hatenablog.com/entry/20181222/1545495849>

`\KKvOpChange` can change font and color of the output of `\KKverb`. Also, it can activate or deactivate the scanner. The usage is as follows:

Input

```
1 {\KKvOpChange{color=blue, font=\gtfamily, enabled=true}%
2 \KKverb|\def\TEST{Test Text.}|}
```

Output

```
\def\TEST[Test Text.]
```

表 1: Default Values of `\KKvOpChange`

Key	Default Value	Description
font	<code>\ttfamily</code>	Sets the font for the verbatim text.
color	<code>color</code>	Sets the text color (requires <code>xcolor</code> ).
enabled	<code>true</code>	Activates or deactivates the scanning engine.