

keisenote Package Documentation

Kosei Kawaguchi a.k.a. KKTeX

Version 1.0.4 (2025/10/04)

Contents

1	Acknowledgements / Credit	2
2	Installation	2
3	Package options	2
4	Package options	2
5	Commands	4
5.1	<code>\notefill</code>	4
5.2	<code>\note</code>	4
5.3	<code>\masumefill</code>	5
5.4	<code>\masume</code>	5
6	Package Parameters	6
7	Examples	6
7.1	Short Note Block	6
7.2	Full Page Fill	7
8	License	8
9	Version History	8
10	Source Code	8

1 Acknowledgements / Credit

This package is based on the code from [VoD's Qiita article](#), with some improvements. The original author has kindly granted permission to release this as a LaTeX package.

2 Installation

Place `keisennote.sty` in a directory where LaTeX can find it, e.g., your local `texmf` tree or alongside your document.

Dependencies:

- `xcolor`
- `tikz`
- `zref`, `zref-savepos`, `fp`
- `kvoptions`

Load the package:

```
\usepackage{keisennote}
```

3 Package options

4 Package options

This package accepts key–value style options at load time. The option handling is powered by `kvoptions`, with `family=kn` and `prefix=kn@`. All options are declared as string options (accepting any TeX length expression) and are applied during `\ProcessKeyvalOptions*`. The available options and their default values are listed below.

Option name	Default value	Description
<code>linewidth</code>	<code>.5truept</code>	Width of the line used for note drawing. The value is assigned internally to <code>\noteLineWidth</code> . Any T _E X length (e.g. <code>1pt</code> , <code>0.6truept</code> , <code>0.2mm</code>) is accepted.
<code>radius</code>	<code>.8truept</code>	Radius of each dot. Internally stored in <code>\dotsRadius</code> .
<code>distance</code>	<code>6truemm</code>	Spacing between adjacent dots. Internally stored in <code>\noteLineDistance</code> .
<code>triangle</code>	<code>.5pt</code>	Size of triangular markers. Internally stored in <code>\VoD@mag</code> .

Internal behaviour

- Each option is first stored as a string macro (e.g. `\kn@linewidth`), as imposed by `\DeclareStringOption`. The package then assigns it to a `\dimen` register, for example:

```

\noteLineWidth=\kn@linewidth\relax
\dotsRadius=\kn@radius\relax
\noteLineDistance=\kn@distance\relax
\VoD@mag=\kn@triangle\relax

```

This conversion ensures that user-supplied expressions such as `1truept` or `0.5mm` are properly interpreted as lengths.

- If the package does not perform this assignment automatically, users may do so manually; however, in normal usage this is handled internally.

Examples

- Specify options at package load:

```

\usepackage[linewidth=1truept, radius=.6truept, distance=8
truemm]{keisenote}

```

- Modify options afterwards using `\setkeys`:

```

\setkeys{kn}{linewidth=0.8pt, distance=5mm}
\noteLineWidth=\kn@linewidth\relax % reassign to internal
registers if needed

```

Remarks

- Absolute units such as `truept` / `truemm` are used as defaults to avoid driver-dependent scaling.
- No range checks are performed on the option values. Excessively small or negative values may lead to undesirable results. If required, minimum-value guards can be implemented via `\ifdim`.

5 Commands

5.1 `\notefill`

`\notefill[<color>]`

Fills the current vertical space with ruled notebook lines and dots.

Example:

`\notefill[green]`

5.2 `\note`

`\note{<lines>}[<color>]`


Typesets a short ruled block with a specified number of lines.

- `<lines>` (mandatory, integer ≥ 2): number of ruled lines.
- `<color>` (optional, default: `white!70!black`): color of lines and dots.

Example:

`\note{5}[NavyBlue]`

This produces the following output.



Inserting `\bigskip` before (and after) using the `\note` command can sometimes improve the appearance.

5.3 `\masumefill`

`\masume[<color>]`

Fills the current vertical space with grids and dots.

- `<color>` (optional, default: white!70!black): color of lines and dots.

Example:

`\notefill[Gray]`

5.4 `\masume`

`\masume{<lines>}[<color>]`


Typesets a short grid block with a specified number of lines.

- `<lines>` (mandatory, integer ≥ 2): number of ruled lines.
- `<color>` (optional, default: white!70!black): color of lines and dots.

Example:

`\masume{5}[NavyBlue]`

This produces the following output.



Inserting `\bigskip` before (and after) using the `\masume` command can sometimes improve the appearance.

6 Package Parameters

These dimensions can be adjusted:

\SetNoteLineWidth You can set the width of note lines : `\SetNoteLineWidth[2mm]`

\SetNoteDotRadius You can set the radius of dots. : `\SetNoteDotRadius[1pt]`

\SetNoteLineDistance You can set the distance between each lines.
: `\SetNoteLineDistance[7mm]`

\SetNoteTriangleSize You can set the size of triangles. : `\SetNoteTriangleSiz[1pt]`

If no argument is given, the parameter is reset to its default value.

7 Examples


7.1 Short Note Block

`\note{4}`



7.2 Full Page Fill

`\notefill`



8 License

Released under the [LaTeX Project Public License \(LPPL\) 1.3c](#).

9 Version History

- **v1.0.0 (2025/09/13)** — Initial public release.
- **v1.0.3 (2025/09/13)** — KKT_ε added `\masume` and `\masumefill`.
- **v1.0.4 (2025/10/4)** — KKT_ε fixed the problem in `\masumefill` and added some package options and setting commands.

10 Source Code

```
\ProvidesPackage{keisennote}[2025/10/04, v1.0.4]

\RequirePackage[dvipsnames, svgnames, x11names]{xcolor}
\RequirePackage{zref, zref-savepos, fp}
\RequirePackage{tikz}

\RequirePackage{kvoptions}

\SetupKeyvalOptions{%
  family=kn,%
  prefix=kn@%
}

\newdimen\noteLineWidth
\noteLineWidth=.5truept

\newdimen\dotsRadius
\dotsRadius=.8truept

\newdimen\noteLineDistance
\noteLineDistance=6truemm

\newdimen\VoD@mag
\VoD@mag=.5pt

%%%
\DeclareStringOption[.5truept]{linewidth}%
```

```

\DeclareStringOption[.8truept]{radius}%
\DeclareStringOption[6truemm]{distance}%
\DeclareStringOption[.5pt]{triangle}%

\ProcessKeyvalOptions* %

%%%
\setlength{\noteLineWidth}{\kn@linewidth}
\setlength{\dotsRadius}{\kn@radius}
\setlength{\noteLineDistance}{\kn@distance}
\setlength{\VoD@mag}{\kn@triangle}

%%%
\NewDocumentCommand{\SetNoteLineWidth}{0{.5truept}}{%
  \setlength{\noteLineWidth}{#1}
}
\NewDocumentCommand{\SetNoteDotRadius}{0{.8truept}}{%
  \setlength{\dotsRadius}{#1}
}
\NewDocumentCommand{\SetNoteLineDistance}{0{6truemm}}{%
  \setlength{\noteLineDistance}{#1}
}
\NewDocumentCommand{\SetNoteTriangleSize}{0{.5pt}}{%
  \setlength{\VoD@mag}{#1}
}

%%%
\newdimen\VDNT@currentXPos
\newdimen\VDNT@currentYPos
\newdimen\VDNT@Xinterval
\newdimen\VDNT@Yinterval
\newdimen\VDNT@notegoal

%%% \notefill
\def\VDNT@pkgname{vodnote}
\global\newcount\VDNT@unique

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

%%% \notefill
\NewDocumentCommand{\notefill}{0{white!70!black}}{\par\bgroup

```

```

\parindent\z@
%%
\@tempcnta\linewidth
\@tempcntb\noteLineDistance
\FPeval\VDNT@dotsNum{round(round((\the)\@tempcnta/(\the)\@tempcntb)/2:0)*2:0}}%
\VDNT@Xinterval\dimexpr(\linewidth)/\VDNT@dotsNum\relax
\VDNT@Yinterval\VDNT@Xinterval
%%
\zsaveposy{\VDNT@pkgname.\the\VDNT@unique.TopPos}%
%%
\leavevmode\vfill\leavevmode
\zsaveposy{\VDNT@pkgname.\the\VDNT@unique.BottomPos}%
%%
\VDNT@notegoal=\dimexpr
\zposy{\VDNT@pkgname.\the\VDNT@unique.TopPos}sp
-\zposy{\VDNT@pkgname.\the\VDNT@unique.BottomPos}sp
\relax
%%
\noindent\smash{%
\begin{tikzpicture}[xscale=0.996]
\VDNT@currentYPos\z@
\fill[#1] (\VDNT@Xinterval*\VDNT@dotsNum/2,\VDNT@currentYPos+\VoD@mag*4pt) -- ++(\VoD@mag*3pt,-\VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) -- cycle;
\@whiledim\VDNT@currentYPos<\VDNT@notegoal\do{
\VDNT@currentXPos\z@
\draw[#1,line width=\noteLineWidth] (0,\VDNT@currentYPos)
-- (\linewidth,\VDNT@currentYPos);
\foreach \k in{0,1,...,\VDNT@dotsNum}{%
\VDNT@currentXPos=\dimexpr\VDNT@Xinterval*\k\relax
\fill[#1] (\VDNT@currentXPos,\VDNT@currentYPos) circle
[radius=\dotsRadius];
}
\advance\VDNT@currentYPos\VDNT@Yinterval\relax
}
\fill[#1] (\VDNT@Xinterval*\VDNT@dotsNum/2,\VDNT@currentYPos-\VDNT@Yinterval-\VoD@mag*4pt) -- ++(\VoD@mag*3pt,\VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) -- cycle;
\end{tikzpicture}}%
}%
\egroup

```

```

%%
\global\advance\VDNT@unique\@ne
\par
}

%%% \note
\NewDocumentCommand{\note}{ m O{white!70!black} }{\par\bgroup

%%
\@tempcnta\linewidth
\@tempcntb\noteLineDistance
\FPeval\VDNT@dotsNum{round(round(((\the)\@tempcnta/(\the)\@tempcntb)/2:0)*2:0)}%
\VDNT@Xinterval\dimexpr\linewidth/\VDNT@dotsNum\relax
\VDNT@Yinterval\VDNT@Xinterval
%%
\noindent
\begin{tikzpicture}[xscale=0.996]
\VDNT@currentYPos\z@
\fill[#2] (\VDNT@Xinterval*\VDNT@dotsNum/2,\VDNT@currentYPos+\VDNT@Yinterval+\VoD@mag*4pt) -- ++(\VoD@mag*3pt,-\VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) -- cycle; %
\foreach \i in{1,2,...,#1}{
\VDNT@currentXPos\z@
\global\VDNT@currentYPos=\dimexpr\VDNT@Yinterval*\i\relax
\draw[#2,line width=\noteLineWidth] (0,\VDNT@currentYPos) -- (\linewidth,\VDNT@currentYPos);
\foreach \k in{0,1,...,\VDNT@dotsNum}{
\VDNT@currentXPos=\dimexpr\VDNT@Xinterval*\k\relax
\fill[#2] (\VDNT@currentXPos,\VDNT@currentYPos) circle [radius=\dotsRadius];
}
}
\fill[#2] (\VDNT@Xinterval*\VDNT@dotsNum/2,\VDNT@currentYPos-\VoD@mag*4pt) -- ++(\VoD@mag*3pt,\VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) -- cycle; %
\end{tikzpicture}%
\egroup
\par
}

```

%%%

```

\NewDocumentCommand{\masumefill}{ 0{white!70!black} }{\par\
  bgroup
  \parindent\z@
  %%
  \@tempcnta\linewidth
  \@tempcntb\noteLineDistance
  \FPeval\VDNT@dotsNum{round(round(((\the)\@tempcnta/(\the)\
    @tempcntb)/2:0)*2:0)}%
  \VDNT@Xinterval\dimexpr(\linewidth)/\VDNT@dotsNum\relax
  \VDNT@Yinterval\VDNT@Xinterval
  %%
  \zsaveposy{\VDNT@pkgname.\the\VDNT@unique.TopPos}%
  %%
  \leavevmode\vfill\leavevmode
  \zsaveposy{\VDNT@pkgname.\the\VDNT@unique.BottomPos}%
  %%
  \VDNT@notegoal=\dimexpr
    \zposy{\VDNT@pkgname.\the\VDNT@unique.TopPos}sp
    -\zposy{\VDNT@pkgname.\the\VDNT@unique.BottomPos}sp
  \relax
  %%
  \noindent\smash{%
    \begin{tikzpicture}[xscale=0.996]
      \VDNT@currentYPos\z@
      \fill[#1] (\VDNT@Xinterval*\VDNT@dotsNum/2,\
        VDNT@currentYPos+\VoD@mag*4pt) -- ++(\VoD@mag*3pt,-\
        VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) -- cycle;
      \@whiledim\VDNT@currentYPos<\VDNT@notegoal\do{
        \VDNT@currentXPos\z@
        \draw[#1,line width=\noteLineWidth] (0,\VDNT@currentYPos)
          -- (\linewidth,\VDNT@currentYPos);
        \foreach \k in{0,1,...,\VDNT@dotsNum}{%
          \VDNT@currentXPos=\dimexpr\VDNT@Xinterval*\k\relax
          \draw[#1,line width=\noteLineWidth]
            (\VDNT@currentXPos,0) -- (\VDNT@currentXPos,\
              VDNT@currentYPos);
          \fill[#1] (\VDNT@currentXPos,\VDNT@currentYPos) circle
            [radius=\dotsRadius];
        }
        \advance\VDNT@currentYPos\VDNT@Yinterval\relax

```

```

    }
    \fill[#1] (\VDNT@Xinterval*\VDNT@dotsNum/2,\
      VDNT@currentYPos-\VDNT@Yinterval-\VoD@mag*4pt) -- ++(\
      VoD@mag*3pt,\VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) --
      cycle;
    \end{tikzpicture}%
  }%
\egroup
%%
\global\advance\VDNT@unique\@ne
\par
}

\NewDocumentCommand{\masume}{ m O{white!70!black} }{\par\bgroup

%%
\@tempcnta\linewidth
\@tempcntb\noteLineDistance
\FPeval\VDNT@dotsNum{round(round(((\the)\@tempcnta/(\the)\
  @tempcntb)/2:0)*2:0)}%
\VDNT@Xinterval\dimexpr\linewidth/\VDNT@dotsNum\relax
\VDNT@Yinterval\VDNT@Xinterval
%%
\noindent
\begin{tikzpicture}[xscale=0.996]
  \VDNT@currentYPos\z@
  \fill[#2] (\VDNT@Xinterval*\VDNT@dotsNum/2,\
    VDNT@currentYPos+\VDNT@Yinterval+\VoD@mag*4pt) -- ++(\
    VoD@mag*3pt,-\VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) --
    cycle; %
  \foreach \i in{1,2,...,#1}{
    \VDNT@currentXPos\z@
    \global\VDNT@currentYPos=\dimexpr\VDNT@Yinterval*\i\relax
    \draw[#2,line width=\noteLineWidth] (0,\VDNT@currentYPos)
      -- (\linewidth,\VDNT@currentYPos);
    \foreach \k in{0,1,...,\VDNT@dotsNum}{
      \VDNT@currentXPos=\dimexpr\VDNT@Xinterval*\k\relax
      \draw[#2,line width=\noteLineWidth] (\VDNT@currentXPos
        ,\VDNT@Yinterval) -- (\VDNT@currentXPos,\
        VDNT@Yinterval*#1);
      \fill[#2] (\VDNT@currentXPos,\VDNT@currentYPos) circle
        [radius=\dotsRadius];
    }
  }

```

```

    }
  }
  \fill[#2] (\VDNT@Xinterval*\VDNT@dotsNum/2,\
    VDNT@currentYPos-\VoD@mag*4pt) -- ++(\VoD@mag*3pt,\
    VoD@mag*4pt) -- ++(-\VoD@mag*6pt,0) -- cycle;    %
\end{tikzpicture}%
\egroup
\par
}

\endinput

```