KCD Seoul 2025

ArgoCD와 함께하는 Multi-Cluster 운영


김태지 | Technical Architect

웨어포인트




rlaxowl5460@gmail.com https://linkedin.com/in/taejikim (LinkedIn) https://kkamji.net (Blog)


Background



Argo Project History



Argo CD 란?



GitOps 기반 지속적 배포(CD) 도구

- Pull 기반 재조정(Reconciliation)
 Git을 단일 기준 저장소로 삼아 주기적 동기화, 커밋 기준 롤백
- 선언적 구성 지원 Helm, Kustomize, YAML, Jsonnet 등 표준 도구를 그대로 사용
- 드리프트 감지와 자동 복구
 Diff/Health 확인, Auto-Prune와 Self-Heal로 원하는 상태 유지
- 커밋 단위 롤백과 감사 추적
 Git History 기반으로 특정 시점으로 롤백 및 변경 기록 보존
- 멀티클러스터 & 멀티테넌시 ApplicationSet과 Projects, RBAC으로 대규모 환경을 일관적으로 운영

GitOps 4대 원칙

GitOps Principles

v1.0.0

Declarative

A system managed by GitOps must have its desired state expressed declaratively.

Versioned and Immutable

Desired state is stored in a way that enforces immutability, versioning and retains a complete version history.


Pulled Automatically

Software agents automatically pull the desired state declarations from the source.

Continuously Reconciled

Software agents continuously observe actual system state and attempt to apply the desired state.


Argo CD 배포 과정



Preview


선언적으로 Application 생성

One Manifest = One Application (1:1)




App of Apps Pattern

One Root App = Many Applications (1:N)



ApplicationSet


One Manifest = Many Applications (1:N)



Application 선언적으로 생성하기



어디에 있는 어떤 Application을? 어떤 클러스터에? 어떤 옵션으로?



HEAD [2]

helm [4]


TARGET REVISION

SYNC OPTIONS

PATH


App of Apps Pattern

```
apiVersion: argoproj.io/v1alpha1
kind: Application
metadata:
  name: kcd-2025-root-east
 namespace: argord
  finalizers:
    - resources-finalizer.argocd.argoproj.io
spec:
  project: kcd-2025
  source:
    repoURL: https://github.com/KKamJi98/kcd-2025.git
    targetRevision: HEAD
    path: argocd/app-of-apps/east
    directory:
      recurse: true
  destination:
    server: https://kubernetes.default.svc
    namespace: argocd
  syncPolicy:
    automated:
      prune: true
      selfHeal: true
    syncOptions:
      - CreateNamespace=true
      ServerSideApply=true
      - PrunePropagationPolicy=foreground
     - PruneLast=true
```




App of Apps Pattern - Sync Wave

```
apiVersion: argoproj.io/v1alpha1
    kind: Application
    metadata:
      name: kcd-2025-east-phase1
      namespace: argord
      annotations:
        argocd.argoproj.io/sync-wave: "0"
      finalizers:
        resources-finalizer.argocd.argoproj.io
    spec:
      project: kcd-2025
      source:
        repoURL: https://github.com/KKamJi98/kcd-2025.git
        path: helm
        targetRevision: HEAD
        helm:
          releaseName: app-of-apps-phase1
          parameters:
           - name: prefix
              value: kcd
            - name: region
              value: east
            - name: replicaCount
              value: "3"
      destination:
        name: kcd-east
        namespace: kcd
      syncPolicy:
        automated:
          prune: true
          selfHeal: true
        syncOptions:
         CreateNamespace=true
          ServerSideApply=true
          - PrunePropagationPolicy=foreground
          - PruneLast=true
```




App of Apps Pattern – Sync Hook


```
.
    apiVersion: batch/v1
     kind: Job
    metadata:
      name: east-wave0-delay
      namespace: argocd
       annotations:
        argocd.argoproj.io/hook: Sync
        argocd.argoproj.io/hook-delete-policy: HookSucceeded
        argocd.argoproj.io/sync-wave: "0"
       backoffLimit: 0
       template:
        spec:
          restartPolicy: Never
          containers:
            - name: sleep
              image: busybox:1.36
              imagePullPolicy: IfNotPresent
              command: ["sh", "-c", "sleep 10"]
    apiVersion: batch/v1
    kind: Job
    metadata:
      name: east-wave1-delay
      namespace: argocd
       annotations:
        argocd.argoproj.io/hook: Sync
        argocd.argoproj.io/hook-delete-policy: HookSucceeded
        argocd.argoproj.io/sync-wave: "1"
    spec:
       backoffLimit: 0
       template:
        spec:
          restartPolicy: Never
          containers:
            - name: sleep
               image: busybox:1.36
              imagePullPolicy: IfNotPresent
              command: ["sh", "-c", "sleep 10"]
```



ApplicationSet (하나의 선언으로 N개의 Application을 생성)



Demo 환경 소개



Demo

https://github.com/KKamJi98/kcd-2025

Summary

- GitOps의 네 가지 핵심 원칙
 선언적 구성 · Git 버전관리 · 자동 Pull · 지속적 동기화
- Argo CD 배포 과정
 Git 저장소 → Repo Server → Application Controller → 대상 클러스터
- Application 선언적으로 구성
 YAML Manifest로 원하는 상태를 정의하고 GitOps로 관리
- App of Apps Pattern
 Root Application으로 여러 애플리케이션을 그룹화, Sync Wave 및 Sync Hook을 통한 배포 순서 제어
- ApplicationSet 하나의 Manifest로 멀티 클러스터/멀티 앱 자동 생성 및 일관성 유지

KCD Seoul 2025

ArgoCD와 함께하는 Multi-Cluster 운영

김태지 | Technical Architect

웨어포인트



rlaxowl5460@gmail.com https://linkedin.com/in/taejikim (LinkedIn) https://kkamji.net (Blog)