

1. feladat:

```
mint@mint: ~  
File Edit View Search Terminal Help  
To run a command as administrator (user "root"), use "sudo <command>".  
See "man sudo_root" for details.  
  
mint@mint:~$ mkdir gyumolcs  
mint@mint:~$ cd gyumolcs  
mint@mint:~/gyumolcs$ mkdir bokor  
mint@mint:~/gyumolcs$ cd bokor  
mint@mint:~/gyumolcs/bokor$ mkdir malna  
mint@mint:~/gyumolcs/bokor$ mkdir mogyoro  
mint@mint:~/gyumolcs/bokor$ mkdir szilva  
mint@mint:~/gyumolcs/bokor$ cd ..  
mint@mint:~/gyumolcs$ mkdir fa  
mint@mint:~/gyumolcs$ cd fa  
mint@mint:~/gyumolcs/fa$ mkdir alma  
mint@mint:~/gyumolcs/fa$ cd ..  
mint@mint:~/gyumolcs$ mkdir fold  
mint@mint:~/gyumolcs$ cd fold  
mint@mint:~/gyumolcs/fold$ mkdir eper  
mint@mint:~/gyumolcs/fold$ mkdir gesztenye  
mint@mint:~/gyumolcs/fold$ cd  
mint@mint:~$ ls  
Desktop Documents Downloads Music Pictures Public Templates Videos gyumolcs  
mint@mint:~$ cd gyumolcs  
mint@mint:~/gyumolcs$ ls  
bokor fa fold  
mint@mint:~/gyumolcs$ cd bokor  
mint@mint:~/gyumolcs/bokor$ ls  
malna mogyoro szilva  
mint@mint:~/gyumolcs/bokor$ cd ..  
mint@mint:~/gyumolcs$ cd fa  
mint@mint:~/gyumolcs/fa$ ls  
alma  
mint@mint:~/gyumolcs/fa$ cd ..  
mint@mint:~/gyumolcs$ cd fold  
mint@mint:~/gyumolcs/fold$ ls  
eper gesztenye  
mint@mint:~/gyumolcs/fold$ cd
```

2. Feladat:

```
mint@mint: ~  
File Edit View Search Terminal Help  
To run a command as administrator (user "root"), use "sudo <command>".  
See "man sudo_root" for details.  
  
mint@mint:~$ cp -r gyumolcs/fold/eper gyumolcs/fa  
mint@mint:~$ cp -r gyumolcs/bokor/malna gyumolcs/fa  
mint@mint:~$
```

3. feladat:

```
mint@mint: ~  
File Edit View Search Terminal Help  
        than the destination file or when the  
        destination file is missing  
-v, --verbose      explain what is being done  
-Z, --context      set SELinux security context of destination  
                   file to default type  
--help            display this help and exit  
--version          output version information and exit  
  
The backup suffix is '~', unless set with --suffix or SIMPLE_BACKUP_SUFFIX.  
The version control method may be selected via the --backup option or through  
the VERSION_CONTROL environment variable. Here are the values:  
  
none, off          never make backups (even if --backup is given)  
numbered, t        make numbered backups  
existing, nil       numbered if numbered backups exist, simple otherwise  
simple, never       always make simple backups  
  
GNU coreutils online help: <https://www.gnu.org/software/coreutils/>  
Report mv translation bugs to <https://translationproject.org/team/>  
Full documentation at: <https://www.gnu.org/software/coreutils/mv>  
or available locally via: info '(coreutils) mv invocation'  
mint@mint:~$ mv gyumolcs/bokor/szilva gyumolcs/fa  
mint@mint:~$ mv gyumolcs/fold/gesztenye gyumolcs/fa  
mint@mint:~$
```

4. feladat:

```
mint@mint: ~  
File Edit View Search Terminal Help  
-d, --dir          remove empty directories  
-v, --verbose      explain what is being done  
--help            display this help and exit  
--version          output version information and exit  
  
By default, rm does not remove directories. Use the --recursive (-r or -R)  
option to remove each listed directory, too, along with all of its contents.  
  
To remove a file whose name starts with a '-', for example '-foo',  
use one of these commands:  
    rm -- -foo  
  
    rm ./-foo  
  
Note that if you use rm to remove a file, it might be possible to recover  
some of its contents, given sufficient expertise and/or time. For greater  
assurance that the contents are truly unrecoverable, consider using shred.  
  
GNU coreutils online help: <https://www.gnu.org/software/coreutils/>  
Report rm translation bugs to <https://translationproject.org/team/>  
Full documentation at: <https://www.gnu.org/software/coreutils/rm>  
or available locally via: info '(coreutils) rm invocation'  
mint@mint:~$ rm -r gyumolcs/fold  
mint@mint:~$
```

4.-5. feladat:

```
mint@mint: ~/gyumolcs/bokor/malna
File Edit View Search Terminal Help
To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

mint@mint:~$ cd gyumolcs
mint@mint:~/gyumolcs$ cd bokor
mint@mint:~/gyumolcs/bokor$ cd malna
mint@mint:~/gyumolcs/bokor/malna$ cat > leiras.txt

Dunantul egyes reszein elterjedt nepies magyar neve a Boldogasszony csipkeje
Kb. 2 m magas felcserje.
Levelei 3-5, ritkan 7 taguak, felul simak, alul gyapjasak, szeluk fureszfogas.
```

```
mint@mint: ~/gyumolcs/fa
File Edit View Search Terminal Help
To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

mint@mint:~$ cd gyumolcs
mint@mint:~/gyumolcs$ cd fa
mint@mint:~/gyumolcs/fa$ cat > felsorolas.txt

alma
korte
szilva
cseresznye
meggy
```