

Algorithms and datastructures Exercises

Kristoffer Klokke

2022

Contents

6	Uge	4
6.1	Indicate the following according to figure 1.	4
6.1.a	The attributes of each realtion	4
6.1.b	The tuples of each realtion	4
6.1.c	The components of one tube of each realtion	5
6.1.d	The relation schema of each realtion	5
6.1.e	The database schema	5
6.1.f	A suitable domain of each attribute	5
6.1.g	Another equivalent way to present each relation.	5
6.2	In a table with the following attributes which are valid example of keys	6
6.3	How many ways can relation be represented if it has:	6
6.3.a	Four attributes and five tuples	6
6.3.b	n attributes and m tuples	6
6.4	Write a database schema of the following relations	6
6.4.a	Write a schema for <i>Product</i>	6
6.4.b	Write a schema for <i>PC</i>	6
6.4.c	Write a schema for <i>Printer</i>	7
6.4.d	Write an alternation for Printer and delete the attribute color	7
6.4.e	Add an <i>od</i> attribute for PC, which defaults to none an otherwise can be cd or dvd	7
7	Uge	7
7.1	Working with linear notation	7
7.1.a	PC models which have speed of at least 3.00?	7
7.1.b	PC manufacturers which makes PC with a hdd with at least 100GB	7
7.1.c	Find model and price of all products made by manufacturer <i>B</i>	8
7.1.d	Find model numbers of all color laster printers	8
7.1.e	Find manufactures that sell Laptops but not PC	8
7.1.f	Find hd size which accour in two or more PC's	8
7.2	In the following data, what is the result of $\pi_{speed}(PC)$ when treated as a bag and set	9
8	Week	10
8.1	What are the expexted FD's in the following database and what key would it have	10

8.2	Consider the relation with schema $R(A, B, C, D)$ and FD's $AB \rightarrow C, C \rightarrow D, D \rightarrow A$	10
8.2.a	What are all the nontrivial FD's that follow from the given FD's? You should restrict yourself to FD's with single attributes on the righth side	10
8.2.b	What are all the keys of R	10
8.2.c	What are all the superkeys for R that is not keys? . . .	11
8.3	Find BCNF violations and decompose the schema	11
8.3.a	$R(A, B, C, D)$ with $AB \rightarrow C, C \rightarrow D$, and $D \rightarrow A$. .	11
8.3.b	$R(A, B, C, D, E)$ and $AB \rightarrow C, DE \rightarrow C, B \rightarrow D$. . .	11
8.4	Perform the chase method on the relations $R(A, B, C), R(B, C, D), R(A, C, E)$ using the given FD's	11
8.4.a	$B \rightarrow E$ and $CE \rightarrow A$	11
8.4.b	$A \rightarrow D, D \rightarrow E$ and $B \rightarrow D$	12
8.5	The following exercise is on the relation $Courses(C, T, H, R, S, G)$	12
8.5.a	What are all the keys for $Courses$	12
8.5.b	Verify that the given FD's are their own minimal basis	12
8.5.c	Make the relation into a 3NF and check if any BCNF violation occurs	12
9	Week	13
9.1	Create a ER diagram from the given information	13
9.2	Create a ER diagram from the given information	13
9.3	Create a ER diagram from the given information	13
9.4	Create a relation schema from the given diagram	13
9.5	Create a relation using the different methods, from the given diagram	14
9.5.a	Straight E/R model	15
9.5.b	The object oriented	15
9.5.c	The null method	15

6 Uge

6.1 Indicate the following according to figure 1.

<i>acctNo</i>	<i>type</i>	<i>balance</i>
12345	savings	12000
23456	checking	1000
34567	savings	25

The relation **Accounts**

<i>firstName</i>	<i>lastName</i>	<i>idNo</i>	<i>account</i>
Robbie	Banks	901-222	12345
Lena	Hand	805-333	12345
Lena	Hand	805-333	23456

The relation **Customers**

Figure 1: Two relations of a banking database

6.1.a The attributes of each relation

Accounts: *acctNo*, *type*, *balance*

Customers: *firstName*, *lastName*, *idNo*, *account*

6.1.b The tuples of each relation

- 12345, *savings*, 12000
- 23456, *checking*, 1000
- 34567, *savings*, 25

- *Robbie, Banks*, 901 – 222, 12345
- *Lena, Hand*, 805 – 333, 12345
- *Lena, Hand*, 805 – 333, 23456

6.1.c The components of one tuple of each relation

12000

Banks

6.1.d The relation schema of each relation

Accounts(*acctNo*, *type*, *balance*)

Customers(*firstName*, *lastName*, *idNo*, *account*)

6.1.e The database schema

Accounts, *Customers*

6.1.f A suitable domain of each attribute

- *acctNo* - *INT*
- *type* - *VARCHAR*[20]
- *balance* - *INT*
- *firstName* - *VARCHAR*[20]
- *lastName* - *VARCHAR*[20]
- *idNo* - *CHAR*[7]
- *account* - *INT*

6.1.g Another equivalent way to present each relation.

The attributes could simply just be in a different order.

6.2 In a table with the following attributes which are valid example of keys

title, year, length, genre, studioName, producerC#

- title, year
- title, year, studioName
- title, length
- length, genre, studioName, year

6.3 How many ways can relation be represented if it has:

6.3.a Four attributes and five tuples

$$4! \cdot 5! = 2880$$

6.3.b n attributes and m tuples

$$n! \cdot m!$$

6.4 Write a database schema of the following relations

The database schema includes

Product(*make, model, type*)

PC(*model, speed, ramhd, price*)

Laptop(*model, speed, ram, hd, screen, price*)

Printer(*model, color, type, price*)

6.4.a Write a schema for *Product*

```
CREATE TABLE Product(VARCHAR[20] maker, INT model, INT type)
```

The type is here an int where 0 is PC, 1 is laptop and 2 is printer. There is no foreign keys due to it being the lookup table for the other relations

6.4.b Write a schema for *PC*

```
CREATE TABLE PC(INT model, FLOAT speed, INT ram, BOOLEAN hd,  
FLOAT prize, FOREIGN KEY(Products) REFERENCES Products(model))
```

Here the model is a reference to products, speed is gigahertz of CPU

6.4.c Write a schema for *Printer*

```
CREATE TABLE Printer(INT model, BOOLEAN color, VARCHAR[20]  
type, FLOAT price, FOREIGN KEY(Products) REFERENCES Products(model))
```

6.4.d Write an alternation for *Printer* and delete the attribute *color*

```
ALTER TABKE Printer DROP color
```

6.4.e Add an *od* attribute for *PC*, which defaults to none an otherwise can be *cd* or *dvd*

```
ALTER TABLE PC ADD VARCHAR[20] od DEFAULT 'none'
```

7 Uge

7.1 Working with linear notation

The following exercises uses the following schema:

Product(*maker*, *model*, *type*)

PC(*model*, *speed*, *ram*, *hd*, *price*)

Laptop(*model*, *speed*, *ram*, *hd*, *screen*, *price*)

Printer(*model*, *color*, *type*, *price*)

7.1.a PC models which have speed of at least 3.00?

$$\pi_{model}(\sigma_{speed > 3.00}(PC))$$

7.1.b PC manufacturers which makes PC with a hdd with at least 100GB

$$\pi_{maker}(Product \bowtie \sigma_{hd \geq 100}(PC))$$

7.1.c Find model and price of all products made by manufacturer B

$$\begin{aligned}
man &:= \sigma_{maker=B}(Product) \\
PCModelPrice &:= \pi_{model,price}(man \bowtie PC) \\
LaptopModelPrice &:= \pi_{model,price}(man \bowtie Laptop) \\
PrinterModelPrice &:= \pi_{model,price}(man \bowtie Printer) \\
modPrice &:= PCModelPrice \cup LaptopModelPrice \cup PrinterModelPrice
\end{aligned}$$

7.1.d Find model numbers of all color laser printers

$$\pi_{model}(Product \bowtie \sigma_{color=1 \wedge Dtype=laser}(Printer))$$

7.1.e Find manufactures that sell Laptops but not PC

Due to algebra not including a method for group by I have answered in form of SQL queries.

SELECT (SELECT maker FROM LAPTOP NATURAL JOIN Product GROUP BY maker) - (SELECT maker FROM PC NATURAL JOIN Product GROUP BY maker)

7.1.f Find hd size which accour in two or more PC's

$$\begin{aligned}
PC &= \pi_{model,hd}(PC) \\
PC2(model2, hd) &= \pi_{model,hd}(PC) \\
hd &= \pi_{hd}(\sigma_{model \neq model}(PC \bowtie PC2))
\end{aligned}$$

7.2 In the following data, what is the result of $\pi_{speed}(PC)$ when treated as a bag and set

model	speed	ram	hd	price
1001	2.66	1024	250	2114
1002	2.10	512	250	995
1003	1.42	512	80	478
1004	2.80	1024	250	649
1005	3.20	512	250	630
1006	3.20	1024	320	1049
1007	2.20	1024	200	510
1008	2.20	2048	250	770
1009	2.00	1024	250	650
1010	2.80	2048	300	770
1011	1.86	2048	160	959
1012	2.80	1024	160	649
1013	3.06	512	80	529

Bag

speed
2.66
2.10
1.42
2.80
3.20
3.20
2.20
2.20
2.00
2.80
1.86
2.80
3.06

Set

speed
2.66
2.10
1.42
2.80
3.20
2.20
2.00
2.80
1.86
3.06

8 Week

8.1 What are the expected FD's in the following database and what key would it have

- name
- Social Security number
- street address
- city
- state
- ZIP code
- area code
- phone number

Social Security number \rightarrow name, street address, city, state, ZIP code, area code

phone number \rightarrow name key: Social security number, phone number

8.2 Consider the relation with schema $R(A, B, C, D)$ and FD's $AB \rightarrow C, C \rightarrow D, D \rightarrow A$

8.2.a What are all the nontrivial FD's that follow from the given FD's? You should restrict yourself to FD's with single attributes on the right side

$AB \rightarrow C$

$C \rightarrow D$

$D \rightarrow A$

ABD

$C \rightarrow A$

8.2.b What are all the keys of R

$AB^+ = \{C, D\}$

$C^+ = \{A, D\}$

$D^+ = \{A\}$

$BC^+ = \{D, A\}$

$BD^+ = \{A, C\}$
 AB, BC, DC

8.2.c What are all the superkeys for R that is not keys?

BC, BD

8.3 Find BCNF violations and decompose the schema

8.3.a $R(A, B, C, D)$ with $AB \rightarrow C$, $C \rightarrow D$, and $D \rightarrow A$

$AB^+ = \{C, D, A\}$ - violation.

$R_1 = R - AB^+ + AB = R(A, B)$

$R_2 = AB^+ = R_2(A, C, D)$

8.3.b $R(A, B, C, D, E)$ and $AB \rightarrow C, DE \rightarrow C, B \rightarrow D$

Starts with the original relation

$R(A, B, C, D, E)$

The table violates ABC

$AB^+ = \{C, D\}$

$R_1 = R - AB^+ = R(A, B, E)$

$R_2 = AB^+ + AB = R(A, B, C, D)$

But R_2 violates $B \rightarrow D$

$B^+ = \{D\}$

$R_3 = R_2 - B^+ = R(A, B, C)$

$R_4 = B^+ + B = R(B, D)$

Therefore the new relations are R_1, R_3, R_4 , since none now violates BCNF.

8.4 Perform the chase method on the relations $R(A, B, C), R(B, C, D), R$ using the given FD's

8.4.a $B \rightarrow E$ and $CE \rightarrow A$

A, B, C, D_1, E_1

A_2, B, C, D, E_2

A, B_3, C, D_3, E

$E_1 = E_2 - B \rightarrow E$

$A_2 = A - CE_1 \rightarrow A$

$E_1 = E - CE \rightarrow A$

Therefore on line two is now

A, B, C, D, E

8.4.b $A \rightarrow D, D \rightarrow E$ and $B \rightarrow D$

A, B, C, D_1, E_1

A_2, B, C, D, E_2

A, B_3, C, D_3, E

$D_1 = D - B \rightarrow D$

$A_2 = A - A \rightarrow D$

$D_3 = D - A \rightarrow D$

$E_1 = E - D \rightarrow E$

8.5 The following exercise is on the relation $Courses(C, T, H, R, S, G)$

The relation has the following FD's

$C \rightarrow T$

$HR \rightarrow C$

$HT \rightarrow R$

$HS \rightarrow R$

$CS \rightarrow G$

8.5.a What are all the keys for $Courses$

The candidate keys are:

$CSH^+ = \{T, G, R\}$

$SHR^+ = \{C, T, G\}$

8.5.b Verify that the given FD's are their own minimal basis

$C^+ = \{T\}$

$HR^+ = \{C, T\}$

$HT^+ = \{R, C\}$

$HS^+ = \{R, C, T\}$

$CS^+ = \{G, T\}$

As it can be seen no one of the FD's closure result in another FD, therefore making it minimal.

8.5.c Make the relation into a 3NF and check if any BCNF violation occurs

$R1(C, T)$

$R2(H, R, C, T)$

$R3(H, T, R, C)$

$R4(H, S, R, C, T)$

$R5(C, S, G, T)$

$R2$ violates BCNF due to $HT \rightarrow R$, the same with $R3$ due to HR FD.

9 Week

9.1 Create a ER diagram from the given information




Figure 2: ER diagram describing a bank scenario

9.2 Create a ER diagram from the given information




Figure 3: ER diagram describing a course and student enrollment

9.3 Create a ER diagram from the given information

9.4 Create a relation schema from the given diagram

Customer(SSNO primary, phone, addr, name)

Flights(number primary, day primary, aircraft)

Bookings(SSNo primary, number primary, day primary, row, seat)






Figure 4: ER diagram describing a department and course situation with a weak key



9.5 Create a relation using the different methods, from the given diagram



9.5.a Straight E/R model

Courses(room,number primary)
Depts(name primary, chair)
GivenBy(number primary, name primary)
LabCourses(number primary, computerAllo)

9.5.b The object oriented

The same as Depts, GivenBy and Courses but...
LavCourses(number primary, room, CcomputerAllo)

9.5.c The null method

The same Depts and Given by but...
LabCourses(number primary, room, computerAllo)

10 Week

Create the following functions in Java The functions are used on:

Product(maker, model, type)
PC(model, speed, ram, hd, price)

10.0.a Given speed and RAM, find PC's model number

```
import java.sql.*;
```

```
Class.forName("org.postgresql.Driver"); //For postgresql envirement  
String url = "jdbc:postgresql://" + host + "[:" + port + "]/" + databa  
Connection myCon = DriverManager.getConnection(URL, username, password  
  
public static ArrayList<String> findModel(int speed, int ram) {  
    Statement stat = myCon.createStatement("SELECT_model_FROM_PC_W  
    ResultSet res = stat.executeQuery();  
    ArrayList<String> models = new ArrayList<>();  
    while(res.next())  
        models.add(res.getString(0));  
    return models;  
}
```

10.0.b Given a model number, remove the tuple

```
public static void removeModel(String model) {
    Statement stat = myCon.createStatement();
    stat.executeUpdate("REMOVE_FROM_PC_WHERE_model='" + model + "'");
    Statement stat2 = myCon.createStatement();
    stat2.executeUpdate("REMOVE_FROM_Products_WHERE_model='" + model + "'");
    myCon.commit();
}
```

10.0.c Decrease price of PC to 100 given model

```
public static void updatePrice(String model) {
    Statement stat = myCon.createStatement();
    stat.executeUpdate("UPDATE_PC_SET_price=100_WHERE_model='" + model + "'");
    myCon.commit();
}
```

10.0.d Given all info for a PC check if model number exist if not insert

```
public static void tryInsert(String model, int speed, int ram, int hd,
    Statement stat = myCon.createStatement("SELECT_model_FROM_PC_WHERE_model='" + model + "'");
    ResultSet res = stat.executeQuery();
    if(res != null) {
        System.out.println("Model_already_exist");
        return;
    }
    Statement stat = myCon.createStatement();
    stat.executeUpdate("INSERT_INTO_PC_VALUES('"+model+"', '"+speed+"', '"+ram+"', '"+hd+"')");
    myCon.commit();
}
```

10.0.e Ask the user for a price and print maker, model and speed of PC

```
import java.util.Scanner;
Scanner sc = new Scanner(System.in);

public static void closestPrice() {
```



```

        System.out.println("Wanted_price?");
        int wantedPrice = sc.nextInt();
        int closestPrice = 0;
        String closestModel;
        Statement stat = myCon.createStatement("SELECT_price ,_model_FROM Pro");
        ResultSet res = stat.executeQuery();
        while(res.next()) {
            int price = res.getInt(0);
            if(Math.abs(wantedPrice - closestPrice) > Math.abs(wantedPrice - price)) {
                closestPrice = price;
                model = res.getString(1);
            }
        }
        Statement stat2 = myCon.createStatement("SELECT_maker_FROM Pro");
        String maker = stat2.executeQuery().getString(0);
        System.out.println("The_closest_PC_to_the_price_is:_"+ model + "by "+ maker);
    }
}

```

10.0.f Ask for minimum speed, RAM, hdd and screen, and print all compatible laptops plus maker

```

public static void findLaptop() {
    System.out.println("Wanted_speed ,_RAM,_hdd_size_and_screen_size");
    int speed = sc.nextInt();
    int ram = sc.nextInt();
    int hdd = sc.nextInt();
    int screen = sc.nextInt();
    Statement stat = myCon.createStatement("SELECT_*_FROM_PC");
    ResultSet res = stat.executeQuery();
    while(res.next()) {
        int PCSpeed = res.getInt(1);
        int PCRam = res.getInt(2);
        int PCHd = res.getInt(3);
        int PCScreen = res.getInt(4);
        if(PCSpeed > speed && PCRam > ram && PCHd > hdd && PCScreen > screen) {
            String model = res.getString(0);
            Statement stat2 = myCon.createStatement("SELECT_maker_FROM_PC");
            String maker = stat2.executeQuery().getString(0);
            System.out.println("The_model:_"+model+"by "+maker);
        }
    }
}

```

```

    }
}

```

10.1 Write OSN procedues for the following tasks

```

MovieStar(name, address, gender, birtdate)
MovieExec(name, address, cert#, netWorth)
Studio(name, address, presC#)

```

10.1.a Given name of a movie studio return net worth of president

```

CREATE PROCEDURE netWorth(IN studio CHAR(15), OUT worth INT)
DECLARE foundWorth INTEGER; BEGIN SET worth = 0; set foundWorth
= SELECT netWorth FROM MovieExec WHERE cert = (SELECT presC
FROM Studio WHERE name = studio); SET worth = worth + foundWorth;
END;

```

10.1.b Given name and address, return 1 if movie star, 2 if executive producer, 3 if non, 4 if both

```

CREATE PROCEDURE title(IN n CHAR(15),IN a CHAR(15), OUT INT)
DECLARE star INTEGER; DECARE prod INTEGER; BEGIN SET star =
SELECT COUNT(name) FROM MovieStar WHERE name = n AND ad-
dress = a; SET prod = SELECT COUNT(name) FROM MovieExec WHERE
name = n AND address = a; IF(1 j= star AND 1j= prod) return 4; ELSEIF
(1 j= star) return 1; ELSEIF (1 j= prod) return 2; ELSE return 3; END IF;
END;

```