

Algorithms and datastructures Exercises

Kristoffer Klokke

2022

Contents

6	Uge	3
6.1	Indicate the following according to figure 1.	3
6.1.a	The attributes of each realtion	3
6.1.b	The tuples of each realtion	3
6.1.c	The components of one tube of each realtion	4
6.1.d	The relation schema of each realtion	4
6.1.e	The database schema	4
6.1.f	A suitable domain of each attribute	4
6.1.g	Another equivalent way to present each relation.	4
6.2	In a table with the following attributes which are valid example of keys	5
6.3	How many ways can relation be represented if it has:	5
6.3.a	Four attributes and five tuples	5
6.3.b	n attributes and m tuples	5
6.4	Write a database schema of the following relations	5
6.4.a	Write a schema for <i>Product</i>	5
6.4.b	Write a schema for <i>PC</i>	5
6.4.c	Write a schema for <i>Printer</i>	6
6.4.d	Write an alternation for Printer and delete the at- tribute color	6
6.4.e	Add an <i>od</i> attribute for PC, which defaults to none an otherwise can be cd or dvd	6

6 Uge

6.1 Indicate the following according to figure 1.

<i>acctNo</i>	<i>type</i>	<i>balance</i>
12345	savings	12000
23456	checking	1000
34567	savings	25

The relation **Accounts**

<i>firstName</i>	<i>lastName</i>	<i>idNo</i>	<i>account</i>
Robbie	Banks	901-222	12345
Lena	Hand	805-333	12345
Lena	Hand	805-333	23456

The relation **Customers**

Figure 1: Two relations of a banking database

6.1.a The attributes of each relation

Accounts: *acctNo*, *type*, *balance*

Customers: *firstName*, *lastName*, *idNo*, *account*

6.1.b The tuples of each relation

- 12345, *savings*, 12000
- 23456, *checking*, 1000
- 34567, *savings*, 25

- *Robbie, Banks*, 901 – 222, 12345
- *Lena, Hand*, 805 – 333, 12345
- *Lena, Hand*, 805 – 333, 23456

6.1.c The components of one tuple of each relation

12000

Banks

6.1.d The relation schema of each relation

Accounts(*acctNo*, *type*, *balance*)

Customers(*firstName*, *lastName*, *idNo*, *account*)

6.1.e The database schema

Accounts, *Customers*

6.1.f A suitable domain of each attribute

- *acctNo* - *INT*
- *type* - *VARCHAR*[20]
- *balance* - *INT*
- *firstName* - *VARCHAR*[20]
- *lastName* - *VARCHAR*[20]
- *idNo* - *CHAR*[7]
- *account* - *INT*

6.1.g Another equivalent way to present each relation.

The attributes could simply just be in a different order.

6.2 In a table with the following attributes which are valid example of keys

title, year, length, genre, studioName, producerC#

- title, year
- title, year, studioName
- title, length
- length, genre, studioName, year

6.3 How many ways can relation be represented if it has:

6.3.a Four attributes and five tuples

$$4! \cdot 5! = 2880$$

6.3.b n attributes and m tuples

$$n! \cdot m!$$

6.4 Write a database schema of the following relations

The database schema includes

Product(*make, model, type*)

PC(*model, speed, ramhd, price*)

Laptop(*model, speed, ram, hd, screen, price*)

Printer(*model, color, type, price*)

6.4.a Write a schema for *Product*

CREATE TABLE Product(VARCHAR[20] maker, INT model, INT type)

The type is here an int where 0 is PC, 1 is laptop and 2 is printer. There is no foreign keys due to it being the lookup table for the other relations

6.4.b Write a schema for *PC*

CREATE TABLE PC(INT model, FLOAT speed, INT ram, BOOLEAN hd, FLOAT prize, FOREIGN KEY(Products) REFERENCES Products(model))

Here the model is a reference to products, speed is gigahertz of CPU

6.4.c Write a schema for *Printer*

```
CREATE TABLE Printer(INT model, BOOLEAN color, VARCHAR[20]  
type, FLOAT price, FOREIGN KEY(Products) REFERENCES Products(model))
```

6.4.d Write an alternation for Printer and delete the attribute color

```
ALTER TABKE Printer DROP color
```

6.4.e Add an *od* attribute for PC, which defaults to none an otherwise can be cd or dvd

```
ALTER TABLE PC ADD VARCHAR[20] od DEFAULT 'none'
```