

PAG7936LT: 1 Mega Pixel Global Shutter Color Image Sensor

General Description

The PAG7936LT is an ultra-low-power global shutter color image sensor. It supports 1280 x 800 resolution and up to 120 frames per second (fps) image capture capability to output clear, low-noise images in low-light and bright scenes.

PAG7936LT's low-power architecture enables the always-on feature in the customer's applications, which is especially beneficial for the battery-powered system. The sensor is suitable for consumer products, machine vision, or industrial applications such as augmented reality (AR), virtual reality (VR), AI classification & recognition, collision avoidance, barcode applications, factory automation, etc.

PAG7936LT registers can be accessed through the standard I²C interface, while the image output is through MIPI or parallel interface.

Key Features

- Ultra-low-power consumption
- LED Strobe
- RGB Lens shading compensation
- Programmable control for
 - Frame rate
 - Mirror & Flip
 - WOI
- Supports image resolution: 1280 x 800, 640 x 400, 320 x 200
- Data format: 8-bit/10-bit RAW
- Supports I²C multi-slave ID by I/O strapping

- Auto Exposure and Gain Control
- De-noise
- Context Switch
- Fast AE

Applications


- VR/AR
- Face Recognition
- Factory Automation
- Drone/ Barcode Reader

Key Parameters

Parameter	Value
Optical Format	1/4"
Array Size	1288 x 808 pixel
Pixel Size	3.0 x 3.0 μm^2
Max. CRA	14.45 deg
Shutter Type	Global shutter
Max. Frame Rate	120 fps
Signal to Noise Ratio, SNR	36.9 dB
Dynamic Range	66 dB
Sensitivity	2751 mV/Lux-Sec at 530nm
Supply Voltage	VDDMA: 2.8V VDD12: 1.2V I/O: 1.8 to 2.8V
Power Consumption	82.3mW (1280 x 800, 120fps)
Operating Temperature, Tj	-40 to +85 °C
Stable image	0 to +65 °C
Package Dimension	5.050 x 5.470 x 0.768 mm ³

Ordering Information

Part Number	Description	Package Type	Packing Type
PAG7936LT	Global Shutter Image Sensor	Chip Scale Package	Chip Tray



For any additional inquiries, please contact us at <http://www.pixart.com>

Preliminary: This product is still under product development where the product specifications are subjected to change upon product release.