

Improving Structure with Inheritance


Chapter-8; Objects First with Java using BlueJ



The Network example

- A small, prototype social network.
- Supports a news feed with posts.
- Stores text posts and photo posts.
 - MessagePost: multi-line text message.
 - PhotoPost: photo and caption.
- Allows operations on the posts:
 - e.g., search, display and remove.

Class diagram



Network classes

MessagePost

username message timestamp likes comments

like unlike addComment getText getTimeStamp display

PhotoPost top half username shows fields filename caption timestamp likes comments like unlike addComment getImageFile getCaption bottom half getTimeStamp shows methods display

Message-Post source code

```
public class MessagePost {
   private String username;
   private String message;
   private long timestamp;
   private int likes;
   private ArrayList<String> comments;
   public MessagePost(String author, String text) {
        username = author;
        message = text;
        timestamp = System.currentTimeMillis();
        likes = 0:
        comments = new ArrayList<String>();
   public void addComment(String text) { ... }
   public void like() { ... }
   public void display() { ... }
```

```
public class PhotoPost {
   private String username;
   private String filename;
   private String caption;
   private long timestamp;
   private int likes;
   private ArrayList<String> comments;
   public PhotoPost(String author, String filename, String caption) {
         username = author;
         this.filename = filename;
         this.caption = caption;
         timestamp = System.currentTimeMillis();
         likes = 0;
         comments = new ArrayList<String>();
   public void addComment(String text) { ... }
   public void like() { ... }
   public void display() { ... }
```

NewsFeed

```
public class NewsFeed {
   private ArrayList<MessagePost> messages;
   private ArrayList<PhotoPost> photos;
   public void show() {
       for (MessagePost message : messages) {
         message.display();
         System.out.println(); // empty line between posts
       for (PhotoPost photo : photos) {
          photo.display();
         System.out.println(); // empty line between posts
```



Network objects

: MessagePost

username

message

timestamp

likes

comments

: PhotoPost

username

filename


caption

timestamp

likes

comments

Network object model






Critique of Network

- Code duplication:
 - MessagePost and PhotoPost classes very similar (large parts are identical)
 - makes maintenance difficult/more work
 - introduces danger of bugs through incorrect maintenance
- Code duplication in NewsFeed class as well.

Using inheritance





Using inheritance

- define one superclass : Post
- define <u>subclasses</u> for MessagePost and <u>PhotoPost</u>
- the superclass defines common attributes (via fields)
- the subclasses inherit the superclass attributes
- the subclasses add other attributes

Inheritance in Java

```
no change here
       public class Post {
                                         change here
                  public class PhotoPost( extends Post -
public class MessagePost extends Post {
```

Superclass

```
public class Post {
    private String username;
    private long timestamp;
    private int likes;
    private ArrayList<String> comments;

// constructor and methods omitted.
}
```

Subclasses

```
public class MessagePost extends Post {
   private String message;

   // constructor and methods omitted.
}
```

```
public class PhotoPost extends Post {
   private String filename;
   private String caption;

// constructor and methods omitted.
}
```

Inheritance Hierarchies Animal Mammal Bird Chicken Dog Sparrow Cat Dalmatian Poodle Objects First with Java - A Practical Introductio es, Michael Kölling 16

public class Post {

Inheritance & constructors

```
private String username;
private long timestamp;
private int likes;
private ArrayList<String> comments;
  Initialise the fields of the post.
public Post(String author) {
    username = author;
    timestamp = System.currentTimeMillis();
    likes = 0;
    comments = new ArrayList<String>();
// methods omitted
```

Inheritance & constructors


```
public class MessagePost extends Post {
    private String message;
     * Constructor for objects of class MessagePost
    public MessagePost(String author, String text) {
        super(author);
        message = text;
   // methods omitted
```




Superclass constructor call

- Subclass constructors must always contain a 'super' call.
- If none is written, the compiler inserts one (without parameters)
 - works only, if the superclass has a constructor without parameters
- Must be the first statement in the subclass constructor.

Adding more item types



Deeper hierarchies





Review (so far)

Inheritance (so far) helps with:

- Avoiding code duplication
- Code reuse
- Easier maintenance
- Extendibility

```
public class NewsFeed {
    private ArrayList<Post> posts;
    /**
     * Construct an empty news feed.
    public NewsFeed() {
        posts = new ArrayList<Post>();
    /**
      Add a post to the news feed.
    public void addPost(Post post) {
        posts.add(post);
```


Revised NewsFeec source code

avoids code duplication in the client class!

New NewsFeed source code

```
* Show the news feed. Currently: print the
 * news feed details to the terminal.
  (Later: display in a web browser.)
public void show() {
   for (Post post : posts) {
       post.display();
       System.out.println(); // Empty line ...
```

Improved Class diagram



Subtyping

First, we had:

```
public void addMessagePost(MessagePost message)
public void addPhotoPost(PhotoPost photo)
```

Now, we have:

```
public void addPost(Post post)
```

We call this method with:


```
PhotoPost myPhoto = new PhotoPost(...);
feed.addPost(myPhoto);
```

Subclasses and subtyping

- Classes define types.
- Subclasses define subtypes.
- Objects of subclasses can be used where objects of super-types are required.

(This is called substitution.)

Subtyping and assignment




subclass objects may be assigned to superclass variables

```
Vehicle v1 = new Vehicle();
Vehicle v2 = new Car();
Vehicle v3 = new Bicycle();
```

Subtyping & parameter passing

```
public class NewsFeed {
    public void addPost(Post post) {
                                    subclass objects
                                    may be used as
                                    actual parameters
                                   for the superclass
PhotoPost photo = new PhotoPost(...);
MessagePost message = new MessagePost(...);
NewsFeed feed = new NewsFeed();
feed.addPost(photo);
feed.addPost(message);
```

Object diagram





Polymorphic variables

• Variables in Java are polymorphic.

They can hold objects of more than one type.

 They can hold objects of the declared type, or of subtypes of the declared type.

Casting

- We can assign sub-type to super-type;
- But we cannot assign super-type to sub-type!

```
Vehicle v;
Car c = new Car();
v = c; // correct
c = v; // compile error!
```

Casting fixes this:


```
c = (Car) v;
```

(only ok if the vehicle really is a Car!)

Casting

- An object type in parentheses.
- Used to overcome 'type loss'.
- The object is not changed in any way.
- A runtime check is made to ensure the object really is of that type:
 - ClassCastException if it isn't!

The Object class





Review

- Inheritance allows the definition of classes as extensions of other classes.
- Inheritance
 - avoids code duplication
 - allows code reuse
 - simplifies the code
 - simplifies maintenance and extending
- Variables can hold subtype objects.
- Subtypes can be used wherever supertype objects are expected (substitution).



Exercise

- 8.12
- Page 294 of BlueJ



شعرامروز

ما عاشق عشقیم که عشق است نجات جان چون خضر است و عشق چون آب حیات

وای آنکه ندارد از شه عشق برات حیوان چه خبر دارد از کان نبات