

Bertini_Real

User's Manual



need a sweet picture here

Manual by
Pierce Cunneen & Daniel Brake
University of Notre Dame
ACMS

July 23, 2015

Contents

1	Introduction	1
1.1	Contact	1
1.2	License	1
2	Quick Start	2
3	Compilation and Installation	2
3.1	Installation	2
3.2	Installation of Bertini/bertini_real on macIntosh	2
4	Using Bertini_Real	3
4.1	Command Line Options	3
5	Troubleshooting	4
6	Visualization	4
7	3D Printing	4
A	Output Formats	5
A.1	.curve	5
A.2	.edge	5
A.3	.vert	5

1 Introduction

Welcome to Bertini_real, software for real algebraic geometry. This manual is intended to help the user operate this piece of numerical software, to obtain useful and high-quality results from decomposing real algebraic curves and surfaces.

Bertini_real is compiled software, links against a parallel version of Bertini 1 compiled as a library, and requires Matlab and the Symbolic Computation toolbox. It also requires several other libraries, including a few from Boost, and an installation of MPI. All libraries should be compiled using the same compilers.

1.1 Contact

Acknowledgements

- This research utilized the CSU ISTeC Cray HPC System supported by NSF Grant CNS-0923386.
- This material is based upon work supported by the National Science Foundation under Grants No. DMS-1025564 and DMS-1115668.

1.2 License

Disclaimer

Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation or any other organization.

2 Quick Start

Bertini_Real can be downloaded from <http://bertinireal.com/download.html>. Use of Bertini_Real depends on Bertini, which itself has several important dependencies (see section 3) Once installed, you can run Bertini_real on an input file from the command line. After navigating to the working directory of the input file, the flow of Bertini_real is as follows:

1. Run Bertini on an input file using the “tracktype: 1” setting. This is done by typing in the command line: `bertini` with an input file named ‘input’. Bertini will produce a Numerical Irreducible Decomposition that will be used by Bertini_real.
2. Run Bertini_Real on the same input file. Similarly, just type `bertini_real` in the command line. Bertini_Real will provide a cellular decomposition of the real portion of a one- or two-dimensional complex algebraic set.
3. Visualize the results of Bertini_real in MATLAB. Enter MATLAB and call `gather_br_samples`, which parses the output results of Bertini_real into a .mat file, and then call `bertini_real_plotter`, which will plot the curve or surface in MATLAB (N.B. The MATLAB executable must be on the path to the input file for Bertini_real to run).

3 Compilation and Installation

3.1 Installation

Before installing Bertini_real, you must first be sure to have several libraries and dependencies that the software requires.

First, you must install Bertini (as a library). The Bertini source code can be found at <https://bertini.nd.edu/download.html>. Download the Bertini source code using the `./configure && make && make install` process.

Bertini itself has the following dependencies: a C++ compiler capable of the C++ 11 standard, an MPI (such as MPICH2), Boost ≥ 1.53 , MPFR, and GMP. Instructions specifically for mac users are listed below. If on Linux, use the package manager provided (e.g. `apt-get`). Unfortunately, Windows users are unsupported at this time, except possibly through Cygwin or a virtual machine. If interested in porting Bertini and Bertini_real to windows, please contact Dr. Brake at dbrake@nd.edu. Bertini_real also is dependent on MATLAB. Once Bertini and all the necessary dependencies are installed, navigate to the directory containing Bertini_real and install Bertini_real via the `./configure && make && make install` process.

3.2 Installation of Bertini/bertini_real on macIntosh

If you are using a mac, we encourage the use of Homebrew (<http://brew.sh>) to install these packages. After installing Homebrew itself, installing the previously listed dependencies becomes simple. In terminal, just type, `brew search ----` to list packages related to ----, where ---- is your search (for example, GMP, Boost, or MPICH2). To download via Homebrew, type in terminal: `brew install ----`.

4 Using Bertini_real

4.1 Command Line Options

Below are the command line options for Bertini_real. These are placed after the initial `bertini_real` command. Each command starts with a single dash, and any required arguments should be placed after. For example, if you wanted to run Bertini_real decomposing a specific component, you would type: `bertini_real -component x` where x is the integer index of the component to decompose.

- `-debug`
If used, program will pause for 30 seconds before running for debugging purposes. No required argument.
- `-dim` or `-d`
Required argument is the target dimension for Bertini_real to shoot for
- `-component`, `-comp`, or `-c`
Required argument is the integer index of the component for Bertini_real to decompose (e.g `-component 1`)
- `-gammatrick` or `-g`
Indicator for whether Bertini_real should use the gamma trick in a particular solver. Required argument is either 1 (if you'd like Bertini_real to use the gamma trick) or 0 (if not).
- `-verb`
Required argument is the level of the verbosity you'd like to set.
- `-output`, `-out`, or `-o`
Required argument is the name of the output directory.
- `-nostifle` or `-ns`
If used, screen output will not be stifled. No required argument
- `-nomerge` or `-nm`
Indicates that Bertini_real should not merge ends. No required argument.
- `-projection`, `-pi`, or `-p`
Indicator for whether to read the projection from a file, rather than randomly choose it. Required argument is the file name.
- `-sphere` or `-s`
Sets indicator that Bertini_real should use sphere created by user rather than just compute sphere. Required argument is the name of the file for Bertini_real to read
- `-input` or `-i`
Used if input file is named something other than 'input'. Required argument is the file name.
- `-quick` or `-q`
Sets the level of quickness for the solver. The quicker the solver, the less robust it is as well.
★
- `-veryquick` or `-vq`
Sets the level of quickness for the solver. The quicker the solver, the less robust it is as well.
- `-version` or `-v`
Displays the version of Bertini_real running on your computer. Has no required argument.

Not sure the difference
between setting quick_run
value to be 1 or 2 via `-quick`
and `-veryquick`

- **-help** or **-h**
Displays a help message containing the version of Bertini_real, where Bertini_real can be found online, support information, and finally the command line options.
- **-mode** or **-m**
Sets the mode of Bertini_real to be used. Required argument is the mode of operation, and there are currently two valid modes (**bertini_real** and **crit**). **bertini_real** is the default mode.

5 Troubleshooting

6 Visualization

7 3D Printing

A Output Formats

A.1 .curve

(num_variables total) num_vertices num_edges

num_V0 num_V1 num_midpts num_newpts

indices of V0

indices of V1

indices of midpoints

indices of added_points

projection excluding the homogeneous 0 coordinate.

A.2 .edge

A.3 .vert